

[Description](#)
[Options](#)[Quick start](#)
[Remarks and examples](#)[Menu](#)
[Also see](#)[Syntax](#)

Description

`twoway fpfitci` calculates the prediction for *yvar* from estimation of a fractional polynomial of *xvar* and plots the resulting curve along with the confidence interval of the mean.

Quick start

Fractional-polynomial prediction plot of *y* on *x* with 95% confidence interval

```
twoway fpfitci y1 x
```

Same as above, with a 90% confidence interval

```
twoway fpfitci y1 x, level(90)
```

Same as above, but estimate fractional polynomial of degree 4

```
twoway fpfitci y1 x, level(90) estopts(degree(4))
```

Overlay a scatterplot

```
twoway fpfitci y1 x || scatter y x
```

Same as above, but use small circles as markers

```
twoway fpfitci y1 x || scatter y x, msymbol(o)
```

Display confidence limits as a pair of lines

```
twoway fpfitci y1 x, ciplot(rline)
```

Same as above, with an overlaid scatterplot and medium-thick line for predicted values

```
twoway fpfitci y1 x, ciplot(rline) clwidth(medthick) || scatter y1 x
```

Predictions from estimation command `logit` with binary dependent variable *y2*

```
twoway fpfitci y2 x, estcmd(logit)
```

Add “My Title” as the title of the graph

```
twoway fpfitci y1 x || scatter y x, title("My Title")
```

Menu

Graphics > Two-way graph (scatter, line, etc.)

Syntax

```
twoway fptestci yvar xvar [if] [in] [weight] [ , options]
```

options	Description
<i>fptest_options</i>	any of the options of [G-2] graph twoway fptest
level(#)	set confidence level; default is level(95)
nofit	prevent plotting the prediction
fitplot(<i>plotype</i>)	how to plot fit; default is fitplot(line)
ciplot(<i>plotype</i>)	how to plot CIs; default is ciplot(rarea)
<i>fcline_options</i>	change look of predicted line
<i>fitarea_options</i>	change look of CI
<i>axis_choice_options</i>	associate plot with alternative axis
<i>twoway_options</i>	titles, legends, axes, added lines and text, by, regions, name, aspect ratio, etc.

Option level() is *rightmost*; nofit, fitplot(), and ciplot() are *unique*; see [G-4] **Concept: repeated options**.

aweight, fweight, and pweight are allowed. Weights, if specified, affect estimation but not how the weighted results are plotted. See [U] 11.1.6 **weight**.

Options

fptest_options refers to any of the options of graph twoway fptest; see [G-2] **graph twoway fptest**. These options are seldom specified.

level(#) specifies the confidence level, as a percentage, for the confidence intervals. The default is level(95) or as set by set level; see [U] 20.8 **Specifying the width of confidence intervals**.

nofit prevents the prediction from being plotted.

fitplot(*plotype*) is seldom specified. It specifies how the prediction is to be plotted. The default is fitplot(line), meaning that the prediction will be plotted by graph twoway line. See [G-2] **graph twoway** for a list of *plotype* choices. You may choose any plotypes that expect one *y* variable and one *x* variable.

ciplot(*plotype*) specifies how the confidence interval is to be plotted. The default is ciplot(rarea), meaning that the prediction will be plotted by graph twoway rarea.
A reasonable alternative is ciplot(rline), which will substitute lines around the prediction for shading. See [G-2] **graph twoway** for a list of *plotype* choices. You may choose any plotypes that expect two *y* variables and one *x* variable.

fcline_options specify how the prediction line is rendered; see [G-3] **fcline_options**. If you specify fitplot(), then rather than using *fcline_options*, you should select options that affect the specified *plotype* from the options in scatter; see [G-2] **graph twoway scatter**.

fitarea_options specify how the confidence interval is rendered; see [G-3] **fitarea_options**. If you specify ciplot(), then rather than using *fitarea_options*, you should specify whatever is appropriate.

axis_choice_options associate the plot with a particular *y* or *x* axis on the graph; see [G-3] **axis_choice_options**.

twoway_options are a set of common options supported by all *twoway* graphs. These options allow you to title graphs, name graphs, control axes and legends, add lines and text, set aspect ratios, create graphs over `by()` groups, and change some advanced settings. See [G-3] *twoway_options*.

Remarks and examples


Remarks are presented under the following headings:

Typical use
Advanced use
Cautions
Use with `by()`

Typical use


`twoway fptestci` by default draws the confidence interval of the predicted mean:

```
. use https://www.stata-press.com/data/r19/auto  
(1978 automobile data)  
. twoway fptestci mpg weight
```



If you specify the `ciplot(rline)` option, the confidence interval will be designated by lines rather than shading:


```
. twoway fptestci mpg weight, ciplot(rline)
```



Advanced use

`fptestci` can be usefully overlaid with other plots:

```
. use https://www.stata-press.com/data/r19/auto, clear
(1978 automobile data)
. twoway fptestci mpg weight || scatter mpg weight
```



In the above graph, the shaded area corresponds to the 95% confidence interval for the mean.

It is of great importance to note that we typed

```
. twoway fptestci ... || scatter ...
```

and not

```
. twoway scatter ... || fptestci ...
```

Had we drawn the scatter diagram first, the confidence interval would have covered up most of the points.

Cautions

Do not use `twoway fptestci` when specifying the `axis_scale_options` `yscale(log)` or `xscale(log)` to create log scales. Typing

```
. twoway fptestci mpg weight || scatter mpg weight ||, xscale(log)
```


will produce a curve that will be fit from a fractional polynomial regression of mpg on weight rather than `log(weight)`.

See [Cautions](#) in [\[G-2\] graph twoway lfptestci](#).

Use with by()

`fptestci` may be used with `by()` (as can all the `twoway` plot commands):

```
. twoway fptestci mpg weight ||  
  scatter mpg weight ||  
  , by(foreign, total row(1))
```



Also see

[\[G-2\] graph twoway lfptestci](#) — Two-way linear prediction plots with CIs

[\[G-2\] graph twoway qfptestci](#) — Two-way quadratic prediction plots with CIs

[\[G-2\] graph twoway fptestci](#) — Two-way fractional-polynomial prediction plots

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).