

*pr\_options* — Options for use with graph print

[Description](#)[Syntax](#)[Options](#)[Remarks and examples](#)[Also see](#)

## Description

The *pr\_options* are used with `graph print`; see [\[G-2\] graph print](#).

## Syntax

<i>pr_options</i>	Description
<code>tmargin(#)</code>	top margin, in inches, $0 \leq \# \leq 20$
<code>lmargin(#)</code>	left margin, in inches, $0 \leq \# \leq 20$
<code>logo(on off)</code>	whether to display Stata logo

Current default values may be listed by typing

```
. graph set print
```

The defaults may be changed by typing

```
. graph set print name value
```

where *name* is the name of a *pr\_option*, omitting the parentheses.

## Options

`tmargin(#)` and `lmargin(#)` set the top and left page margins—the distance from the edge of the page to the start of the graph. # is specified in inches, must be between 0 and 20, and may be fractional.

`logo(on)` and `logo(off)` specify whether the Stata logo should be included at the bottom of the graph.

## Remarks and examples

stata.com

Remarks are presented under the following headings:

*Using the pr\_options*

*Setting defaults*

*Note for Unix users*

## Using the *pr\_options*

You have drawn a graph and wish to print it. You wish, however, to suppress the Stata logo (although we cannot imagine why you would want to do that):

```
. graph ...                               (draw a graph)
. graph print, logo(off)
```

## Setting defaults

If you always wanted `graph print` to suppress the Stata logo, you could type

```
. graph set print logo off
```

At a future date, you could type

```
. graph set print logo on
```

to set it back. You can determine your default *pr\_options* settings by typing

```
. graph set print
```

## Note for Unix users

In addition to the options documented above, there are other options you may specify. Under Stata for Unix, the *pr\_options* are in fact *ps\_options*; see [\[G-3\] \*ps\\_options\*](#).

## Also see

[\[G-2\] \*graph print\*](#) — Print a graph