

B Advanced Stata usage

Contents

- B.1 [Executing commands every time Stata is started](#)
- B.2 [Other ways to launch Stata](#)
- B.3 [Stata batch mode](#)
- B.4 [Changing Stata's locale](#)
- B.5 [More](#)
- B.6 [Memory size considerations](#)

B.1 Executing commands every time Stata is started

Stata looks for the file `profile.do` when it is invoked and, if it finds it, executes the commands in it. Stata looks for `profile.do` first in the directory where Stata is installed, then in the current directory, then along your path, and finally along the `ado-path` (see [\[P\] sysdir](#)). We recommend that you put `profile.do` in `/Users/yourhome/Library/Application Support/Stata`.

Say that every time you start Stata, you would like to start a dated log for the session. In `/Users/yourhome/Library/Application Support/Stata`, create the file `profile.do` containing this rather odd-looking command (the command will be explained at the end of this session):

```
log using `: display %tCCYY-NN-DD-HH-MM-SS ///
    Clock("`c(current_date)'" `c(current_time)'" ,"DMYhms")', ///
    name(default_log_file)
```

When you invoke Stata, the usual opening appears but with the following additional command, which will be executed:

```
running ~/Library/Application Support/Stata/profile.do ...
```

How does the command work? Let's work from the inside out:

- `c(current_date)` and `c(current_time)` are local system macros containing the current date and current time. See [\[P\] creturn](#) for more information.
- The left (‘) and right (’) quotes around the local macros expand them. See [\[P\] macro](#) for a full explanation.
- The `Clock()` function uses the resulting date string and the date mask "DMYhms" to create a datetime number Stata understands. See [\[D\] datetime](#).
- The format `%tCCYY-NN-DD-HH-MM-SS` formats this number in year-month-day-hour-minute-second form because this will make the files sort nicely. See [\[D\] datetime display formats](#) for the details.
- The odd-looking ``: display ...'` allows the formatted date to be used directly in the command as the file name. This is the advanced concept of an in-line expansion of an extended macro function. You can see more in [\[P\] macro](#).
- The `log using` command starts a log file, such as shown in [\[GSM\] 16 Saving and printing results by using logs](#).
- The `name` option gives the log file the internal name `default_log_file` so that it will not likely conflict with other log files. See [\[R\] log](#) for details.
- Finally, the `///` notations are continuation comments so that the three separate lines are interpreted as a single command. See [\[P\] comments](#) for more about comments.

There are many advanced Stata programming concepts in this one single command!

`profile.do` is treated just as any other do-file once it is executed; results are just the same as if you had started Stata and then typed `run profile.do`. The only special thing about `profile.do` is that Stata looks for it and runs it automatically.

System administrators might also find `sysprofile.do` useful. This file is handled in the same way as `profile.do`, except that Stata first looks for `sysprofile.do`. If that file is found, Stata will execute any commands it contains. After that, Stata will look for `profile.do` and, if that file is found, execute the commands in it.

One example of how `sysprofile.do` might be useful would be when system administrators want to change the path to one of Stata's system directories. Here `sysprofile.do` could be created to contain the command

```
sysdir set SITE "/Library/Application Support/Stata"
```

See [U] 16 Do-files for an explanation of do-files. They are nothing more than text files containing sequences of commands for Stata to execute.

B.2 Other ways to launch Stata

You can start Stata by double-clicking on a Stata `.dta` dataset, a Stata `.do` do-file, or a Stata `.gph` graph file. In all cases except for do-files, your current working directory will become the folder containing the file you have double-clicked. Do-files opened for editing do not change your working directory.

Stata will behave as you would expect in each case. If you double-click on a dataset, Stata will open the dataset after Stata starts. If you double-click on a graph, the graph will be opened by Stata. If you double-click on a do-file, the do-file will be opened either in the Do-file Editor, or will execute its commands.

If you would rather have Stata execute the commands in a do-file when it is double-clicked, select **Stata > Preferences > General Preferences...**, click on the **Windows** toolbar button, click on the *Do-file Editor* item, click on the **Advanced** tab, and uncheck the *Edit do-files opened from the Finder in Do-file Editor* checkbox.

B.3 Stata batch mode

To run Stata in batch mode, you need to start it in the Terminal. The syntax of the command to start Stata from in the Terminal is

```
StataSE [-option [-option [...]]] [stata_command]
```

where the options are

| Option | Result |
|-------------|--|
| -b | set background (batch) mode and log in plain text |
| -e | set background (batch) mode and log in plain text without prompting when Stata command has completed |
| -q | suppress logo and initialization messages |
| -rngstream# | set random-number generator to mt64s (see [R] set rng) and set random-number stream to # (see [R] set rngstream) |
| -s | set background (batch) mode and log in SMCL |

For you to run Stata from the Terminal, you need to be sure that the shell can find Stata. To do this, you must add the path to the Stata executable in Stata's application bundle to your shell's path. Once that is done, you can invoke Stata from any directory from a shell.

For example, if Stata is installed in /Applications/Stata, then the path to the executable for Stata/SE is /Applications/Stata/StataSE.app/Contents/MacOS. Type StataSE to start Stata/SE.

For Stata/MP, it is /Applications/Stata/StataMP.app/Contents/MacOS. Type StataMP to start Stata/MP.

For Stata/IC, it is /Applications/Stata/Stata.app/Contents/MacOS. Type Stata to start Stata/IC.

Suppose you had a do-file named bigjob.do. If you want to use Stata in batch mode, typing

```
% StataSE -b do bigjob
```

tells Stata to execute the commands in bigjob.do, suppress all screen output, and route the output to bigjob.log in the same directory. Stata will display a dialog when the commands have finished executing.

Typing

```
% StataSE -e do bigjob
```

tells Stata to execute the commands in bigjob.do, suppress all screen output, and route the output to bigjob.log in the same directory. Stata will simply exit without displaying a dialog when the commands have finished executing.

```
% StataSE -s do bigjob
```

tells Stata to execute the commands in bigjob.do, suppress all screen output, and route the output to bigjob.smcl in the same directory.

Specifying -s -e sets the background (batch) mode and logs in SMCL without prompting when a Stata command has completed.

You can also run the above examples in the background by typing

```
% StataSE -b do bigjob &
% StataSE -e do bigjob &
% StataSE -s do bigjob &
```

Note: Stata runs profile.do before doing bigjob.do, just as it would if you were working interactively.

General notes

While your do-file is executing, the Stata icon will appear on the dock.

The icon has a badge showing a rough percentage of how much of the do-file Stata has executed. (Stata calculates this percentage from the number of characters in the do-file, so the percentage may not accurately reflect the amount of time left for the job to complete.)

If you right-click on the icon on the taskbar, Stata will display a box asking if you want to cancel the batch job.

Once the do-file is complete, Stata will bounce the icon on the dock. You can then click on the icon to close Stata. If you wish for Stata to automatically exit after running the batch do-file, use `-e` rather than `-b`.

You do not have to run large do-files in batch mode. Any do-file that you run in batch mode can also be run interactively. Simply start Stata, type `log using filename`, and type `do filename`. You can then watch the do-file run, or you can minimize Stata while the do-file is running.

B.4 Changing Stata's locale

To change the locale of Stata to English, type

```
set locale_ui en
```

To change it back to match the locale set for your operating system, type

```
set locale_ui default
```

For a complete explanation of locales and Stata, see [\[U\] 12.4.2.4 Locales in Unicode](#).


B.5 More

If you would like Stata to pause every time the screen fills with results, type `set more on`. This will cause a `—more—` prompt to appear at the bottom of the Results window whenever there is more information to be displayed than can fit on the screen. This happens, for example, when you are listing many observations.

```
. list make mpg
```

| | make | mpg |
|-----|-------------------|-----|
| 1. | Linc. Continental | 12 |
| 2. | Linc. Mark V | 12 |
| 3. | Cad. Deville | 14 |
| 4. | Cad. Eldorado | 14 |
| 5. | Linc. Versailles | 14 |
| 6. | Herc. Cougar | 14 |
| 7. | Herc. XR-7 | 14 |
| 8. | Peugeot 604 | 14 |
| 9. | Buick Electra | 15 |
| 10. | Herc. Marquis | 15 |
| 11. | Buick Riviera | 16 |
| 12. | Chev. Impala | 16 |
| 13. | Dodge Magnum | 16 |
| 14. | Olds Toronado | 16 |
| 15. | AMC Pacer | 17 |
| 16. | Audi 5000 | 17 |
| 17. | Dodge St. Regis | 17 |
| 18. | Volvo 260 | 17 |
| 19. | Buick LeSabre | 18 |
| 20. | Dodge Diplomat | 18 |

```
—more—
```

If you want to see the next screen of text, you have a few options: press any key, such as the Spacebar; click on the **More** button, ; or click on the blue `—more—` at the bottom of the Results window. To see just the next line of text, press *Return*. Pressing *q* will interrupt the command. If you click and hold the **More** button, you can also select the **Run to completion** menu item to let the command completely finish.

B.6 Memory size considerations

Memory management in Stata is automatic. For details on efficiency tweaks needed by a very few Stata users, look at [\[D\] memory](#).