

Description

`bicplot` graphs the Bayesian information criterion (BIC) function after a lasso fit.

`bicplot` can be used after `lasso`, `elasticnet`, `sqrtlasso`, `tlasso`, or any of the lasso inference commands.

Quick start

Graph the BIC function after `lasso`, `sqrtlasso`, or `elasticnet`

```
bicplot
```

Graph the BIC function after `elasticnet` for $\alpha = 0.5$

```
bicplot, alpha(.5)
```

After any of the `ds` or `po` commands, graph the BIC function for the dependent variable `y`

```
bicplot, for(y)
```

After an `xpo` command without option `resample`, graph the BIC function for `x` in cross-fit fold 2

```
bicplot, for(x) xfold(2)
```

After an `xpo` command with `resample`, graph the BIC function for `x` in cross-fit fold 2 for the first resample

```
bicplot, for(x) xfold(2) resample(1)
```

Same as above, but graph the BIC function as a function of the ℓ_1 -norm of the standardized coefficient vector

```
bicplot, for(x) xfold(2) resample(1) xunits(l1norm)
```

After `tlasso`, graph the BIC function for the outcome variable `y` at treatment level 1

```
bicplot, for(y) tlevel(1)
```

Menu

Statistics > Postestimation

Syntax

After `lasso`, `sqrlasso`, and `elasticnet`

```
bicplot [ , options ]
```

After `ds` and `po` commands

```
bicplot, for(varspec) [ options ]
```

After `xpo` commands without `resample`

```
bicplot, for(varspec) xfold(#) [ options ]
```

After `xpo` commands with `resample`

```
bicplot, for(varspec) xfold(#) resample(#) [ options ]
```

After `telasso` for the outcome variable

```
bicplot, for(varspec) tlevel(#) [ options ]
```

After `telasso` for the treatment variable

```
bicplot, for(varspec) [ options ]
```

After `telasso` for the outcome variable with cross-fitting but without `resample`

```
bicplot, for(varspec) tlevel(#) xfold(#) [ options ]
```

After `telasso` for the treatment variable with cross-fitting but without `resample`

```
bicplot, for(varspec) xfold(#) [ options ]
```

After `telasso` for the outcome variable with cross-fitting and `resample`

```
bicplot, for(varspec) tlevel(#) xfold(#) resample(#) [ options ]
```

After `telasso` for the treatment variable with cross-fitting and `resample`

```
bicplot, for(varspec) xfold(#) resample(#) [ options ]
```

varspec is *varname*, except after `poivregress` and `xpoivregress`, when it is either *varname* or `pred(varname)`.

<i>options</i>	Description
Main	
<code>xunits(<i>x_unit_spec</i>)</code>	<i>x</i> -axis units (scale); default is <code>xunits(rlnlambda)</code> , where <code>rlnlambda</code> denotes λ on a reverse logarithmic scale
<code>minmax</code>	add labels for the minimum and maximum <i>x</i> -axis units
<code>*for(varspect)</code>	lasso for <i>varspect</i> ; <code>tlasso</code> , <code>ds</code> , <code>po</code> , and <code>xpo</code> commands only
<code>*xfold(#)</code>	lasso for the <i>#</i> th cross-fit fold; <code>xpo</code> commands and <code>tlasso</code> with <code>xfolds</code> only
<code>*resample(#)</code>	lasso for the <i>#</i> th resample; <code>xpo</code> commands and <code>tlasso</code> with <code>resample</code> only
<code>*tlevel(#)</code>	lasso for the outcome model with the treatment level <i>#</i> ; <code>tlasso</code> only
<code>alpha(#)</code>	graph BIC function for $\alpha = \#$; default is the selected value α^* ; allowed after <code>elasticnet</code> only
<code>lineopts(<i>cline_options</i>)</code>	affect rendition of the plotted lines
Reference lines	
<code>biclineopts(<i>xline_options</i>)</code>	affect rendition of reference line identifying the minimum of the BIC function or other stopping rule
<code>nobicline</code>	suppress reference line identifying the minimum of the BIC function or other stopping rule
<code>lslineopts(<i>xline_options</i>)</code>	affect rendition of reference line identifying the value selected using <code>lassoselect</code>
<code>nolsline</code>	suppress reference line identifying the value selected using <code>lassoselect</code>
<code>rlabelopts(<i>r_label_opts</i>)</code>	change look of labels for reference line
Data	
<code>data(<i>filename</i> [, <i>replace</i>])</code>	save plot data to <i>filename</i>
Y axis, X axis, Titles, Legend, Overall	
<code>twoway_options</code>	any options other than <code>by()</code> documented in [G-3] <i>twoway_options</i>

`*for(varspect)` is required for all `ds`, `po`, and `xpo` commands and for `tlasso`.

`xfold(#)` is required for all `xpo` commands and for `tlasso` when the option `xfolds(#)` was specified.

`resample(#)` is required for `xpo` and for `tlasso` when the option `resample(#)` was specified.

`tlevel(#)` is required for the outcome model in `tlasso`.

<i>x_unit_spec</i>	Description
<code>rlnlambda</code>	λ on a reverse logarithmic scale; the default
<code>lnlambda</code>	λ on a logarithmic scale
<code>linorm</code>	ℓ_1 -norm of standardized coefficient vector
<code>linormraw</code>	ℓ_1 -norm of unstandardized coefficient vector

<i>xline_options</i>	Description
<code>style(<i>addedlinestyle</i>)</code>	overall style of added line
<code>[no]extend</code>	[do not] extend line through plot region's margins
<code>lstyle(<i>linestyle</i>)</code>	overall style of line
<code>lpattern(<i>linepatternstyle</i>)</code>	line pattern (solid, dashed, etc.)
<code>lwidth(<i>linewidthstyle</i>)</code>	thickness of line
<code>lcolor(<i>colorstyle</i>)</code>	color and opacity of line
<i>r_label_opts</i>	Description
<code>labgap(<i>size</i>)</code>	margin between tick and label
<code>labstyle(<i>textstyle</i>)</code>	overall style of label
<code>labsize(<i>textsizestyle</i>)</code>	size of label
<code>labcolor(<i>colorstyle</i>)</code>	color and opacity of label

Options

Main

`xunits(x_unit_spec)` specifies the x -axis units used for graphing the BIC function. The following *x_unit_specs* are available:

`rlnlambda` specifies x -axis units λ on a reverse logarithmic scale. This is the default.

`lnlambda` specifies x -axis units λ on a logarithmic scale.

`l1norm` specifies x -axis units ℓ_1 -norm of the standardized coefficient vector.

`l1normraw` specifies x -axis units ℓ_1 -norm of the unstandardized coefficient vector.

`minmax` adds labels for the minimum and maximum x -axis units to the graph of the BIC function.

`for(varspec)` specifies a particular lasso after `telasso` or a `ds`, `po`, or `xpo` estimation command fit using the option `selection(bic)`. For all commands except `poivregress` and `xpoivregress`, *varspec* is always *varname*; it is either *depvar*, the dependent variable, or one of *varsofinterest* for which inference is done.

For `poivregress` and `xpoivregress`, *varspec* is either *varname* or `pred(varname)`. The lasso for *depvar* is specified with its *varname*. For the endogenous variable *varname*, there are two lassos, which can be identified by *varname* and `pred(varname)`. The exogenous variables of interest each have only one lasso, and it is specified by `pred(varname)`.

This option is required after `ds`, `po`, and `xpo` commands.

`xfold(#)` specifies a particular lasso after an `xpo` estimation command. For each variable to be fit with a lasso, K lassos are done, one for each cross-fit fold, where K is the number of folds. This option specifies which fold, where $\# = 1, 2, \dots, K$. `xfold(#)` is required after an `xpo` command.

`resample(#)` specifies a particular lasso after an `xpo` estimation command fit using the option `resample(#)`. For each variable to be fit with a lasso, $R \times K$ lassos are done, where R is the number of resamples and K is the number of cross-fitting folds. This option specifies which resample, where $\# = 1, 2, \dots, R$. `resample(#)`, along with `xfold(#)`, is required after an `xpo` command with resampling.

`tlevel(#)` specifies the lasso for the outcome variable at the specified treatment level after `telasso`.

This option is required to refer to the outcome model after `telasso`.

`alpha(#)` graphs the BIC function for $\alpha = \#$. The default is `alpha(α^*)`, where α^* is the selected α .

`alpha(#)` may only be specified after `elasticnet`.

`lineopts(cline_options)` affects the rendition of the plotted line. See [G-3] [cline_options](#).

Reference lines

`biclineopts(xline_options)` affects the rendition of the reference line identifying the minimum BIC value, the value selected when the stopping tolerance is reached, or the grid-minimum value.

xline_options are the following: `style(addedlinestyle)`, `noextend`, `lstyle(linestyle)`, `lpattern(linepatternstyle)`, `lwidth(linewidthstyle)`, and `lcolor(colorstyle)`. They specify how the reference line identifying the minimum BIC value is presented. See [G-4] [addedlinestyle](#), [G-4] [linestyle](#), [G-4] [linepatternstyle](#), [G-4] [linewidthstyle](#), and [G-4] [colorstyle](#).

`nobicline` suppresses the reference line identifying the minimum BIC value, the value selected when either the stopping tolerance or the grid-minimum value is reached.

`lslineopts(xline_options)` affects the rendition of the reference line identifying the value selected using `lassoselect`.

xline_options are the following: `style(addedlinestyle)`, `noextend`, `lstyle(linestyle)`, `lpattern(linepatternstyle)`, `lwidth(linewidthstyle)`, and `lcolor(colorstyle)`. They specify how the reference line identifying the value selected using `lassoselect` is presented. See [G-4] [addedlinestyle](#), [G-4] [linestyle](#), [G-4] [linepatternstyle](#), [G-4] [linewidthstyle](#), and [G-4] [colorstyle](#).

`nolsline` suppresses the reference line identifying the value selected using `lassoselect`.

`rlabelopts(r_label_opts)` changes the look of labels for the reference line. The label options `labgap(relativesize)`, `labstyle(textstyle)`, `labsize(textsizestyle)`, and `labcolor(colorstyle)` specify details about how the labels are presented. See [G-4] [size](#), [G-4] [textstyle](#), [G-4] [textsizestyle](#), and [G-4] [colorstyle](#).

Data

`data(filename [, replace])` saves the plot data to a Stata data file.

Y axis, X axis, Titles, Legend, Overall

twoway_options are any of the options documented in [G-3] [twoway_options](#), excluding `by()`. These include options for titling the graph (see [G-3] [title_options](#)) and options for saving the graph to disk (see [G-3] [saving_option](#)).

Remarks and examples

BIC plots graph the BIC function over the search grid for the lasso penalty parameter λ .

The search grid can be shown as the log of the lasso penalty parameter λ , `xunits(lnlambda)`; the reverse of that scale, `xunits(rlnlambda)`; the ℓ_1 -norm of the standardized coefficients, `xunits(l1norm)`; or the ℓ_1 -norm of the unstandardized coefficients, `xunits(l1normraw)`. The reverse log of lambda is the default because it represents the BIC search path over λ , with the first λ tried on the left and the last λ tried on the right.

BIC plots can be drawn after any command that directly searches over a grid of λ 's. They can be drawn after the commands `lasso`, `elasticnet`, `sqrtlasso`, `telasso`, or any of the 11 lasso inference commands.

Examples that demonstrate how to use `bicplot` after the `lasso` command can be found in [BIC](#) in [\[LASSO\] lasso examples](#).

Also see

[\[LASSO\] lasso inference postestimation](#) — Postestimation tools for lasso inferential models

[\[LASSO\] lasso postestimation](#) — Postestimation tools for lasso for prediction

[\[CAUSAL\] telasso postestimation](#) — Postestimation tools for telasso

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

