

[Description](#)

[Syntax](#)

[Remarks and examples](#)

[Also see](#)

Description

Many Mata functions are written in Mata. `viewsource` will allow you to examine their source code.

Syntax

```
viewsource functionname.mata
```

Remarks and examples

Some Mata functions are implemented in C (they are part of Mata itself), and others are written in Mata.

`viewsource` allows you to look at the official source code written in Mata. Reviewing this code is a great way to learn Mata.

The official source code is stored in `.mata` files. To see the source code for `diag()` (see [M-5] [diag\(\)](#)), for instance, type

```
. viewsource diag.mata
```

You type this at Stata's dot prompt, not at Mata's colon prompt.

If a function is built in, such as `abs()` (see [M-5] [abs\(\)](#)), here is what will happen when you attempt to view the source code:

```
. viewsource abs.mata
file "abs.mata" not found
r(601);
```

You can verify that `abs()` is built in by using the `mata which` (see [M-3] [mata which](#)) command:

```
. mata: mata which abs()
abs(): built-in
```

`viewsource` can be also used to look at source code of community-contributed functions if the distribution included the source code (it might not).

Also see

[P] [viewsource](#) — View source code

[M-1] [Intro](#) — Introduction and advice

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).