

Description

`mata which fcnname` looks for *fcnname*() and reports whether it is built in, stored in a `.mlib` library, or stored in a `.mo` file.

Syntax

```
: mata which fcnname()
```

This command is for use in Mata mode following Mata's colon prompt. To use this command from Stata's dot prompt, type

```
. mata: mata which ...
```

Remarks and examples

`mata which fcnname()` looks for *fcnname*() and reports where it is found:

```
: mata which I()
I():  built-in
: mata which assert()
assert():  lmatabase
: mata which myfcn()
userfunction():  .\myfcn.mo
: mata which nosuchfunction()
function nosuchfunction() not found
r(111);
```

Function `I()` is built in; it was written in C and is a part of Mata itself.

Function `assert()` is a library function and, as a matter of fact, its executable object code is located in the official function library `lmatabase.mlib`.

Function `myfcn()` exists and has its executable object code stored in file `myfcn.mo`, located in the current directory.

Function `nosuchfunction()` does not exist.

Going back to `mata which assert()`, which was found in `lmatabase.mlib`, if you wanted to know where `lmatabase.mlib` was stored, you could type `findfile lmatabase.mlib` at the Stata prompt; see [\[P\] find-file](#).

Also see

[M-3] [Intro](#) — Commands for controlling Mata

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

