

Description

`_diag(Z, v)` replaces the diagonal of the matrix Z with v . Z need not be square.

1. If v is a vector, the vector replaces the principal diagonal.
2. If v is 1×1 , each element of the principal diagonal is replaced with v .
3. If v is a void vector (1×0 or 0×1), Z is left unchanged.

Syntax

void `_diag(numeric matrix Z, numeric vector v)`

Conformability

`_diag(Z, v)`:

input:

Z : $n \times m, n \leq m$
 v : $1 \times 1, 1 \times n$, or $n \times 1$

or

Z : $n \times m, n > m$
 v : $1 \times 1, 1 \times m$, or $m \times 1$

output:

Z : $n \times m$

Diagnostics

`_diag(Z, v)` aborts with error if Z or v is a view.

Also see

[M-5] [diag\(\)](#) — Create diagonal matrix

[M-4] [Manipulation](#) — Matrix manipulation

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).