

Description

`cat(filename)` returns a column vector containing the lines from text file *filename*.

`cat(filename, line1)` returns a column vector containing the lines from text file *filename* starting with line number *line1*.

`cat(filename, line1, line2)` returns a column vector containing the lines from text file *filename* starting with line number *line1* and ending with line number *line2*.

Syntax

string colvector `cat`(*string scalar* *filename* [, *real scalar* *line1* [, *real scalar* *line2*]])

Remarks and examples

`cat(filename)` removes new-line characters at the end of lines.

Conformability

`cat(filename, line1, line2):`

<i>filename</i> :	1×1
<i>line1</i> :	1×1 (optional)
<i>line2</i> :	1×1 (optional)
<i>result</i> :	$r \times 1$, $r \geq 0$

Diagnostics

`cat(filename)` aborts with error if *filename* does not exist.

`cat()` returns a 0×1 result if *filename* contains 0 bytes.

Also see

[M-4] **IO** — I/O functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

