

Description

`eltype()` returns the current *eltype* of the argument.

`orgtype()` returns the current *orgtype* of the argument.

`classname()` returns the name of the class for a Mata class scalar.

`structname()` returns the name of the struct for a Mata struct scalar.

See [M-6] [Glossary](#) for a definition of *eltype* and *orgtype*.

Syntax

string scalar `eltype(X)`

string scalar `orgtype(X)`

string scalar `classname(X)`

string scalar `structname(X)`

Remarks and examples

If X is a matrix (syntax 1), returned is

<code>eltype(X)</code>	<code>orgtype(X)</code>
real	scalar
complex	rowvector
string	colvector
pointer	matrix
struct	
class	

The returned value reflects the current contents of X . That is, X might be declared a transmorphic matrix, but at any instant, it contains something, and if that something were 5, returned would be "real" and "scalar".

For `orgtype()`, returned is "scalar" if the object is currently 1×1 ; "rowvector" if it is $1 \times k$, $k \neq 1$; "colvector" if it is $k \times 1$, $k \neq 1$; and "matrix" otherwise (it is $r \times c$, $r \neq 1$, $c \neq 1$).

X can be a function (syntax 2). Returned is

<code>eltype*(<i>&func()</i>)</code>	<code>orgtype*(<i>&func()</i>)</code>
<code>transmorphic</code>	<code>matrix</code>
<code>numeric</code>	<code>vector</code>
<code>real</code>	<code>rowvector</code>
<code>complex</code>	<code>colvector</code>
<code>string</code>	<code>scalar</code>
<code>pointer</code>	<code>void</code>
<code>struct</code>	
<code>structdef</code>	
<code>class</code>	
<code>classdef</code>	

These types are obtained from the declaration of the function.

Aside: `struct` and `structdef` have to do with structures; see [M-2] **struct**. `structdef` indicates that the function not only returns a structure but is the routine that defines the structure as well. `class` and `classdef` have to do with Mata classes; see [M-2] **class**. `classdef` indicates the function not only returns a class but is the routine that defines the class as well.

`classname()` returns the name "cA" if the object is a class cA scalar. The function returns "" if the object has element type other than class or has organizational type other than scalar.

`structname()` returns the name "sA" if the object is a struct sA scalar. The function returns "" if the object has element type other than struct or has organizational type other than scalar.

Conformability

`eltype(X)`, `orgtype(X)`, `classname(X)`, `structname(X)`:

X : $r \times c$
result: 1×1

Diagnostics

None.

Also see

[M-5] **isreal()** — Storage type of matrix

[M-5] **isview()** — Whether matrix is view

[M-4] **Utility** — Matrix utility functions

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).