

findfile() — Find file

[Description](#) [Syntax](#) [Remarks and examples](#) [Conformability](#)
[Diagnostics](#) [Also see](#)

Description

`findfile(fn, dirlist)` looks for file *fn* along the semicolon-separated list of directories *dirlist* and returns the fully qualified path and filename if *fn* is found. `findfile()` returns "" if the file is not found.

`findfile(fn)` is equivalent to `findfile(fn, c("adopath"))`. `findfile()` with one argument looks along the official Stata ado-path for file *fn*.

Syntax

string scalar `findfile(string scalar fn, string scalar dirlist)`

string scalar `findfile(string scalar fn)`

Remarks and examples

[stata.com](#)

For instance,

```
findfile("kappa.ado")
```

might return C:\Program Files\Stata15\ado\base\k\kappa.ado.

Conformability

`findfile(fn, dirlist):`

<i>fn</i> :	1×1	
<i>dirlist</i> :	1×1	(optional)
<i>result</i> :	1×1	

Diagnostics

`findfile(fn, dirlist)` and `findfile(fn)` return "" if the file is not found. If the file is found, the returned fully qualified path and filename is guaranteed to exist and be readable at the instant `findfile()` concluded.

Also see

[M-4] [io](#) — I/O functions