

Description	Syntax	Remarks and examples	Conformability
Diagnostics	References	Also see	

## Description

`hash1(x)` returns Jenkins’s one-at-a-time hash calculated over the bytes of *x*;  $0 \leq \text{hash1}(x) \leq 4,294,967,295$ .

`hash1(x, n)` returns Jenkins’s one-at-a-time hash scaled to  $1 \leq \text{hash1}(x, n) \leq n$ , assuming  $n < .$  (missing). `hash1(x, .)` is equivalent to `hash1(x)`.

`hash1(x, n, byteorder)` returns `hash1(x, n)` performed on the bytes of *x* ordered as they would be on a HILO computer (*byteorder* = 1), or as they would be on a LOHI computer (*byteorder* = 2), or as they are on this computer (*byteorder*  $\geq .$ ). See [M-5] [byteorder\(\)](#) for a definition of byte order.

In all cases, the values returned by `hash1()` are integers.

## Syntax

*real scalar* `hash1`(*x* [*, real scalar n* [*, real scalar byteorder*]])

where

<i>x</i> :	any type except <code>struct</code> and any dimension
<i>n</i> :	$1 \leq n \leq 2,147,483,647$ or <code>.</code> ; default is <code>.</code> (missing)
<i>byteorder</i> :	1 (HILO), 2 (LOHI), <code>.</code> (natural byte order); default <code>.</code> (missing)

## Remarks and examples

Calculation is significantly faster using the natural byte order of the computer. Argument *byteorder* is included for those rare cases when it is important to calculate the same hash value across different computers, which in the case of `hash1()` is mainly for testing. `hash1()`, being a one-at-a-time method, is not sufficient for constructing digital signatures. It is sufficient for constructing hash tables; see [M-5] [asarray\(\)](#), in which case, byte order is irrelevant. Also note that because strings occur in the same order on all computers, the value of *byteorder* is irrelevant when *x* is a string.

For instance,

```
: hash1("this"), hash1("this",.,1), hash1("this",.,2)
      1           2           3
1  2385389520  2385389520  2385389520

: hash1(15), hash1(15,.,1), hash1(15,.,2)
      1           2           3
1  463405819  3338064604  463405819
```

The computer on which this example was run is evidently *byteorder* = 2, meaning LOHI, or least-significant byte first.

In a Mata context, it is the two-argument form of `hash1()` that is most useful. In that form, the full result is mapped onto  $[1, n]$ :

$$\text{hash1}(x, n) = \text{floor}((\text{hash1}(x)/4294967295)*n) + 1$$

For instance,

```
: hash1("this", 10)
      6
: hash1(15, 10)
      2
```

The result of `hash1(x, 10)` could be used directly to index a  $10 \times 1$  array.

## Conformability

```
hash1(x, n, byteorder):
      x:      r × c
      n:      1 × 1      (optional)
      byteorder: 1 × 1      (optional)
      result:  1 × 1
```

## Diagnostics

None.

Note that `hash1(x[, ...])` never returns a missing result, even if *x* is or contains a missing value. In the missing case, the hash value is calculated of the missing value. Also note that *x* can be a vector or a matrix, in which case the result is calculated over the elements aligned rowwise as if they were a single element. Thus `hash1(("a", "b")) == hash1("ab")`.

## References

Jenkins, B. 1997. *Dr. Dobbs's Journal*. Algorithm alley: Hash functions. <https://www.ddj.com/184410284>.  
 ———. unknown. A hash function for hash table lookup. <https://www.burtleburtle.net/bob/hash/doobs.html>.

## Also see

[M-5] **asarray()** — Associative arrays

[M-4] **Programming** — Programming functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

