

Description

`indexnot(s_1 , s_2)` returns the position of the first byte of s_1 not found in s_2 , or it returns 0 if all bytes of s_1 are found in s_2 . Note that a Unicode character may contain multiple bytes. Use `strlen()` or `ustrlen()` to check if s_1 or s_2 has more bytes than its number of Unicode characters.

Syntax

real matrix `indexnot(string matrix s_1 , string matrix s_2)`

Conformability

`indexnot(s_1 , s_2)`:

s_1 : $r_1 \times c_1$

s_2 : $r_2 \times c_2$, s_1 and s_2 r-conformable

result: $\max(r_1, r_2) \times \max(c_1, c_2)$

Diagnostics

`indexnot(s_1 , s_2)` returns 0 if all bytes of s_1 are found in s_2 .

Also see

[M-4] [String](#) — String manipulation functions

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).