

## Description

`luinv(A)` and `luinv(A, tol)` return the inverse of real or complex, square matrix  $A$ .

`_luinv(A)` and `_luinv(A, tol)` do the same thing except that, rather than returning the inverse matrix, they overwrite the original matrix  $A$  with the inverse.

`_luinv_la(A, b)` is the interface to the **LAPACK** routines that do the work. The output  $b$  is a real scalar, which is missing if the MKL LAPACK routine was used, is 1 if the Netlib LAPACK routine used a blocked algorithm, and is 0 otherwise. This function uses the MKL LAPACK by default.

`_luinv_lapacke(A)` and `_luinv_lapacke(A, tol)` are the interfaces to the **LAPACK** routines that do the work. Both of these function use MKL LAPACK by default.

In all cases, optional argument `tol` specifies the tolerance for determining singularity; see [Remarks and examples](#) below.

## Syntax

*numeric matrix*    `luinv(numeric matrix A)`

*numeric matrix*    `luinv(numeric matrix A, real scalar tol)`

*void*                `_luinv(numeric matrix A)`

*void*                `_luinv(numeric matrix A, real scalar tol)`

*real scalar*        `_luinv_la(numeric matrix A, b)`

*real scalar*        `_luinv_lapacke(numeric matrix A)`

*real scalar*        `_luinv_lapacke(numeric matrix A, real scalar tol)`

## Remarks and examples

These routines calculate the inverse of  $A$ . The inverse matrix  $A^{-1}$  of  $A$  satisfies the conditions

$$AA^{-1} = I$$

$$A^{-1}A = I$$

$A$  is required to be square and of full rank. See [\[M-5\] qrinv\(\)](#) and [\[M-5\] pinv\(\)](#) for generalized inverses of nonsquare or rank-deficient matrices. See [\[M-5\] invsym\(\)](#) for inversion of real, symmetric matrices.

`luinv(A)` is logically equivalent to `lusolve(A, I(rows(A)))`; see [\[M-5\] lusolve\(\)](#) for details and for use of the optional `tol` argument.

## Conformability

```

luinv(A, tol):
    A:       $n \times n$ 
    tol:     $1 \times 1$  (optional)
    result:  $n \times n$ 

_luinv(A, tol):
    input:
        A:       $n \times n$ 
        tol:     $1 \times 1$  (optional)
    output:
        A:       $n \times n$ 

_luinv_la(A, b):
    input:
        A:       $n \times n$ 
    output:
        A:       $n \times n$ 
        b:       $1 \times 1$ 
    result:     $1 \times 1$ 

_luinv_lapacke(A, tol):
    input:
        A:       $n \times n$ 
    output:
        A:       $n \times n$ 
        tol:     $1 \times 1$  (optional)
    result:     $1 \times 1$ 

```

## Diagnostics

The inverse returned by these functions is real if  $A$  is real and is complex if  $A$  is complex. If you use these functions with a singular matrix, returned will be a matrix of missing values. The determination of singularity is made relative to  $tol$ . See [Tolerance](#) under *Remarks and examples* in [M-5] [lusolve\(\)](#) for details.

`luinv( $A$ )` and `_luinv( $A$ )` return a matrix containing missing if  $A$  contains missing values.

`_luinv( $A$ )` aborts with error if  $A$  is a view.

`_luinv_la( $A$ ,  $b$ )`, `_luinv_lapacke( $A$ )`, and `_luinv_lapacke( $A$ ,  $tol$ )` should not be used directly; use `_luinv()`.

See [M-5] [lusolve\(\)](#) and [M-1] [Tolerance](#) for information on the optional  $tol$  argument.

## Also see

- [M-5] **cholinv()** — Symmetric, positive-definite matrix inversion
- [M-5] **\_invmat()** — Inverse and pseudoinverse of a square matrix
- [M-5] **invsym()** — Symmetric real matrix inversion
- [M-5] **lud()** — LU decomposition
- [M-5] **lusolve()** — Solve  $AX=B$  for  $X$  using LU decomposition
- [M-5] **pinv()** — Moore–Penrose pseudoinverse
- [M-5] **qrinv()** — Generalized inverse of matrix via QR decomposition
- [M-4] **Matrix** — Matrix functions
- [M-4] **Solvers** — Functions to solve  $AX=B$  and to obtain  $A$  inverse

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).