

Description

`reldif(X, Y)` returns the relative difference defined by

$$r = \frac{|X - Y|}{|Y| + 1}$$

calculated element by element.

`mreldif(X, Y)` returns the maximum relative difference and is equivalent to `max(reldif(X, Y))`.

`mreldifsym(X)` is equivalent to `mreldif(X', X)` and so is a measure of how far the matrix is from being symmetric (Hermitian).

`mreldifre(X)` is equivalent to `mreldif(Re(X), X)` and so is a measure of how far the matrix is from being real.

Syntax

real matrix `reldif(numeric matrix X, numeric matrix Y)`

real scalar `mreldif(numeric matrix X, numeric matrix Y)`

real scalar `mreldifsym(numeric matrix X)`

real scalar `mreldifre(numeric matrix X)`

Conformability

`reldif(X, Y):`

X: $r \times c$

Y: $r \times c$

result: $r \times c$

`mreldif(X, Y):`

X: $r \times c$

Y: $r \times c$

result: 1×1

`mreldifsym(X):`

X: $n \times n$

result: 1×1

`mreldifre(X):`

X: $r \times c$

result: 1×1

Diagnostics

The relative difference function treats equal missing values as having a difference of 0 and different missing values as having a difference of missing (.):

```
reldif(., .) == reldif(.a, .a) == ... == reldif(.z, .z) == 0
```

```
reldif(., .a) == reldif(., .z) == ... == reldif(.y, .z) == .
```

Also see

[M-4] [Utility](#) — Matrix utility functions

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).