

## Description

`select( $X$ ,  $v$ )` returns  $X$

1. omitting the rows for which  $v[i] == 0$  ( $v$  a column vector) or
2. omitting the columns for which  $v[j] == 0$  ( $v$  a row vector).

`st_select( $A$ ,  $X$ ,  $v$ )` does the same thing, except that the result is placed in  $A$  and, if  $X$  is a view,  $A$  will be a view.

`selectindex( $v$ )` returns

1. a row vector of column indices  $j$  for which  $v[j] != 0$  ( $v$  a row vector) or
2. a column vector of row indices  $i$  for which  $v[i] != 0$  ( $v$  a column vector).

## Syntax

*transmorphic matrix* `select(transmorphic matrix  $X$ , real vector  $v$ )`

*void* `st_select( $A$ , transmorphic matrix  $X$ , real vector  $v$ )`

*real vector* `selectindex(real vector  $v$ )`

## Remarks and examples

Remarks are presented under the following headings:

[Examples](#)

[Using st\\_select\(\)](#)

### Examples

1. To select rows 1, 2, and 4 of  $5 \times c$  matrix  $X$ ,

```
submat = select(X, (1\1\0\1\0))
```

See [\[M-2\] Subscripts](#) for another solution, `submat = X[(1\2\4), .]`.

2. To select columns 1, 2, and 4 of  $r \times 5$  matrix  $X$ ,

```
submat = select(X, (1,1,0,1,0))
```

See [\[M-2\] Subscripts](#) for another solution, `submat = X[:, (1,2,4)]`.

3. To select rows of  $X$  for which the first element is positive,

```
submat = select(X, X[:,1]:>0)
```

4. To select columns of  $X$  for which the first element is positive,

```
submat = select(X, X[1,:]:>0)
```

5. To select rows of  $X$  for which there are no missing values,

```
submat = select(X, rowmissing(X)==0)
```

6. To select rows and columns of square matrix  $X$  for which the diagonal elements are positive,

```
pos = diagonal(X):>0
submat = select(X, pos)
submat = select(submat, pos')
```

or, equivalently,

```
pos = diagonal(X):>0
submat = select(select(X, pos), pos')
```

7. To select column indices for which  $v[j] \neq 0$ ,

```
: v
      1   2   3   4   5
1  [ 6   0   7   0   8 ]

: selectindex(v)
      1   2   3
1  [ 1   3   5 ]
```

8. To select row indices for which  $v[i] \neq 0$ ,

```
: w
      1
1  [ 0 ]
2  [ 3 ]
3  [ 0 ]
4  [ 2 ]
5  [ 1 ]

: selectindex(w)
      1
1  [ 2 ]
2  [ 4 ]
3  [ 5 ]
```

## Using st\_select()

### Coding

```
st_select(submat, X, v) (1)
```

produces the same result as coding

```
submat = st_select(X, v) (2)
```

The difference is in how the result is stored. If  $X$  is a view (it need not be), then (1) will produce `submat` as a view or, if you will, a subview, whereas in (2), `submat` will always be a regular (nonview) matrix.

When  $X$  is a view, (1) executes more quickly than (2) and produces a result that consumes less memory.

See [M-5] [st\\_view\(\)](#) for a description of views.

## Conformability

`select(X, v):`

$X:$	$r_1 \times c_1$		
$v:$	$r_1 \times 1$	or	$1 \times c_1$
<i>result:</i>	$r_2 \times c_1$	or	$r_1 \times c_2, \quad r_2 \leq r_1, c_2 \leq c_1$

`st_select(A, X, v):`

*input:*

$X:$	$r_1 \times c_1$		
$v:$	$r_1 \times 1$	or	$1 \times c_1$

*output:*

$A:$	$r_2 \times c_1$	or	$r_1 \times c_2, \quad r_2 \leq r_1, c_2 \leq c_1$
------	------------------	----	--

`selectindex(v):`

$v:$	$r_1 \times 1$	or	$1 \times c_1$
<i>result:</i>	$r_2 \times 1$	or	$1 \times c_2, \quad r_2 \leq r_1, c_2 \leq c_1$

## Diagnostics

None.

## Also see

[M-5] [st\\_subview\(\)](#) — Make view from view

[M-2] [op\\_colon](#) — Colon operators

[M-2] [Subscripts](#) — Use of subscripts

[M-4] [Utility](#) — Matrix utility functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

