

**sizeof()** — Number of bytes consumed by object

Description Diagnostics	Syntax Also see	Remarks and examples	Conformability
----------------------------	--------------------	----------------------	----------------

## Description

`sizeof(A)` returns the number of bytes consumed by  $A$ .

## Syntax

*real scalar*    `sizeof(transmorphic matrix A)`

## Remarks and examples

stata.com

`sizeof(A)` returns the same number as shown by `mata describe`; see [M-3] [mata describe](#).

A  $500 \times 5$  real matrix consumes 20,000 bytes:

```
: sizeof(mymatrix)
20000
```

A  $500 \times 5$  view matrix, however, consumes only 24 bytes:

```
: sizeof(myview)
24
```

To obtain the number of bytes consumed by a function, pass a dereferenced function pointer:

```
: sizeof(&myfcn())
320
```

## Conformability

`sizeof(A)`:

<i>A</i> :	$r \times c$
<i>result</i> :	$1 \times 1$

## Diagnostics

The number returned by `sizeof(A)` does not include any overhead, which usually amounts to 64 bytes, but can be less (as small as zero in the case of recently used scalars).

If  $A$  is a pointer matrix, the number returned reflects the amount of memory required to store  $A$  itself and does not include the memory consumed by its siblings.

## Also see

[M-4] [Programming](#) — Programming functions