

**st\_data()** — Load copy of current Stata dataset

|                            |                    |                      |                |
|----------------------------|--------------------|----------------------|----------------|
| Description<br>Diagnostics | Syntax<br>Also see | Remarks and examples | Conformability |
|----------------------------|--------------------|----------------------|----------------|

## Description

`_st_data(i, j)` returns the numeric value of the *i*th observation of the *j*th Stata variable. Observations are numbered 1 through `st_nobs()`. Variables are numbered 1 through `st_nvar()`.

`st_data(i, j)` is similar to `_st_data(i, j)` except

1. *i* may be specified as a vector or matrix to obtain multiple observations simultaneously,
2. *j* may be specified using names or indices (indices are faster), and
3. *j* may be specified to obtain multiple variables simultaneously.

The net effect is that `st_data()` can return a scalar (the value of one variable in one observation), a row vector (the value of many variables in an observation), a column vector (the value of a variable in many observations), or a matrix (the value of many variables in many observations).

`st_data(i, j, selectvar)` works like `st_data(i, j)` except that only observations for which *selectvar*  $\neq$  0 are returned.

`_st_sdata()` and `st_sdata()` are the string variants of `_st_data()` and `st_data()`. `_st_data()` and `st_data()` are for use with numeric variables; they return missing (.) when used with string variables. `_st_sdata()` and `st_sdata()` are for use with string variables; they return empty string ("") when used with numeric variables.

## Syntax

|                      |  |         |
|----------------------|--|---------|
| <i>real scalar</i>   | <code>_st_data(<i>real scalar i</i>, <i>real scalar j</i>)</code>                        |         |
| <i>real matrix</i>   | <code>st_data(<i>real matrix i</i>, <i>rowvector j</i>)</code>                           | (1,2)   |
| <i>real matrix</i>   | <code>st_data(<i>real matrix i</i>, <i>rowvector j</i>, <i>scalar selectvar</i>)</code>  | (1,2,3) |
| <i>string scalar</i> | <code>_st_sdata(<i>real scalar i</i>, <i>real scalar j</i>)</code>                       |         |
| <i>string matrix</i> | <code>st_sdata(<i>real matrix i</i>, <i>rowvector j</i>)</code>                          | (1,2)   |
| <i>string matrix</i> | <code>st_sdata(<i>real matrix i</i>, <i>rowvector j</i>, <i>scalar selectvar</i>)</code> | (1,2,3) |

where

1. *i* may be specified as a  $1 \times 1$  scalar, as a  $1 \times 1$  scalar containing missing, as a column vector of observation numbers, as a row vector specifying an observation range, or as a  $k \times 2$  matrix specifying both.
  - a. `st_data(1, 2)` returns the first observation on the second variable.

- b. `st_data(., 2)` returns all observations on the second variable.
- c. `st_data((1\2\5), 2)` returns observations 1, 2, and 5 on the second variable.
- d. `st_data((1,5), 2)` returns observations 1 through 5 on the second variable.
- e. `st_data((1,5\7,9), 2)` returns observations 1 through 5 and observations 7 through 9 on the second variable.

When a range is specified, any element of the range ( $i_1, i_2$ ) may be specified to contribute zero observations if  $i_2 = i_1 - 1$ .

- 2.  $j$  may be specified as a real row vector or as a string scalar or string row vector.
  - a. `st_data(., .)` returns the values of all variables, all observations of the Stata dataset.
  - b. `st_data(., 1)` returns the value of the first variable, all observations.
  - c. `st_data(., (3,1,9))` returns the values of the third, first, and ninth variables of all observations.
  - d. `st_data(., ("mpg", "weight"))` returns the values of variables `mpg` and `weight`, all observations.
  - e. `st_data(., ("mpg weight"))` does the same as d above.
  - f. `st_data(., ("gnp", "l.gnp"))` returns the values of `gnp` and the lag of `gnp`, all observations.
  - g. `st_data(., ("gnp l.gnp"))` does the same as f above.
  - h. `st_data(., ("mpg i.rep78"))` returns the value of `mpg` and the 5 pseudovariates associated with `i.rep78`. There are 5 pseudovariates because we are imagining that `auto.dta` is in memory; the actual number is a function of the values taken on by the variable in the sample specified. Factor variables can be specified only with string scalars; specifying ("`mpg`", "`i.rep78`") will not work.
- 3. *selectvar* may be specified as real or as a string. Observations for which *selectvar*  $\neq 0$  will be selected. If *selectvar* is real, it is interpreted as a variable number. If string, *selectvar* should contain the name of a Stata variable.

Specifying *selectvar* as "" or as missing (.) has the same result as not specifying *selectvar*; no observations are excluded.

Specifying *selectvar* as 0 means that observations with missing values of the variables specified by  $j$  are to be excluded.

## Remarks and examples

[stata.com](http://www.stata.com)

Remarks are presented under the following headings:

*Description of `_st_data()` and `_st_sdata()`*

*Description of `st_data()` and `st_sdata()`*

*Details of observation subscripting using `st_data()` and `st_sdata()`*

## Description of `_st_data()` and `_st_sdata()`

`_st_data()` returns one variable's value in one observation. You refer to variables and observations by their numbers. The first variable in the Stata dataset is 1; the first observation is 1.

---

|                             |                                 |
|-----------------------------|---------------------------------|
| <code>_st_data(1, 1)</code> | value of 1st obs., 1st variable |
| <code>_st_data(1, 2)</code> | value of 1st obs., 2nd variable |
| <code>_st_data(2, 1)</code> | value of 2nd obs., 1st variable |

---

`_st_sdata()` works the same way. `_st_data()` is for use with numeric variables, and `_st_sdata()` is for use with string variables.

`_st_data()` and `_st_sdata()` are the fastest way to obtain the value of a variable in one observation.

## Description of `st_data()` and `st_sdata()`

`st_data()` can be used just like `_st_data()`, and used that way, it produces the same result.

Variables, however, can be referred to by their names or their numbers:

---

|                                |                                 |
|--------------------------------|---------------------------------|
| <code>st_data(1, 1)</code>     | value of 1st obs., 1st variable |
| <code>st_data(1, 2)</code>     | value of 1st obs., 2nd variable |
| <code>st_data(2, 1)</code>     | value of 2nd obs., 1st variable |
| <code>st_data(1, "mpg")</code> | value of 1st obs, variable mpg  |
| <code>st_data(2, "mpg")</code> | value of 2nd obs, variable mpg  |

---

Also, you may specify more than one variable:

---

|   |  |
|---|--|
| <code>st_data(2, (1,2,3))</code>                    | value of 2nd obs., variables 1, 2, and 3               |
| <code>st_data(2, ("mpg", "weight", "displ"))</code> | value of 2nd obs., variables<br>mpg, weight, and displ |
| <code>st_data(2, "mpg weight displ")</code>         | (same as previous)                                     |

---

Used this way, `st_data()` returns a row vector.

Similarly, you may obtain multiple observations:

---

|                                       |  |
|---------------------------------------|--|
| <code>st_data((1\2\3), 10)</code>     | values of obs. 1, 2, and 3, variable 10                    |
| <code>st_data((1,5), 10)</code>       | values of obs. 1 through 5, variable 10                    |
| <code>st_data((1,5)\(7,9), 10)</code> | values of obs. 1 through 5 and 7 through 9,<br>variable 10 |

---

`st_sdata()` works the same way as `st_data()`.

## Details of observation subscripting using `st_data()` and `st_sdata()`

1.  $i$  may be specified as a scalar: the specified, single observation is returned.  $i$  must be between 1 and `st_nobs()`; see [M-5] `st_nvar()`.
2.  $i$  may be specified as a scalar containing missing value: all observations are returned.
3.  $i$  may be specified as a column vector: the specified observations are returned. Each element of  $i$  must be between 1 and `st_nobs()` or may be missing. Missing is interpreted as `st_nobs()`.
4.  $i$  may be specified as a  $1 \times 2$  row vector: the specified range of observations is returned;  $(c_1, c_2)$  returns the  $c_2 - c_1 + 1$  observations  $c_1$  through  $c_2$ .  
  
 $c_2 - c_1 + 1$  must evaluate to a number greater than or equal to 0. In general,  $c_1$  and  $c_2$  must be between 1 and `st_nobs()`, but if  $c_2 - c_1 + 1 = 0$ , then  $c_1$  may be between 1 and `st_nobs()` + 1 and  $c_2$  may be between 0 and `st_nobs()`. Regardless,  $c_1 == .$  or  $c_2 == .$  is interpreted as `st_nobs()`.
5.  $i$  may be specified as a  $k \times 2$  matrix:  $((1,5)\(7,7)\(20,30))$  specifies observations 1 through 5, 7, and 20 through 30.

## Conformability

`_st_data(i, j)`, `_st_sdata(i, j)`:

$i$ :  $1 \times 1$   
 $j$ :  $1 \times 1$   
 result:  $1 \times 1$

`st_data(i, j)`, `st_sdata(i, j)`:

$i$ :  $n \times 1$  or  $n_2 \times 2$   
 $j$ :  $1 \times k$  or  $1 \times 1$  containing  $k$  elements when expanded  
 result:  $n \times k$

`st_data(i, j, selectvar)`, `st_sdata(i, j, selectvar)`:

$i$ :  $n \times 1$  or  $n_2 \times 2$   
 $j$ :  $1 \times k$  or  $1 \times 1$  containing  $k$  elements when expanded  
 $selectvar$ :  $1 \times 1$   
 result:  $(n - e) \times k$ , where  $e$  is number of observations excluded by  $selectvar$

## Diagnostics

`_st_data(i, j)` returns missing (`.`) if  $i$  or  $j$  is out of range; it does not abort with error.

`_st_sdata(i, j)` returns "" if  $i$  or  $j$  is out of range; it does not abort with error.

`st_data(i, j)` and `st_sdata(i, j)` abort with error if any element of  $i$  or  $j$  is out of range.  $j$  may be specified as variable names or variable indices. If names are specified, abbreviations are allowed. If you do not want this and no factor variables nor time-series-operated variables are specified, use `st_varindex()` (see [M-5] `st_varindex()`) to translate variable names into variable indices.

## Also see

[M-5] [st\\_view\(\)](#) — Make matrix that is a view onto current Stata dataset

[M-5] [st\\_store\(\)](#) — Modify values stored in current Stata dataset

[M-4] [stata](#) — Stata interface functions

[D] [putmata](#) — Put Stata variables into Mata and vice versa