

Description

`st_tempname()` returns a Stata temporary name, the same as would be returned by Stata's `tempvar` and `tempname` commands; see [P] [macro](#).

`st_tempname(n)` returns *n* temporary Stata names, $n \geq 0$.

`st_tempfilename()` returns a Stata temporary filename, the same as would be returned by Stata's `tempfile` command; see [P] [macro](#).

`st_tempfilename(n)` returns *n* temporary filenames, $n \geq 0$.

Syntax

string scalar `st_tempname()`

string rowvector `st_tempname(real scalar n)`

string scalar `st_tempfilename()`

string rowvector `st_tempfilename(real scalar n)`

Remarks and examples

Remarks are presented under the following headings:

Creating temporary objects

When temporary objects will be eliminated

Creating temporary objects

`st_tempname()`s can be used to name Stata's variables, matrices, and scalars. Although in Stata a distinction is drawn between `tempvars` and `tempnames`, there is no real distinction, and so `st_tempname()` handles both in Mata. For instance, one can create a temporary variable by coding

```
idx = st_addvar("double", st_tempname())
```

See [M-5] [st_addvar\(\)](#).

One creates a temporary file by coding

```
fh = fopen(st_tempfilename(), "w")
```

See [M-5] [fopen\(\)](#).

When temporary objects will be eliminated

Temporary objects do not vanish when the Mata function ends, nor when Mata itself ends. They are removed when the ado-file (or do-file) calling Mata terminates.

Forget Mata for a minute. Stata eliminates temporary variables and files when the program that created them ends. That same rule applies to Mata: Stata eliminates them, not Mata, and that means that the ado-file or do-file that called Mata will eliminate them when that ado-file or do-file ends. Temporary variables and files are not eliminated by Mata when the Mata function ends. Thus Mata functions can create temporary objects for use by their ado-file callers, should that prove useful.

Conformability

`st_tempname()`, `st_tempfilename()`:

result: 1×1

`st_tempname(n)`, `st_tempfilename(n)`:

n: 1×1

result: $1 \times n$

Diagnostics

`st_tempname(n)` and `st_tempfilename(n)` abort with error if $n < 0$ and return `J(1,0,"")` if $n = 0$.

Also see

[M-5] [st_addvar\(\)](#) — Add variable to current Stata dataset

[M-4] [Stata](#) — Stata interface functions

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).