

stataversion() — Version of Stata being used

Description
Diagnostics

Syntax
Also see

Remarks and examples

Conformability

Description

`stataversion()` returns the version of Stata/Mata that is running, multiplied by 100. For instance, if you have Stata 15 installed on your computer, `stataversion()` returns 1500.

`statatasetversion()` returns the version of Stata that has been set by the user—the version of Stata that Stata is currently emulating—multiplied by 100. Usually `stataversion() == statatasetversion()`. If the user has set a previous version—say, version 8 by typing `version 8` in Stata—`statatasetversion()` will return a number less than `stataversion()`.

`statatasetversion(version)` allows you to reset the version being emulated. Results are the same as using Stata's `version` command; see [P] [version](#). `version`, however, is specified as an integer equal to 100 times the version you want.

Syntax

real scalar `stataversion()`

real scalar `statatasetversion()`

void `statatasetversion(real scalar version)`

Note: The version number is multiplied by 100: Stata 2.0 is 200, Stata 5.1 is 510, and Stata 15.0 is 1500.

Remarks and examples

stata.com

It is usually not necessary to reset `statatasetversion()`. If you do reset `statatasetversion()`, good form is to set it back when you are finished:

```
current_version = statatasetversion()
statatasetversion(desired_version)
...
statatasetversion(current_version)
```

Conformability

```
stataversion():  
    result:    1 × 1  
  
statasetversion():  
    result:    1 × 1  
  
statasetversion(version):  
    version:   1 × 1  
    result:    void
```

Diagnostics

`statasetversion(version)` aborts with error if *version* is less than 100 or greater than `stataversion()`.

Also see

[M-5] [bufio\(\)](#) — Buffered (binary) I/O

[M-5] [byteorder\(\)](#) — Byte order used by computer

[M-4] [programming](#) — Programming functions