

stofreal() — Convert real to string

Description
Also see

Syntax

Remarks and examples

Conformability

Diagnostics

Description

`stofreal(R)` returns *R* as a string using Stata's %9.0g format. `stofreal(R)` is equivalent to `stofreal(R, "%9.0g")`.

`stofreal(R, format)` returns *R* as a string formatted using *format*.

Leading blanks are trimmed from the result.

When arguments are not scalar, `stofreal()` returns element-by-element results.

Syntax

string matrix `stofreal(real matrix R)`

string matrix `stofreal(real matrix R, string matrix format)`

Remarks and examples

stata.com

`stofreal()` will ignore the format specified with `set dp`. To display numeric values as strings while respecting the format specified with `set dp`, use `sprintf()`.

Conformability

`stofreal(R, format):`

<i>R</i> :	$r_1 \times c_1$	
<i>format</i> :	$r_2 \times c_2$,	<i>R</i> and <i>format</i> r-conformable (optional)
<i>result</i> :	$\max(r_1, r_2) \times \max(c_1, c_2)$	

Diagnostics

`stofreal(R, format)` returns "." if *format* is invalid.

Also see

[M-5] [strtoreal\(\)](#) — Convert string to real

[M-4] [String](#) — String manipulation functions