

sublowertriangle() — Return a matrix with zeros above a diagonal

[Description](#)

[Syntax](#)

[Remarks and examples](#)

[Conformability](#)

[Diagnostics](#)

[Also see](#)

Description

`sublowertriangle(A, p)` returns A with the elements above a diagonal set to zero. In the returned matrix, $A[i, j] = 0$ for all $i - j < p$. If it is not specified, p is set to zero.

`_sublowertriangle()` mirrors `sublowertriangle()` but modifies A .

`_sublowertriangle(A, p)` sets $A[i, j] = 0$ for all $i - j < p$. If it is not specified, p is set to zero.

Syntax

numeric matrix `sublowertriangle(numeric matrix A [, numeric scalar p])`

void `_sublowertriangle(numeric matrix A [, numeric scalar p])`

where argument p is optional.

Remarks and examples

Remarks are presented under the following headings:

[Get lower triangle of a matrix](#)
[Nonsquare matrices](#)

Get lower triangle of a matrix

If A is a square matrix, then `sublowertriangle(A, 0) = lowertriangle(A)`.

`sublowertriangle()` is a generalization of `lowertriangle()`.

We begin by defining A

```
: A = (1, 2, 3 \ 4, 5, 6 \ 7, 8, 9)
```

`sublowertriangle(A, 0)` returns A with zeros above the main diagonal as does `lowertriangle()`:

```
: sublowertriangle(A, 0)
```

	1	2	3
1	1	0	0
2	4	5	0
3	7	8	9

sublowertriangle(A, 1) returns A with zeros in the main diagonal and above.

```
: sublowertriangle(A, 1)
```

```
1  2  3
```

1	0	0	0
2	4	0	0
3	7	8	0

sublowertriangle(A, p) can take negative p . For example, setting $p = -1$ yields

```
: sublowertriangle(A, -1)
```

```
1  2  3
```

1	1	2	0
2	4	5	6
3	7	8	9

Nonsquare matrices

sublowertriangle() and _sublowertriangle() may be used with nonsquare matrices.

For instance, we define a nonsquare matrix A

```
: A = (1, 2, 3, 4 \ 5, 6, 7, 8 \ 9, 10, 11, 12)
```

We use sublowertriangle() to obtain the lower triangle of A:

```
: sublowertriangle(A, 0)
```

```
1  2  3  4
```

1	1	0	0	0
2	5	6	0	0
3	9	10	11	0

Conformability

`sublowertriangle(A, p)`:

input:

A : $r \times c$

p : 1×1 (optional)

output:

result: $r \times c$

`_sublowertriangle(A, p)`:

input:

A : $r \times c$

p : 1×1 (optional)

output:

A : $r \times c$

Diagnostics

None.

Also see

[M-4] [Manipulation](#) — Matrix manipulation

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).