

## Description

`unlink(filename)` erases *filename* if it exists, does nothing if *filename* does not exist, and aborts with error if *filename* exists but cannot be erased.

`_unlink(filename)` does the same, except that, if *filename* cannot be erased, rather than aborting with error, `_unlink()` returns a negative error code. `_unlink()` returns 0 if *filename* was erased or *filename* did not exist.

## Syntax

```
void          unlink(string scalar filename)
real scalar   _unlink(string scalar filename)
```

## Remarks and examples

To remove directories, see `rmdir()` in [\[M-5\] chdir\(\)](#).

## Conformability

```
unlink(filename)
  filename:    1 × 1
  result:      void

_unlink(filename)
  filename:    1 × 1
  result:      1 × 1
```

## Diagnostics

`unlink(filename)` aborts with error when `_unlink()` would give a negative result.

`_unlink(filename)` returns a negative result if the file cannot be erased and returns 0 otherwise. If the file did not exist, 0 is returned. When there is an error, most commonly returned are -3602 (filename invalid) or -3621 (file is read-only).

## Also see

### [\[M-4\] IO](#) — I/O functions

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

