

Description

`ustrreverse(string matrix s)` reverses the Unicode string *s*.

When arguments are not scalar, this function returns element-by-element results.

Syntax

string matrix `ustrreverse(string matrix s)`

Remarks and examples

The function does not take [Unicode character equivalence](#) into consideration. Hence, a Unicode character in a decomposed form will not be reversed as one unit. An invalid UTF-8 sequence is replaced with a Unicode replacement character `\ufffd`.

Use `strreverse()` to return a string with its bytes in reverse order.

Conformability

`ustrreverse(s)`:
s: $r \times c$
result: $r \times c$

Diagnostics

`ustrreverse(s)` returns an empty string if an error occurs.

Also see

[M-5] [strreverse\(\)](#) — Reverse string

[M-4] [String](#) — String manipulation functions

[U] [12.4.2 Handling Unicode strings](#)

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).