

estat wcorrelation — Display within-cluster correlations and standard deviations

[Description](#)

[Remarks and examples](#)

[Also see](#)

[Menu for estat](#)

[Stored results](#)

[Syntax](#)

[Methods and formulas](#)

[Options](#)

[Reference](#)

Description

`estat wcorrelation` is for use after estimation with `menl` and `mixed`.

`estat wcorrelation` displays the overall correlation matrix for a given cluster calculated on the basis of the design of the random effects and their assumed covariance and the correlation structure of the residuals. This allows for a comparison of different multilevel models in terms of the ultimate within-cluster correlation matrix that each model implies.

Menu for estat

Statistics > Postestimation

Syntax

```
estat wcorrelation [ , options ]
```

<i>options</i>	Description
<code>at(<i>at_spec</i>)</code>	specify the cluster for which you want the correlation matrix; default is the first two-level cluster encountered in the data
<code>all</code>	display correlation matrix for all the data
<code>covariance</code>	display the covariance matrix instead of the correlation matrix
<code>list</code>	list the data corresponding to the correlation matrix
<code>nosort</code>	list the rows and columns of the correlation matrix in the order they were originally present in the data
<code>iterate(#)</code>	maximum number of iterations to compute random effects; default is <code>iterate(50)</code> ; only for use after <code>menl</code>
<code>tolerance(#)</code>	convergence tolerance when computing random effects; default is <code>tolerance(1e-4)</code> ; only for use after <code>menl</code>
<code>format(%<i>fmt</i>)</code>	set the display format; default is <code>format(%6.3f)</code>
<code>matlist_options</code>	style and formatting options that control how matrices are displayed

Options

`at(at_spec)` specifies the cluster of observations for which you want the within-cluster correlation matrix. *at_spec* is

```
relevel_var = value [, relevel_var = value ...]
```

For example, if you specify

```
. estat wcorrelation, at(school = 33)
```

you get the within-cluster correlation matrix for those observations in school 33. If you specify

```
. estat wcorrelation, at(school = 33 classroom = 4)
```

you get the correlation matrix for classroom 4 in school 33.

If `at()` is not specified, then you get the correlations for the first level-two cluster encountered in the data. This is usually what you want.

`all` specifies that you want the correlation matrix for all the data. This is not recommended unless you have a relatively small dataset or you enjoy seeing large $n \times n$ matrices. However, this can prove useful in some cases.

`covariance` specifies that the within-cluster covariance matrix be displayed instead of the default correlations and standard deviations.

`list` lists the model data for those observations depicted in the displayed correlation matrix. With linear mixed-effects models, this option is also useful if you have many random-effects design variables and you wish to see the represented values of these design variables.

`nosort` lists the rows and columns of the correlation matrix in the order that they were originally present in the data. Normally, `estat wcorrelation` will first sort the data according to level variables, by-group variables, and time variables to produce correlation matrices whose rows and columns follow a natural ordering. `nosort` suppresses this.

`iterate(#)` specifies the maximum number of iterations when computing estimates of the random effects. The default is `iterate(50)`. This option is only for use after `menl`.

`tolerance(#)` specifies a convergence tolerance when computing estimates of the random effects. The default is `tolerance(1e-4)`. This option is only for use after `menl`.

`format(%fmt)` sets the display format for the standard-deviation vector and correlation matrix. The default is `format(%6.3f)`.

matlist_options are style and formatting options that control how the matrix (or matrices) is displayed; see [P] [matlist](#) for a list of options that are available.

Remarks and examples

[stata.com](http://www.stata.com)

► Example 1: Displaying within-cluster correlations for different clusters

Here we fit a model where different clusters have different within-cluster correlations, and we show how to display them for different clusters. We use the Asian children weight data from [example 6 of \[ME\] mixed](#).

```
. use http://www.stata-press.com/data/r15/childweight
(Weight data on Asian children)
. mixed weight age || id: age, covariance(unstructured)
```

Performing EM optimization:

Performing gradient-based optimization:

```
Iteration 0: log likelihood = -344.37065
Iteration 1: log likelihood = -342.83887
Iteration 2: log likelihood = -342.71863
Iteration 3: log likelihood = -342.71777
Iteration 4: log likelihood = -342.71777
```

Computing standard errors:

```
Mixed-effects ML regression      Number of obs    =      198
Group variable: id              Number of groups =       68
                                Obs per group:
                                min =          1
                                avg =         2.9
                                max =          5
                                Wald chi2(1)    =      755.27
                                Prob > chi2     =      0.0000
```

Log likelihood = -342.71777

weight	Coef.	Std. Err.	z	P> z	[95% Conf. Interval]	
age	3.459671	.1258877	27.48	0.000	3.212936	3.706406
_cons	5.110496	.1494781	34.19	0.000	4.817524	5.403468

Random-effects Parameters	Estimate	Std. Err.	[95% Conf. Interval]	
id: Unstructured				
var(age)	.202392	.1242868	.0607406	.6743838
var(_cons)	.0970272	.1107998	.0103483	.9097447
cov(age, _cons)	.140134	.0566901	.0290234	.2512445
var(Residual)	1.357922	.1650502	1.070076	1.723198

LR test vs. linear model: chi2(3) = 27.38 Prob > chi2 = 0.0000

Note: LR test is conservative and provided only for reference.

We use `estat wcorrelation` to display the within-cluster correlations for the first cluster.

```
. estat wcorrelation, list
```

Standard deviations and correlations for id = 45:

Standard deviations:

obs	1	2	3	4	5
sd	1.224	1.314	1.448	1.506	1.771

Correlations:

obs	1	2	3	4	5
1	1.000				
2	0.141	1.000			
3	0.181	0.274	1.000		
4	0.193	0.293	0.376	1.000	
5	0.230	0.348	0.447	0.477	1.000

Data:

	id	weight	age
1.	45	5.171	.136893
2.	45	10.86	.657084
3.	45	13.15	1.21834
4.	45	13.2	1.42916
5.	45	15.88	2.27242

We specified the `list` option to display the data associated with the cluster. The next cluster in the dataset has ID 258. To display the within-cluster correlations for this cluster, we specify the `at()` option.

```
. estat wcorrelation, at(id=258) list
```

Standard deviations and correlations for id = 258:

Standard deviations:

obs	1	2	3	4
sd	1.231	1.320	1.424	1.782

Correlations:

obs	1	2	3	4
1	1.000			
2	0.152	1.000		
3	0.186	0.270	1.000	
4	0.244	0.356	0.435	1.000

Data:

	id	weight	age
1.	258	5.3	.19165
2.	258	9.74	.687201
3.	258	9.98	1.12799
4.	258	11.34	2.30527

The within-cluster correlations for this model depend on age. The values for `age` in the two clusters are different, as are the corresponding within-cluster correlations.

See [example 1](#) of [ME] [mixed postestimation](#) for a model fit where each cluster had the same model-implied within-cluster correlations.

Stored results

estat wcorrelation stores the following in `r()`:

Matrices

<code>r(sd)</code>	standard deviations
<code>r(Corr)</code>	within-cluster correlation matrix
<code>r(Cov)</code>	within-cluster variance-covariance matrix
<code>r(G)</code>	variance-covariance matrix of random effects
<code>r(Z)</code>	model-based design matrix
<code>r(R)</code>	variance-covariance matrix of level-one errors

Results `r(G)`, `r(Z)`, and `r(R)` are available only after `mixed`.

Methods and formulas

Methods and formulas are presented under the following headings:

[Linear mixed-effects model](#)

[Nonlinear mixed-effects model](#)

Linear mixed-effects model

A two-level linear mixed model of the form

$$\mathbf{y}_j = \mathbf{X}_j\boldsymbol{\beta} + \mathbf{Z}_j\mathbf{u}_j + \boldsymbol{\epsilon}_j$$

implies the marginal model

$$\mathbf{y}_j = \mathbf{X}_j\boldsymbol{\beta} + \boldsymbol{\epsilon}_j^*$$

where $\boldsymbol{\epsilon}_j^* \sim N(\mathbf{0}, \mathbf{V}_j)$, $\mathbf{V}_j = \mathbf{Z}_j\mathbf{G}\mathbf{Z}_j' + \mathbf{R}$. In a marginal model, the random part is described in terms of the marginal or total residuals $\boldsymbol{\epsilon}_j^*$, and \mathbf{V}_j is the covariance structure of these residuals.

estat wcorrelation calculates the marginal covariance matrix $\tilde{\mathbf{V}}_j$ for cluster j and by default displays the results in terms of standard deviations and correlations. This allows for a comparison of different multilevel models in terms of the ultimate within-cluster correlation matrix that each model implies.

Calculation of the marginal covariance matrix extends naturally to higher-level models; see, for example, chapter 4.8 in [West, Welch, and Galecki \(2015\)](#).

Nonlinear mixed-effects model

For nonlinear mixed-effects models, there is no closed-form expression for the marginal covariance matrix $\text{Cov}(\mathbf{y}_j)$. This is because it is expressed in terms of a q -dimensional integral (q is the number of random effects in the model), which, in general, is analytically intractable. Under the linear mixed-effects approximation, the marginal covariance matrix is estimated by $\hat{\mathbf{V}}_j = \hat{\mathbf{Z}}_j\hat{\boldsymbol{\Sigma}}\hat{\mathbf{Z}}_j' + \hat{\sigma}^2\hat{\boldsymbol{\Lambda}}_j$, where $\hat{\mathbf{Z}}_j$, $\hat{\boldsymbol{\Sigma}}$, and $\hat{\boldsymbol{\Lambda}}_j$ are defined in [Methods and formulas](#) of [ME] [menl](#).

`estat wcorrelation` calculates the estimated marginal covariance matrix $\widehat{\mathbf{V}}_j$ for cluster j and by default displays the results in terms of standard deviations and correlations.

Under the linear mixed-effects approximation, estimation of the marginal covariance matrix extends naturally to higher-level models; see, for example, chapter 4.8 in [West, Welch, and Gálecki \(2015\)](#).

Reference

West, B. T., K. B. Welch, and A. T. Gálecki. 2015. *Linear Mixed Models: A Practical Guide Using Statistical Software*. 2nd ed. Boca Raton, FL: Chapman & Hall/CRC.

Also see

[ME] [menl](#) — Nonlinear mixed-effects regression

[ME] [mixed](#) — Multilevel mixed-effects linear regression

[U] [20 Estimation and postestimation commands](#)