

mi export ice — Export mi data to ice format

Description Menu Syntax Option
 Remarks and examples References Also see

Description

`mi export ice` converts the `mi` data in memory to `ice` format. See [Royston \(2004, 2005a, 2005b, 2007, 2009\)](#) for a description of `ice`.

Menu

Statistics > Multiple imputation

Syntax

```
mi export ice [ , clear ]
```

Option

`clear` specifies that it is okay to replace the data in memory even if they have changed since they were last saved to disk.

Remarks and examples

`mi export ice` is the inverse of `mi import ice` (see [\[MI\] mi import ice](#)). Below we use `mi export ice` to convert `miproto.dta` to `ice` format. `miproto.dta` happens to be in wide form, but that is irrelevant.

```
. use http://www.stata-press.com/data/r15/miproto
(mi prototype)
. mi describe
Style: wide
last mi update 20jan2017 14:52:05, approximately 22 hours ago
Obs.: complete 1
incomplete 1 (M = 2 imputations)
-----
total 2
Vars.: imputed: 1; b(1)
passive: 1; c(1)
regular: 1; a
system: 1; _mi_miss
(there are no unregistered variables)
. list
```

	a	b	c	_1_b	_2_b	_1_c	_2_c	_mi_miss
1.	1	2	3	2	2	3	3	0
2.	4	.	.	4.5	5.5	8.5	9.5	1

```
. mi export ice  
. list, separator(2)
```

	a	b	c	_mj	_mi
1.	1	2	3	0	1
2.	4	.	.	0	2
3.	1	2	3	1	1
4.	4	4.5	8.5	1	2
5.	1	2	3	2	1
6.	4	5.5	9.5	2	2

References

- Royston, P. 2004. Multiple imputation of missing values. *Stata Journal* 4: 227–241.
- . 2005a. Multiple imputation of missing values: Update. *Stata Journal* 5: 188–201.
- . 2005b. Multiple imputation of missing values: Update of ice. *Stata Journal* 5: 527–536.
- . 2007. Multiple imputation of missing values: Further update of ice, with an emphasis on interval censoring. *Stata Journal* 7: 445–464.
- . 2009. Multiple imputation of missing values: Further update of ice, with an emphasis on categorical variables. *Stata Journal* 9: 466–477.

Also see

- [MI] [intro](#) — Introduction to mi
- [MI] [mi export](#) — Export mi data
- [MI] [mi import ice](#) — Import ice-format data into mi