

Description

`mi extract #` replaces the data in memory with the data for $m = \#$. The data are not `mi set`.

Menu

Statistics > Multiple imputation

Syntax

`mi extract # [, options]`

where $0 \leq \# \leq M$

<i>options</i>	Description
<code>clear</code>	okay to replace unsaved data in memory
<code>esample(...)</code>	rarely specified option
<code>esample(<i>varname</i>)</code>	... syntax when $\# > 0$
<code>esample(<i>varname</i> $\#_e$)</code>	... syntax when $\# = 0$; $1 \leq \#_e \leq M$

Options

`clear` specifies that it is okay to replace the data in memory even if the current data have not been saved to disk.

`esample(varname [$\#_e$])` is rarely specified. It is for use after `mi estimate` (see [MI] [mi estimate](#)) when the `esample(newvar)` option was specified to store in *newvar* the `e(sample)` for $m = 1, m = 2, \dots, m = M$. It is now desired to extract the data for one m and for `e(sample)` set correspondingly.

`mi extract #, esample(varname), $\# > 0$` , is the usual case in this unlikely event. One extracts one of the imputation datasets and redefines `e(sample)` based on the `e(sample)` previously stored for $m = \#$.

The odd case is `mi extract 0, esample(varname $\#_e$)`, where $\#_e > 0$. One extracts the original data but defines `e(sample)` based on the `e(sample)` previously stored for $m = \#_e$.

Specifying the `esample()` option changes the sort order of the data.

Remarks and examples

If you wanted to give up on `mi` and just get your original data back, you could type

```
. mi extract 0
```

You might do this if you wanted to send your original data to a coworker or you wanted to try a different approach to dealing with the missing values in these data. Whatever the reason, the result is that the original data replace the data in memory. The data are not `mi set`. Your original `mi` data remain unchanged.

If you suspected there was something odd about the imputations in $m = 3$, you could type

```
. mi extract 3
```

You would then have a dataset in memory that looked just like your original, except the missing values of the imputed and passive variables would be replaced with the imputed and passive values from $m = 3$. The data are not `mi set`. Your original data remain unchanged.

Also see

[MI] [Intro](#) — Introduction to `mi`

[MI] [mi replace0](#) — Replace original data

