mi import wide — Import wide-like data into mi

Description Menu Syntax Options
Remarks and examples Also see

Description

`mi import wide` imports wide-like data, that is, data in which $m = 0$, $m = 1$, …, $m = M$ values of imputed and passive variables are recorded in separate variables.

`mi import wide` converts the data to `mi` wide style and `mi sets` the data.

Menu

Statistics > Multiple imputation

Syntax

`mi import wide` [, *options*]

options	Description
`imputed(`*mvlist*`)`	imputed variables
`passive(`*mvlist*`)`	passive variables
`dupsok`	allow variable to be posted repeatedly
`drop`	drop imputed and passive after posting
`clear`	okay to replace unsaved data in memory

See description of options below for definition of *mvlist*.

Options

`imputed(`*mvlist*`)` and `passive(`*mvlist*`)` specify the imputed and passive variables.

For instance, if the data had two imputed variables, `x` and `y`; `x` and `y` contained the $m = 0$ values; the corresponding $m = 1$, $m = 2$, and $m = 3$ values of `x` were in `x1`, `x2`, and `x3`; and the corresponding values of `y` were in `y1`, `y2`, and `y3`, then the `imputed()` option would be specified as

```
imputed(x=x1 x2 x3 y=y1 y2 y3)
```

If variable `y2` were missing from the data, you would specify

```
imputed(x=x1 x2 x3 y=y1 . y3)
```

The same number of imputations must be specified for each variable.

`dupsok` specifies that it is okay if you specify the same variable name for two different imputations. This would be an odd thing to do, but if you specify `dupsok`, then you can specify

```
imputed(x=x1 x1 x3 y=y1 y2 y3)
```

Without the `dupsok` option, the above would be treated as an error.

drop specifies that the original variables containing values for $m = 1$, $m = 2$, …, $m = M$ are to be dropped from the data once mi import wide has recorded the values. This option is recommended.

clear specifies that it is okay to replace the data in memory even if they have changed since they were last saved to disk.

Remarks and examples

The procedure to convert wide-like data to mi wide style is this:

1. use the unset data; see [D] **use**.
2. Issue the mi import wide command.
3. Use mi describe (see [MI] **mi describe**) and mi varying (see [MI] **mi varying**) to verify that the result is as you anticipated.
4. Optionally, use mi convert (see [MI] **mi convert**) to convert the data to what you consider a more convenient style.

For instance, you have been given unset dataset wi.dta and have been told that it contains variables a, b, and c; that variable b is imputed and contains $m = 0$ values; that variables b1 and b2 contain the $m = 1$ and $m = 2$ values; that variable c is passive (equal to a + b) and contains $m = 0$ values; and that variables c1 and c2 contain the corresponding $m = 1$ and $m = 2$ values. Here are the data:

```
. use https://www.stata-press.com/data/r19/wi
(mi prototype)
. list
```

	a	b	c	b1	b2	c1	c2
1.	1	2	3	2	2	3	3
2.	4	.	.	4.5	5.5	8.5	9.5

These are the same data discussed in [MI] **Styles**. To import these data, type

```
. mi import wide, imputed(b=b1 b2  c=c1 c2) drop
```

These data are short enough that we can list the result:

```
. list
```

	a	b	c	_mi_miss	_1_b	_2_b	_1_c	_2_c
1.	1	2	3	0	2	2	3	3
2.	4	.	.	1	4.5	5.5	8.5	9.5

Returning to the procedure, we run `mi describe` and `mi varying` on the result:

```
. mi describe
Style: wide
       last mi update 03mar2025 18:20:16, 0 seconds ago
Observations:
   Complete            1
   Incomplete          1  (M = 2 imputations)
   ---------------------
   Total               2
Variables:
   Imputed: 2; b(1) c(1)
   Passive: 0
   Regular: 0
   System:  1; _mi_miss
   (there is one unregistered variable; a)
. mi varying
            Possible problem   Variable names
-------------------------------------------------------------------------------
         imputed nonvarying:  (none)
         passive nonvarying:  (none)
-------------------------------------------------------------------------------
```

Perhaps you would prefer seeing these data in flong style:

```
. mi convert flong, clear
. list, separator(2)
```

	a	b	c	_mi_miss	_mi_m	_mi_id
1.	1	2	3	0	0	1
2.	4	.	.	1	0	2
3.	1	2	3	.	1	1
4.	4	4.5	8.5	.	1	2
5.	1	2	3	.	2	1
6.	4	5.5	9.5	.	2	2

Also see

[MI] **Intro** — Introduction to mi

[MI] **mi import** — Import data into mi

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on citing Stata documentation.