Description Remarks and examples Also see

Description

Technical information for programmers who wish to extend `mi` is provided below.

Remarks and examples

Remarks are presented under the following headings:

Notation
Definition of styles
  Style all
  Style wide
  Style mlong
  Style flong
  Style flongsep
  Style flongsep_sub
Adding new commands to mi
Outline for new commands
Utility routines
  u_mi_assert_set
  u_mi_certify_data
  u_mi_no_sys_vars and u_mi_no_wide_vars
  u_mi_zap_chars
  u_mi_xeq_on_tmp_flongsep
  u_mi_get_flongsep_tmpname
  mata: u_mi_flongsep_erase()
  u_mi_sortback
  u_mi_save and u_mi_use
  mata: u_mi_wide_swapvars()
  u_mi_fixchars
  mata: u_mi_cpchars_get() and mata: u_mi_cpchars_put()
  mata: u_mi_get_mata_instanced_var()
  mata: u_mi_ptrace_*()
How to write other set commands to work with mi

Notation

$M = \#$ of imputations

$m =$ imputation number
  0. original data with missing values
  1. first imputation dataset
  .
  .
  M. last imputation dataset

$N =$ number of observations in $m = 0$

Definition of styles

Style describes how the mi data are stored. There are four styles: wide, mlong, flong, and flongsep.

Style all

Characteristics:

_dta[_mi_marker]	"_mi_ds_1"

Description: _dta[_mi_marker] is set with all styles, including flongsep_sub. The definitions below apply only if "‘_dta[_mi_marker]’" = "_mi_ds_1".

Style wide

Characteristics:

_dta[_mi_style]	"wide"
_dta[_mi_M]	M
_dta[_mi_ivars]	imputed variables; variable list
_dta[_mi_pvars]	passive variables; variable list
_dta[_mi_rvars]	regular variables; variable list
_dta[_mi_update]	time last updated; %tc_value/1000

Variables:

_mi_miss	whether incomplete; 0 or 1
_#_*varname*	*varname* for $m = \#$, defined for each ‘_dta[_mi_ivars]’ and ‘_dta[_mi_pvars]’

Description: $m = 0$, $m = 1$, …, $m = M$ are stored in one dataset with $_N = N$ observations. Each imputed and passive variable has M additional variables associated with it. If variable bp contains the values in $m = 0$, then values for $m = 1$ are contained in variable _1_bp, values for $m = 2$ in _2_bp, and so on. wide stands for *wide*.

Style mlong

Characteristics:

_dta[_mi_style]	"mlong"
_dta[_mi_M]	M
_dta[_mi_N]	N
_dta[_mi_n]	# of observations in marginal
_dta[_mi_ivars]	imputed variables; variable list
_dta[_mi_pvars]	passive variables; variable list
_dta[_mi_rvars]	regular variables; variable list
_dta[_mi_update]	time last updated; %tc_value/1000

Variables:

_mi_m	m; 0, 1, …, M
_mi_id	ID; 1, …, N
_mi_miss	whether incomplete; 0 or 1 if _mi_m = 0, else .

Description: $m = 0$, $m = 1$, …, $m = M$ are stored in one dataset with $_N = N + M \times n$ observations, where n is the number of incomplete observations in $m = 0$. mlong stands for *marginal long*.

Style flong

Characteristics:

_dta[_mi_style]	"flong"
_dta[_mi_M]	M
_dta[_mi_N]	N
_dta[_mi_ivars]	imputed variables; variable list
_dta[_mi_pvars]	passive variables; variable list
_dta[_mi_rvars]	regular variables; variable list
_dta[_mi_update]	time last updated; %tc_value/1000

Variables:

_mi_m	m; 0, 1, …, M
_mi_id	ID; 1, …, N
_mi_miss	whether incomplete; 0 or 1 if _mi_m $= 0$, else .

Description: $m = 0$, $m = 1, \ldots, m = M$ are stored in one dataset with $_N = N + M \times N$ observations, where N is the number of observations in $m = 0$. flong stands for *full long*.

Style flongsep

Characteristics:

_dta[_mi_style]	"flongsep"
_dta[_mi_name]	*name*
_dta[_mi_M]	M
_dta[_mi_N]	N
_dta[_mi_ivars]	imputed variables; variable list
_dta[_mi_pvars]	passive variables; variable list
_dta[_mi_rvars]	regular variables; variable list
_dta[_mi_update]	time last updated; %tc_value/1000

Variables:

_mi_id	ID; 1, …, N
_mi_miss	whether incomplete; 0 or 1

Description: $m = 0$, $m = 1, \ldots, m = M$ are each separate .dta datasets. If $m = 0$ data are stored in pat.dta, then $m = 1$ data are stored in _1_pat.dta, $m = 2$ in _2_pat.dta, and so on.

The definitions above apply only to $m = 0$, the dataset named '_dta[_mi_name]'.dta. See *Style flongsep_sub* directly below for $m > 0$. flongsep stands for *full long and separate*.

Style flongsep_sub

Characteristics:

_dta[_mi_style]	"flongsep_sub"
_dta[_mi_name]	*name*
_dta[_mi_m]	m; 0, 1, …, M

Variables:

_mi_id	ID; 1, …, N

Description: The description above applies to the _'_dta[_mi_m]'_'_dta[_mi_name]'.dta datasets. There are M such datasets recording $m = 1, \ldots, M$ used by the flongsep style directly above.

Adding new commands to mi

New commands are written in ado. Name the new command `mi_cmd_`*newcmd* and store it in `mi_cmd_`*newcmd*`.ado`. When the user types `mi` *newcmd* ..., `mi_cmd_`*newcmd*`.ado` will be executed.

See *Writing programs for use with mi* of [P] **program properties** for details on how to write estimation commands for use with the `mi estimate` prefix.

Outline for new commands

```
program mi_cmd_newcmd, rclass                                    (1)
        version 19.5      // (or version 19 if you do not have StataNow)

        u_mi_assert_set                                          (2)

        syntax ... [, ... noUPdate ...]                          (3)

        ...

        u_mi_certify_data, acceptable                            (4)

        ...

        if ("`update'"=="") {
                u_mi_certify_data, proper                        (5)
        }

        ...
end
```

Notes:

1. The command may be `rclass`; that is not required. It may be `eclass` instead if you wish.
2. `u_mi_assert_set` verifies that the data are `mi` data; see *u_mi_assert_set* below.
3. If you intend for your command to use `mi update` to update the data before performing its intended task, include a `noupdate` option; see [MI] **noupdate option**. Some commands instead or in addition run `mi update` to perform cleanup after performing their task. Such use does not require a `noupdate` option.
4. `u_mi_certify_data` is the internal routine that performs `mi update`. An update is divided into two parts, called acceptable and proper. All commands should verify that the data are acceptable; see *u_mi_certify_data* below.
5. `u_mi_certify_data, proper` performs the second step of `mi update`; it verifies that acceptable data are proper. Whether you verify properness is up to you, but if you do, you are supposed to include a `noupdate` option to skip running the check.

Utility routines

The only information you absolutely need to know is that already revealed. Using the utility routines described below, however, will simplify your programming task and make your code appear more professional to the end user.

As you read what follows, remember that you may review the source code for the routines by using viewsource; see [P] **viewsource**. If you wanted to see the source for u_mi_assert_set, you would type viewsource u_mi_assert_set.ado. If you do this, you will sometimes see that the routines allow options not documented below. Ignore those options; they may not appear in future releases.

Using viewsource, you may also review examples of the utility commands being used by viewing the source of the mi commands we have written. Each mi command appears in the file mi_cmd_*command*.ado. Also remember that other mi commands make useful utility routines. For instance, if your new command makes passive variables, use mi register to register them. Always call existing mi commands through mi; code mi passive and not mi_cmd_passive.

u_mi_assert_set

u_mi_assert_set [*desired_style*]

This utility verifies that data are mi and optionally of the desired style; it issues the appropriate error message and stops execution if not. The optional argument *desired_style* can be wide, mlong, flong, or flongsep, but is seldom specified. When not specified, any style is allowed.

u_mi_certify_data

u_mi_certify_data [, acceptable proper noupdate sortok]

This command performs mi update. mi update is equivalent to u_mi_certify_data, acceptable proper sortok.

Specify one or both of acceptable and proper. If the noupdate option is specified, then proper is specified. The sortok option specifies that u_mi_certify_data need not spend extra time to preserve and restore the original sort order of the data.

An update is divided into two parts. In the first part, called acceptable, $m = 0$ and the _dta[_mi_*] characteristics are certified. Your program will use the information recorded in those characteristics, and before that information can be trusted, the data must be certified as acceptable. Do not trust any _dta[_mi_*] characteristics until you have run u_mi_certify_data, acceptable.

u_mi_certify_data, proper verifies that data known to be acceptable are proper. In practice, this means that in addition to trusting $m = 0$, you can trust $m > 0$.

Running u_mi_certify_data, acceptable might actually result in the data being certified as proper, although you cannot depend on that. When you run u_mi_certify_data, acceptable and certain problems are observed in $m = 0$, they are fixed in all m, which can lead to other problems being detected, and by the time the whole process is through, the data are proper.

u_mi_no_sys_vars and u_mi_no_wide_vars

u_mi_no_sys_vars "*variable_list*" ["*word*"]

u_mi_no_wide_vars "*variable_list*" ["*word*"]

These routines are for use in parsing user input.

u_mi_no_sys_vars verifies that the specified list of variable names does not include any mi system variables such as _mi_m, _mi_id, _mi_miss, etc.

u_mi_no_wide_vars verifies that the specified list of variable names does not include any style wide $m > 0$ variables of the form _#_*varname*. u_mi_no_wide_vars may be called with any style of data but does nothing if the style is not wide.

Both functions issue appropriate error messages if problems are found. If *word* is specified, the error message will be "*word* may not include …". Otherwise, the error message is "may not specify …".

u_mi_zap_chars

u_mi_zap_chars

u_mi_zap_chars deletes all _dta[_mi_*] characteristics from the data in memory.

u_mi_xeq_on_tmp_flongsep

u_mi_xeq_on_tmp_flongsep [, nopreserve]: *command*

u_mi_xeq_on_tmp_flongsep executes *command* on the data in memory, said data converted to style flongsep, and then converts the flongsep result back to the original style. If the data already are flongsep, a temporary copy is made and, at the end, posted back to the original. Either way, *command* is run on a temporary copy of the data. If anything goes wrong, the user's original data are restored; that is, they are restored unless nopreserve is specified. If *command* completes without error, the flongsep data in memory are converted back to the original style and the original data are discarded.

It is not uncommon to write commands that can deal only with flongsep data, and yet these seem to users as if they work with all styles. That is because the routines use u_mi_xeq_on_tmp_flongsep. They start by allowing any style, but the guts of the routine are written assuming flongsep. mi stjoin is implemented in this way. There are two parts to mi stjoin: mi_cmd_stjoin.ado and mi_sub_stjoin_flongsep.ado. mi_cmd_stjoin.ado ends with

```
u_mi_xeq_on_tmp_flongsep: mi_sub_stjoin_flongsep `if', `options'
```

mi_sub_stjoin_flongsep does all the work, while u_mi_xeq_on_tmp_flongsep handles the issue of converting to flongsep and back again. The mi_sub_stjoin_flongsep subroutine must appear in its own ado-file because u_mi_xeq_on_tmp_flongsep is itself implemented as an ado-file. u_mi_xeq_on_tmp_flongsep would be unable to find the subroutine otherwise.

u_mi_get_flongsep_tmpname

u_mi_get_flongsep_tmpname *macname* : *basename*

u_mi_get_flongsep_tmpname creates a temporary flongsep name based on *basename* and stores it in the local macro *macname*. u_mi_xeq_on_tmp_flongsep, for your information, obtains the temporary name it uses from this routine.

u_mi_get_flongsep_tmpname is seldom used directly because u_mi_xeq_on_tmp_flongsep works well for shifting temporarily into flongsep mode, and u_mi_xeq_on_tmp_flongsep does a lot more than just getting a name under which the data should be temporarily stored. There are instances, however, when one needs to be more involved in the conversion. For examples, see the source mi_cmd_append.ado and mi_cmd_merge.ado. The issue these two routines face is that they need to shift two input datasets to flongsep, then they create a third from them, and that is the only one that needs to be shifted back to the original style. So these two commands handle the conversions themselves using u_mi_get_flongsep_tmpname and mi convert (see [MI] **mi convert**).

For instance, they start with something like

```
u_mi_get_flongsep_tmpname master : __mimaster
```

That creates a temporary name suitable for use with `mi convert` and stores it in `‘master’`. The suggested name is `__mimaster`, but if that name is in use, then `u_mi_get_flongsep_tmpname` will form from it `__mimaster1`, or `__mimaster2`, etc. We recommend that you specify a *basename* that begins with `__mi`, which is to say, two underscores followed by `mi`.

Next you must appreciate that it is your responsibility to eliminate the temporary files. You do that by coding something like

```
...
local origstyle "‘_dta[_mi_style]’"
if ("‘origstyle’"=="flongsep") {
        local origstyle "‘origstyle’ ‘_dta[_mi_name]’"
}
u_mi_get_flongsep_tmpname master : __mimaster
capture {
        quietly mi convert flongsep ‘master’
        ...
        ...
        quietly mi convert ‘origstyle’, clear replace
{
nobreak {
        local rc = _rc
        mata: u_mi_flongsep_erase("‘master’", 0, 0)
        if (‘rc’) {
                exit ‘rc’
        }
}
```

The other thing to note above is our use of `mi convert ‘master’` to convert our data to flongsep under the name `‘master’`. What, you might wonder, happens if our data already is flongsep? A nice feature of `mi convert` is that when run on data that are already flongsep, it performs an `mi copy`; see [MI] **mi copy**.

mata: u_mi_flongsep_erase()

`mata: u_mi_flongsep_erase("`*name*`",` *from* `[ ,` *output* `])`

where

name	*string*; flongsep name
from	#; where to begin erasing
output	0|1; whether to produce output

`mata: u_mi_flongsep_erase()` is the internal version of `mi erase` (see [MI] **mi erase**); use whichever is more convenient.

Input *from* is usually specified as 0 and then `mata: u_mi_flongsep_erase()` erases *name*`.dta`, `_1_`*name*`.dta`, `_2_`*name*`.dta`, and so on. *from* may be specified as a number greater than zero, however, and then erased are `_<`*from*`>_`*name*`.dta`, `_<`*from+1*`>_`*name*`.dta`, `_<`*from+2*`>_`*name*`.dta`, ...

If *output* is 0, no output is produced; otherwise, the erased files are also listed. If *output* is not specified, files are listed.

See `viewsource u_mi.mata` for the source code for this routine.

u_mi_sortback

`u_mi_sortback` *varlist*

`u_mi_sortback` removes dropped variables from *varlist* and sorts the data on the remaining variables. The routine is for dealing with sort-preserve problems when `program` *name*`,` `sortpreserve` is not adequate, such as when the data might be subjected to substantial editing between the preserving of the sort order and the restoring of it. To use `u_mi_sortback`, first record the order of the data:

```
local sortedby : sortedby
tempvar recnum
gen long ‘recnum’ = _n
quietly compress ‘recnum’
```

Later, when you want to restore the sort order, you code

```
u_mi_sortback ‘sortedby’ ‘recnum’
```

u_mi_save and u_mi_use

`u_mi_save` *macname* `:` *filename* [`,` *save_options*]

`u_mi_use` `‘"‘`*macname*`’"’` *filename* [`,` `clear` `nolabel`]

save_options are as described in [D] **save**. `clear` and `nolabel` are as described in [D] **use**. In both commands, *filename* must be specified in quotes if it contains any special characters or blanks.

It is sometimes necessary to save data in a temporary file and reload them later. In such cases, when the data are reloaded, you would like to have the original `c(filename)`, `c(filedate)`, and `c(changed)` restored. `u_mi_save` saves that information in *macname*. `u_mi_use` restores the information from the information saved in *macname*. Note the use of compound quotes around ‘*macname*’ in `u_mi_use`; they are not optional.

mata: u_mi_wide_swapvars()

`mata: u_mi_wide_swapvars(`*m*`,` *tmpvarname*`)`

where

m	#; $1 \leq \# \leq M$
tmpvarname	*string*; name from `tempvar`

This utility is for use with wide data only. For each variable name contained in `_dta[_mi_ivars]` and `_dta[_mi_pvars]`, `mata: u_mi_wide_swapvars()` swaps the contents of *varname* with *_m_varname*. Argument *tmpvarname* must be the name of a temporary variable obtained from command `tempvar`, and the variable must not exist. `mata: u_mi_wide_swapvars()` will use this variable while swapping. See [P] **macro** for more information on `tempvar`.

This function is its own inverse, assuming `_dta[_mi_ivars]` and `_dta[_mi_pvars]` have not changed.

See `viewsource u_mi.mata` for the source code for this routine.

u_mi_fixchars

`u_mi_fixchars` [, `acceptable` `proper`]

`u_mi_fixchars` makes the data and variable characteristics the same in $m = 1, m = 2, \ldots, m = M$ as they are in $m = 0$. The options specify what is already known to be true about the data, that the data are known to be acceptable or known to be proper. If neither is specified, you are stating that you do not know whether the data are even acceptable. That is okay. `u_mi_fixchars` handles performing whatever certification is required. Specifying the options makes `u_mi_fixchars` run faster.

This stabilizing of the characteristics is not about `mi`'s characteristics; that is handled by `u_mi_certify_data`. Other commands of Stata set and use characteristics, while `u_mi_fixchars` ensures that those characteristics are the same across all m.

mata: u_mi_cpchars_get() and mata: u_mi_cpchars_put()

`mata: u_mi_cpchars_get(`*matavar*`)`

`mata: u_mi_cpchars_put(`*matavar*`, {0|1|2})`

where *matavar* is a Mata transmorphic variable. Obtain *matavar* from `u_mi_get_mata_instanced_var()` when using these functions from Stata.

These routines replace the characteristics in one dataset with those of another. They are used to implement `u_mi_fixchars`.

`mata: u_mi_cpchars_get(`*matavar*`)` stores in *matavar* the characteristics of the data in memory. The data in memory remain unchanged.

`mata: u_mi_cpchars_put(`*matavar*`, #)` replaces the characteristics of the data in memory with those previously recorded in *matavar*. The second argument specifies the treatment of `_dta[_mi_*]` characteristics:

0	delete them in the destination data
1	copy them from the source just like any other characteristic
2	retain them as-is from the destination data.

mata: u_mi_get_mata_instanced_var()

`mata: u_mi_get_mata_instanced_var("`*macname*`", "`*basename*`" [ , `*i_value*` ])`

where

macname	name of local macro
basename	suggested name for instanced variable
i_value	initial value for instanced variable

`mata: u_mi_get_mata_instanced_var()` creates a new Mata global variable, initializes it with *i_value* or as a 0×0 real, and places its name in local macro *macname*. Typical usage is

```
local var
capture noisily {
        mata: u_mi_get_mata_instanced_var("var", "myvar")
        ...
        ... use `var' however you wish ...
        ...
}
nobreak {
       local rc = _rc
       capture mata: mata drop `var'
       if (`rc') {
              exit `rc'
       }
}
```

mata: u_mi_ptrace_*()

h = `u_mi_ptrace_open(`"*filename*"`, {"r"|"w"} [, {0|1}])`

`u_mi_ptrace_write_stripes(`*h*`, `*id*`, `*ynames*`, `*xnames*`)`

`u_mi_ptrace_write_iter(`*h*`, `*m*`, `*iter*`, `*B*`, `*V*`)`

`u_mi_ptrace_close(`*h*`)`

`u_mi_ptrace_safeclose(`*h*`)`

The above are Mata functions, where

h, if it is declared, should be declared transmorphic
id is a string scalar
ynames and *xnames* are string scalars
m and *iter* are real scalars
B and *V* are real matrices; *V* must be symmetric

These routines write parameter-trace files; see [MI] **mi ptrace**. The procedure is 1) open the file; 2) write the stripes; 3) repeatedly write iteration information; and 4) close the file.

1. Open the file: *filename* may be specified with or without a file suffix. Specify the second argument as `"w"`. The third argument should be `1` if the file may be replaced when it exists, and `0` otherwise.
2. Write the stripes: Specify *id* as the name of your routine or as `""`; `mi ptrace describe` will show this string as the creator of the file if the string is not `""`. *ynames* and *xnames* are both string scalars containing space-separated names or, possibly, *op*`.`*names*.
3. Repeatedly write iteration information: Written are m, the imputation number; *iter*, the iteration number; B, the matrix of coefficients; and V, the variance matrix. B must be $ny \times nx$ and V must be $ny \times ny$ and symmetric, where $nx =$ `length(tokens(`*xnames*`))` and $ny =$ `length(tokens(`*ynames*`))`.

4. Close the file: In Mata, use `u_mi_ptrace_close(`*h*`)`. It is highly recommended that, before step 1, *h* be obtained from inside Stata (not Mata) using `mata: u_mi_get_mata_instanced_var("h", "`*myvar*`")`. If you follow this advice, include a `mata: u_mi_ptrace_safeclose(‘h’)` in the ado-file cleanup code. This will ensure that open files are closed if the user presses *Break* or something else causes your routine to exit before the file is closed. A correctly written program will have two closes, one in Mata and another in the ado-file, although you could omit the one in Mata. See *mata: u_mi_get_mata_instanced_var()* directly above.

Also included in `u_mi_ptrace_*()` are routines to read parameter-trace files. You should not need these routines because users will use Stata command `mi ptrace use` to load the file you have written. If you are interested, however, then type `viewsource u_mi_ptrace.mata`.

How to write other set commands to work with mi

This section concerns the writing of other set commands such as [ST] **stset** or [XT] **xtset**—set commands having nothing to do with `mi`—so that they properly work with `mi`.

The definition of a set command is any command that creates characteristics in the data, and possibly creates variables in the data, that other commands in the suite will subsequently access. Making such set commands work with `mi` is mostly `mi`’s responsibility, but there is a little you need to do to assist `mi`. Before dealing with that, however, write and debug your set command ignoring `mi`. Once that is done, go back and add a few lines to your code. We will pretend your set command is named `mynewset` and your original code looks something like this:

```
program mynewset
    ...
    syntax ... [, ... ]
    ...
end
```

Our goal is to make it so that `mynewset` will not run on `mi` data while simultaneously making it so that `mi` can call it (the user types `mi mynewset`). When the user types `mi mynewset`, `mi` will 1) give `mynewset` a clean, $m = 0$ dataset on which it can run and 2) duplicate whatever `mynewset` does to $m = 0$ on $m = 1$, $m = 2$, …, $m = M$.

To achieve this, modify your code to look like this:

```
program mynewset
    ...
    syntax ... [, ... MI]                                          (1)
    if ("‘mi’"=="") {                                              (2)
            u_mi_not_mi_set "mynewset"
            local checkvars "*"                                    (3)
    }
    else {
            local checkvars "u_mi_check_setvars settime"           (3)
    }
    ...
    ‘checkvars’ ‘varlist’                                          (4)
    ...
end
```

That is,

1. Add the `mi` option to any options you already have.
2. If the `mi` option is not specified, execute `u_mi_not_mi_set`, passing to it the name of your set command. If the data are not `mi`, then `u_mi_not_mi_set` will do nothing. If the data are `mi`, then `u_mi_not_mi_set` will issue an error telling the user to run `mi mynewset`.
3. Set new local macro `checkvars` to `*` if the `mi` option is not specified, and otherwise to `u_mi_check_setvars`. We should mention that the `mi` option will be specified when `mi mynewset` calls `mynewset`.
4. Run `‘checkvars’` on any input variables `mynewset` uses that must not vary across m. `mi` does not care about other variables or even about new variables `mynewset` might create; it cares only about existing variables that should not vary across m.

   Let's understand what "`‘checkvars’` *varlist*" does. If the `mi` option was not specified, the line expands to "`*` *varlist*", which is a comment, and does nothing. If the `mi` option was specified, the line expands to "`u_mi_check_setvars settime` *varlist*". We are calling `mi` routine `u_mi_check_setvars`, telling it that we are calling at set time, and passing along *varlist*. `u_mi_check_setvars` will verify that *varlist* does not contain `mi` system variables or variables that vary across m. Within `mynewset`, you may call `‘checkvars’` repeatedly if that is convenient.

You have completed the changes to `mynewset`. You finally need to write one short program that reads

```
program mi_cmd_mynewset
        version 19.5      // (or version 19 if you do not have StataNow)
        mi_cmd_genericset ‘"mynewset ‘0’"’ "_mynewset_x _mynewset_y"
end
```

In the above, we assume that `mynewset` might add one or two variables to the data named `_mynewset_x` and `_mynewset_y`. List in the second argument all variables `mynewset` might create. If `mynewset` never creates new variables, then the program should read

```
program mi_cmd_mynewset
        version 19.5      // (or version 19 if you do not have StataNow)
        mi_cmd_genericset ‘"mynewset ‘0’"’
end
```

You are done.

Also see

[MI] **Intro** — Introduction to mi

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on citing Stata documentation.