

## Postestimation commands

The following standard postestimation command is available after `margins`:

Command	Description
<code>marginsplot</code>	graph the results from margins—profile plots, interaction plots, etc.

For information on `marginsplot`, see [R] [marginsplot](#).

The following standard postestimation commands are available after `margins`, `post`:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of parameters
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of parameters
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of parameters
<code>pwcompare</code>	pairwise comparisons of parameters
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

## Remarks and examples

Continuing with the example from *Example 8: Margins of interactions* in [R] [margins](#), we use the dataset and refit the logistic model of outcome:

```
. use https://www.stata-press.com/data/r19/margex
(Artificial data for margins)
. logistic outcome sex##group age
(output omitted)
```

We then estimate the margins for males and females and post the margins as estimation results with a full VCE.

```
. margins sex, post
Predictive margins                                Number of obs = 3,000
Model VCE: OIM
Expression: Pr(outcome), predict()
```

	Delta-method		z	P> z	[95% conf. interval]	
	Margin	std. err.				
sex						
Male	.1600644	.0125653	12.74	0.000	.1354368	.184692
Female	.1966902	.0100043	19.66	0.000	.1770821	.2162983

We can now use `nlcom` (see [R] [nlcom](#)) to estimate a risk ratio of females to males using the average probabilities for females and males posted by margins:

```
. nlcom (risk_ratio: _b[1.sex] / _b[0.sex])
      risk_ratio: _b[1.sex] / _b[0.sex]
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
risk_ratio	1.228819	.1149538	10.69	0.000	1.003514	1.454124

We could similarly estimate the average risk difference between females and males:

```
. nlcom (risk_diff: _b[1.sex] - _b[0.sex])
      risk_diff: _b[1.sex] - _b[0.sex]
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
risk_diff	.0366258	.0160632	2.28	0.023	.0051425	.068109

## Also see

[R] [margins](#) — Marginal means, predictive margins, and marginal effects

[R] [marginsplot](#) — Graph results from margins (profile plots, etc.)

[U] [20 Estimation and postestimation commands](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).