serrbar — Graph standard error bar char	t

Description	Quick start	Menu	Syntax
Options	Remarks and examples	Acknowledgment	Also see

## Description

serrbar is typically used with a dataset containing means, standard deviations or standard errors, and an *xvar*. serrbar uses these data to create a standard error bar chart. The means are plotted against *xvar*, and error bars around the means have a width determined by the standard deviation or standard error. While it is most common to use serrbar with this type of data, serrbar may also be used to create a scatterplot with error bars for other types of data.

## **Quick start**

Plot of y versus x with error bars representing  $y \pm s$ serrbar y s x

Same as above, but with error bars for y  $\pm\,2\times\,s$ 

```
serrbar y s x, scale(2)
```

## Menu

 $Statistics > Other > Quality \ control > Standard \ error \ bar \ chart$ 

## Syntax

serrbar <i>mvar svar xvar</i> $\lfloor if \rfloor \lfloor in \rfloor \lfloor$ , <i>options</i> $\rfloor$				
options	Description			
Main <u>sc</u> ale(#)	scale length of graph bars; default is scale(1)			
Error bars rcap_options	affect rendition of capped spikes			
Plotted points <pre>mvopts(scatter_options)</pre>	affect rendition of plotted points			
Add plots addplot( <i>plot</i> )	add other plots to generated graph			
Y axis, X axis, Titles, Legend, Overall twoway_options	any options other than by () documented in [G-3] <i>twoway_options</i>			

# Options

Main

scale(#) controls the length of the bars. The upper and lower limits of the bars will be *mvar*+scale() × *svar* and *mvar*-scale() × *svar*. The default is scale(1).

Error bars

*rcap\_options* affect the rendition of the plotted error bars (the capped spikes). See [G-2] **graph twoway rcap**.

∫ Plotted points ]

mvopts (*scatter\_options*) affects the rendition of the plotted points (*mvar* versus *xvar*). See [G-2] graph twoway scatter.

Add plots

addplot (*plot*) provides a way to add other plots to the generated graph; see [G-3] *addplot\_option*.

Y axis, X axis, Titles, Legend, Overall

*twoway\_options* are any of the options documented in [G-3] *twoway\_options*, excluding by(). These include options for titling the graph (see [G-3] *title\_options*) and for saving the graph to disk (see [G-3] *saving\_option*).

## **Remarks and examples**

#### Example 1

In quality-control applications, the three most commonly used variables with this command are the process mean, process standard deviation, and time. For instance, we have data on the average weights and standard deviations from an assembly line in San Francisco for the period January 8 to January 16. Our data are

. use https://www.stata-press.com/data/r19/assembly

. list, sep(0) divider

	date	mean	std
1.	108	192.22	3.94
2.	109	192.64	2.83
з.	110	192.37	4.58
4.	113	194.76	3.25
5.	114	192.69	2.89
6.	115	195.02	1.73
7.	116	193.40	2.62

We type serrbar mean std date, scale(2) but, after seeing the result, decide to make it fancier:

. serrbar mean std date, scale(2) title("Observed weight variation")
> sub("San Francisco plant, 1/8 to 1/16") yline(195) yaxis(1 2)

> ylab(195, axis(2)) ytitle("", axis(2))



## Acknowledgment

serrbar was written by Nicholas J. Cox of the Department of Geography at Durham University, UK, who is coeditor of the *Stata Journal* and author of *Speaking Stata Graphics*.

## Also see

[R] QC — Quality control charts

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on citing Stata documentation.