าร
ſ

Description	Quick start	Syntax	Options
Remarks and examples	References	Also see	

# Description

simulate eases the programming task of performing Monte Carlo-type simulations. Typing

. simulate exp\_list, reps(#): command

runs *command* for # replications and collects the results in *exp\_list*.

*command* defines the command that performs one simulation. Most Stata commands and user-written programs can be used with simulate, as long as they follow standard Stata syntax; see [U] 11 Language syntax. The by prefix may not be part of *command*.

 $exp\_list$  specifies the expression to be calculated from the execution of *command*. If no expressions are given,  $exp\_list$  assumes a default, depending upon whether *command* changes results in e() or r(). If *command* changes results in e(), the default is \_b. If *command* changes results in r() (but not e()), the default is all the scalars posted to r(). It is an error not to specify an expression in  $exp\_list$  otherwise.

# **Quick start**

Simple program for use with simulate

Define program myreg to generate data and fit a linear regression

```
program myreg, eclass
  drop _all
  set obs 25
  generate x = rnormal()
  generate y = 3*x + 1 + rnormal()
  regress y x
end
```

### Perform simulation

Record coefficients and SEs from 1,000 simulated replications of program myreg simulate \_b\_se, reps(1000): myreg

Same as above, and set random-number seed to 5,762 for reproducible results
 simulate \_b \_se, reps(1000) seed(5762): myreg

# Syntax

options	Description
nodots	suppress replication dots
dots(#)	display dots every # replications
<u>noi</u> sily	display any output from <i>command</i>
<u>tr</u> ace	trace command
<pre>saving(filename,)</pre>	save results to <i>filename</i>
<u>nol</u> egend	suppress table legend
verbose	display the full table legend
seed(#)	set random-number seed to #

simulate [exp\_list], reps(#) [options] : command

All weight types supported by command are allowed; see [U] 11.1.6 weight.

<i>exp_list</i> contains	(name: elist)
	elist
	eexp
elist contains	newvar = (exp)
	(exp)
<i>eexp</i> is	specname
	[eqno]specname
specname is	_b
	_b[]
	_se
	_se[]
eqno is	<b>#</b> #
	name

exp is a standard Stata expression; see [U] 13 Functions and expressions.

Distinguish between [], which are to be typed, and [], which indicate optional arguments.

# Options

reps(#) is required—it specifies the number of replications to be performed.

nodots and dots (#) specify whether to display replication dots. By default, one dot character is displayed for each successful replication. An "x" is displayed if *command* returns an error or if any value in *exp\_list* is missing. You can also control whether dots are displayed using set dots; see [R] set.

nodots suppresses display of the replication dots.

dots(#) displays dots every # replications. dots(0) is a synonym for nodots.

noisily requests that any output from command be displayed. This option implies the nodots option.

trace causes a trace of the execution of *command* to be displayed. This option implies the noisily option.

- saving (filename, suboptions) creates a Stata data file (.dta file) consisting of (for each statistic in *exp\_list*) a variable containing the replicates.
  - double specifies that the results for each replication be saved as doubles, meaning 8-byte reals. By default, they are saved as floats, meaning 4-byte reals.
  - every (#) specifies that results be written to disk every #th replication. every() should be specified only in conjunction with saving() when command takes a long time for each replication. This will allow recovery of partial results should some other software crash your computer. See [P] postfile.
  - replace specifies that *filename* be overwritten if it exists.
- nolegend suppresses display of the table legend. The table legend identifies the rows of the table with the expressions they represent.
- verbose requests that the full table legend be displayed. By default, coefficients and standard errors are not displayed.
- seed (#) sets the random-number seed. Specifying this option is equivalent to typing the following command before calling simulate:

. set seed #

## **Remarks and examples**

For an introduction to Monte Carlo methods, see Cameron and Trivedi (2022, chap. 5). White (2010) provides a command for analyzing results of simulation studies.

### Example 1: Simulating basic summary statistics

We have a dataset containing means and variances of 100-observation samples from a lognormal distribution (as a first step in evaluating, say, the coverage of a 95%, t-based confidence interval). Then we perform the experiment 1,000 times.

The following command definition will generate 100 independent observations from a lognormal distribution and compute the summary statistics for this sample.

```
program lnsim, rclass
                          // (or version 19 if you do not have StataNow)
        version 19.5
        drop all
        set obs 100
        generate z = exp(rnormal())
        summarize z
        return scalar mean = r(mean)
       return scalar Var = r(Var)
end
```

We can save 1,000 simulated means and variances from lnsim by typing

```
. set seed 1234
. simulate mean=r(mean) var=r(Var), reps(1000) nodots: lnsim
     Command: lnsim
        mean: r(mean)
         var: r(Var)
```

4

. describe $*$							
Variable name	Storage type	Displa forma	y Valu t labe	ie el Va	riable label		
mean var	float float	%9.0g %9.0g		r( r(	mean) Var)		
. summarize							
Variable		Obs	Mean	Std. de	v. Min	Max	
mean	1,	000 1	.630648	.217306	2 1.106372	2.612052	
var	1,	000	4.60798	4.50216	6.966087	70.5597	

## Technical note

Before executing our lnsim simulator, we can verify that it works by executing it interactively.

```
. set seed 1234
. lnsim
Number of observations (_N) was 0, now 100.
    Variable
                      Obs
                                  Mean
                                          Std. dev.
                                                           Min
                                                                      Max
           z
                      100
                              1.534256
                                          1.584568
                                                      .0400387
                                                                 9.818309
. return list
scalars:
                r(Var) = 2.510857086217961
               r(mean) = 1.53425569280982
```

#### Example 2: Simulating a regression model

regress y x

end

Consider a more complicated problem. Let's experiment with fitting  $y_j = a + bx_j + u_j$  when the true model has a = 1, b = 2,  $u_j = z_j + cx_j$ , and when  $z_j$  is N(0, 1). We will save the parameter estimates and standard errors and experiment with varying c.  $x_j$  will be fixed across experiments but will originally be generated as N(0, 1). We begin by interactively making the true data:

```
. drop _all
. set obs 100
Number of observations (_N) was 0, now 100.
. set seed 54321
. generate x = rnormal()
. generate true_y = 1+2*x
. save truth
file truth.dta saved
Our program is
program hetero1
version 19.5 // (or version 19 if you do not have StataNow)
args c
use truth, clear
```

generate y = true\_y + (rnormal() + 'c'\*x)

Note the use of 'c' in our statement for generating y. c is a local macro generated from args c and thus refers to the first argument supplied to hetero1. If we want c = 3 for our experiment, we type

```
. simulate _b _se, reps(10000): hetero1 3
 (output omitted)
```

Our program heterol could, however, be more efficient because it rereads the file truth once every replication. It would be better if we could read the data just once. In fact, if we read in the data right before running simulate, we really should not have to reread for each subsequent replication. A faster version reads

```
program hetero2
    version 19.5 // (or version 19 if you do not have StataNow)
    args c
    capture drop y
    generate y = true_y + (rnormal() + 'c'*x)
    regress y x
end
```

Requiring that the current dataset has the variables true\_y and x may become inconvenient. Another improvement would be to require that the user supply variable names, such as in

```
program hetero3
    version 19.5    // (or version 19 if you do not have StataNow)
    args truey x c
    capture drop y
    generate y = 'truey' + (rnormal() + 'c'*'x')
    regress y x
end
```

#### Thus, we can type

```
. simulate _b _se, reps(10000): hetero3 true_y x 3
(output omitted)
```

```
4
```

## Example 3: Simulating a ratio of statistics

Now, let's consider the problem of simulating the ratio of two medians. Suppose that each sample of size  $n_i$  comes from a normal population with a mean  $\mu_i$  and standard deviation  $\sigma_i$ , where i = 1, 2. We write the program below and save it as a text file called myratio.ado (see [U] 17 Ado-files). Our program is an rclass command that requires six arguments as input, identified by the local macros n1, mu1, sigma1, n2, mu2, and sigma2, which correspond to  $n_1, \mu_1, \sigma_1, n_2, \mu_2$ , and  $\sigma_2$ , respectively. With these arguments, myratio will generate the data for the two samples, use summarize to compute the two medians and store the ratio of the medians in r(ratio).

```
program myratio, rclass
    version 19.5    // (or version 19 if you do not have StataNow)
    args n1 mu1 sigma1 n2 mu2 sigma2
    // generate the data
    drop _all
    local N = 'n1'+'n2'
    set obs 'N'
    tempvar y
    generate 'y' = rnormal()
    replace 'y' = cond(_n<='n1', 'mu1'+'y'*'sigma1', 'mu2'+'y'*'sigma2')
    // calculate the medians
    tempname m1
```

```
summarize 'y' if _n<='n1', detail
scalar 'm1' = r(p50)
summarize 'y' if _n>'n1', detail
// store the results
return scalar ratio = 'm1' / r(p50)
end
```

The result of running our simulation is

```
. set seed 19192
. simulate ratio=r(ratio), reps(1000) nodots: myratio 5 3 1 10 3 2
     Command: myratio 5 3 1 10 3 2
       ratio: r(ratio)
. summarize
                                         Std. dev.
   Variable
                      Obs
                                 Mean
                                                          Min
                                                                      Max
                    1.000
                              1.10875
                                          .5219166
                                                     .3606606
                                                                9.857285
      ratio
```

## Technical note

Stata lets us do simulations of simulations and simulations of bootstraps. Stata's bootstrap command (see [R] **bootstrap**) works much like simulate, except that it feeds the user-written program a bootstrap sample. Say that we want to evaluate the bootstrap estimator of the standard error of the median when applied to lognormally distributed data. We want to perform a simulation, resulting in a dataset of medians and bootstrap estimated standard errors.

As background, summarize (see [R] summarize) calculates summary statistics, leaving the mean in r(mean) and the standard deviation in r(sd). summarize with the detail option also calculates summary statistics, but more of them, and leaves the median in r(p50).

Thus, our plan is to perform simulations by randomly drawing a dataset: we calculate the median of our random sample, we use bootstrap to obtain a dataset of medians calculated from bootstrap samples of our random sample, the standard deviation of those medians is our estimate of the standard error, and the summary statistics are stored in the results of summarize.

Our simulator is

```
program define bsse, rclass
    version 19.5 // (or version 19 if you do not have StataNow)
    drop _all
    set obs 100
    generate x = rnormal()
    tempfile bsfile
    bootstrap midp=r(p50), rep(100) saving('bsfile'): summarize x, detail
    use 'bsfile', clear
    summarize midp
    return scalar mean = r(mean)
    return scalar sd = r(sd)
end
```

4

We can obtain final results, running our simulation 1,000 times, by typing

```
. set seed 48901
. simulate med=r(mean) bs se=r(sd), reps(1000): bsse
  Command: bsse
   med: r(mean)
   bs se: r(sd)
Simulations (1,000): ......10.......20.......30.......40........50.....
> .....60........70.......80.......90.......100.......110.......120..
> ......130.......140.......150......160......170.......180......
> .710......720......730......740.....750......760......770..
> ......910.......920.......930.......940.......950.......960......
. summarize
                      Min
 Variable
        Obs
             Mean
                Std. dev.
                           Max
        1,000
           -.0013359
   med
                .1221602
                    -.3795549
                         .3656219
        1,000
           .1278773
                .0303109
                    .0614031
                         .2484805
  bs se
```

This is a case where the simulation dots (drawn by default, unless the nodots option is specified) will give us an idea of how long this simulation will take to finish as it runs.

#### 

# References

Cameron, A. C., and P. K. Trivedi. 2022. *Microeconometrics Using Stata*. 2nd ed. College Station, TX: Stata Press.
Hilbe, J. M. 2010. Creating synthetic discrete-response regression models. *Stata Journal* 10: 104–124.
Taylor, M. A. 2018. Simulating the central limit theorem. *Stata Journal* 18: 345–356.
White, I. R. 2010. simsum: Analyses of simulation studies including Monte Carlo error. *Stata Journal* 10: 369–385.

## Also see

- [R] bootstrap Bootstrap sampling and estimation
- [R] jackknife Jackknife estimation
- [R] **permute** Permutation tests
- [R] set rngstream Specify the stream for the stream random-number generator

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on citing Stata documentation.