

Postestimation commands

The following postestimation commands are available after zinz:

| Command | Description |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <code>contrast</code> | contrasts and ANOVA-style joint tests of parameters |
| <code>estat ic</code> | Akaike's, consistent Akaike's, corrected Akaike's, and Schwarz's Bayesian information criteria (AIC, CAIC, AICc, and BIC, respectively) |
| <code>estat summarize</code> | summary statistics for the estimation sample |
| <code>estat vce</code> | variance–covariance matrix of the estimators (VCE) |
| <code>estat (svy)</code> | postestimation statistics for survey data |
| <code>estimates</code> | cataloging estimation results |
| <code>etable</code> | table of estimation results |
| * <code>forecast</code> | dynamic forecasts and simulations |
| * <code>hausman</code> | Hausman's specification test |
| <code>lincom</code> | point estimates, standard errors, testing, and inference for linear combinations of parameters |
| * <code>lrtest</code> | likelihood-ratio test |
| <code>margins</code> | marginal means, predictive margins, marginal effects, and average marginal effects |
| <code>marginsplot</code> | graph the results from margins (profile plots, interaction plots, etc.) |
| <code>nlcom</code> | point estimates, standard errors, testing, and inference for nonlinear combinations of parameters |
| <code>predict</code> | number of events, incidence rates, probabilities, etc. |
| <code>predictnl</code> | point estimates, standard errors, testing, and inference for generalized predictions |
| <code>pwcompare</code> | pairwise comparisons of parameters |
| <code>suest</code> | seemingly unrelated estimation |
| <code>test</code> | Wald tests of simple and composite linear hypotheses |
| <code>testnl</code> | Wald tests of nonlinear hypotheses |

* `forecast`, `hausman`, and `lrtest` are not appropriate with `svy` estimation results.

predict

Description for predict

predict creates a new variable containing predictions such as numbers of events, incidence rates, probabilities, linear predictions, and standard errors.

Menu for predict

Statistics > Postestimation

Syntax for predict

```
predict [type] newvar [if] [in] [ , statistic nooffset ]
```

```
predict [type] stub* [if] [in] , scores
```

| statistic | Description |
|-----------|-----------------------------------------|
| Main | |
| n | number of events; the default |
| ir | incidence rate |
| pr | probability of a degenerate zero |
| pr(n) | probability $\Pr(y_j = n)$ |
| pr(a,b) | probability $\Pr(a \leq y_j \leq b)$ |
| xb | linear prediction |
| stdp | standard error of the linear prediction |

These statistics are available both in and out of sample; type predict ... if e(sample) ... if wanted only for the estimation sample.

Options for predict

Main

n, the default, calculates the predicted number of events, which is $(1 - F_j) \exp(\mathbf{x}_j\boldsymbol{\beta})$ if neither offset() nor exposure() was specified when the model was fit, where F_j is the predicted probability of a zero outcome; $(1 - F_j) \exp(\mathbf{x}_j\boldsymbol{\beta} + \text{offset}_j^\beta)$ if offset() was specified; or $(1 - F_j) \{ \exp(\mathbf{x}_j\boldsymbol{\beta}) \times \text{exposure}_j \}$ if exposure() was specified.

ir calculates the incidence rate, which is the predicted number of events when exposure is 1. This is equivalent to specifying both the n and the nooffset options.

pr calculates the probability of a degenerate zero, predicted from the fitted degenerate distribution $F_j = F(\mathbf{z}_j\boldsymbol{\gamma})$. If offset() was specified within the inflate() option, then $F_j = F(\mathbf{z}_j\boldsymbol{\gamma} + \text{offset}_j^\gamma)$ is calculated.

pr(n) calculates the probability $\Pr(y_j = n)$, where n is a nonnegative integer that may be specified as a number or a variable. Note that pr is not equivalent to pr(0).

`pr(a, b)` calculates the probability $\Pr(a \leq y_j \leq b)$, where a and b are nonnegative integers that may be specified as numbers or variables;

b missing ($b \geq .$) means $+\infty$;

`pr(20, .)` calculates $\Pr(y_j \geq 20)$;

`pr(20, b)` calculates $\Pr(y_j \geq 20)$ in observations for which $b \geq .$ and calculates

$\Pr(20 \leq y_j \leq b)$ elsewhere.

`pr(., b)` produces a syntax error. A missing value in an observation of the variable a causes a missing value in that observation for `pr(a, b)`.

`xb` calculates the linear prediction, which is $\mathbf{x}_j\beta$ if neither `offset()` nor `exposure()` was specified;

$\mathbf{x}_j\beta + \text{offset}_j^\beta$ if `offset()` was specified; or $\mathbf{x}_j\beta + \ln(\text{exposure}_j)$ if `exposure()` was specified; see `nooffset` below.

`stdp` calculates the standard error of the linear prediction.

`nooffset` is relevant only if you specified `offset()` or `exposure()` when you fit the model. It modifies the calculations made by `predict` so that they ignore the offset or exposure variable; the linear prediction is treated as $\mathbf{x}_j\beta$ rather than as $\mathbf{x}_j\beta + \text{offset}_j^\beta$ or $\mathbf{x}_j\beta + \ln(\text{exposure}_j)$. Specifying `predict ..., nooffset` is equivalent to specifying `predict ..., ir`.

`scores` calculates equation-level score variables.

The first new variable will contain $\partial \ln L / \partial (\mathbf{x}_j\beta)$.

The second new variable will contain $\partial \ln L / \partial (\mathbf{z}_j\gamma)$.

The third new variable will contain $\partial \ln L / \partial \ln \alpha$.

margins

Description for margins

`margins` estimates margins of response for number of events, incidence rates, probabilities, and linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [ , options ]
margins [marginlist] , predict(statistic ...) [predict(statistic ...) ...] [options]
```

| <i>statistic</i> | Description |
|------------------------------------|---------------------------------------|
| <code>n</code> | number of events; the default |
| <code>ir</code> | incidence rate |
| <code>pr</code> | probability of a degenerate zero |
| <code>pr(<i>n</i>)</code> | probability $\Pr(y_j = n)$ |
| <code>pr(<i>a</i>,<i>b</i>)</code> | probability $\Pr(a \leq y_j \leq b)$ |
| <code>xb</code> | linear prediction |
| <code>stdp</code> | not allowed with <code>margins</code> |

Statistics not allowed with `margins` are functions of stochastic quantities other than $e(b)$.

For the full syntax, see [R] [margins](#).

Methods and formulas

See [Methods and formulas](#) in [R] [zinb](#) for the model definition and notation.

The probabilities calculated using the `pr(n)` option are the probability $\Pr(y_j = n)$. These are calculated using

$$\begin{aligned}\Pr(y_j = 0 | \mathbf{x}_j, \mathbf{z}_j) &= F_j + (1 - F_j) p_2(0 | \mathbf{x}_j) \\ \Pr(y_j = n | \mathbf{x}_j, \mathbf{z}_j) &= (1 - F_j) p_2(n | \mathbf{x}_j) \quad \text{for } n = 1, 2, \dots\end{aligned}$$

where F_j is the probability of obtaining an observation from the degenerate distribution whose mass is concentrated at zero, and $p_2(n | \mathbf{x}_j)$ is the probability of $y_j = n$ from the nondegenerate, negative binomial distribution. F_j can be obtained by using the `pr` option.

See [Cameron and Trivedi \(2013, sec. 4.6\)](#) for further details.

References

- Cameron, A. C., and P. K. Trivedi. 2013. *Regression Analysis of Count Data*. 2nd ed. New York: Cambridge University Press.
- Manjón, M., and O. Martínez. 2014. The chi-squared goodness-of-fit test for count-data models. *Stata Journal* 14: 798–816.

Also see

- [R] [zinb](#) — Zero-inflated negative binomial regression
- [U] [20 Estimation and postestimation commands](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

