

Postestimation commands

The following postestimation commands are available after `zip`:

Command	Description
<code>contrast</code>	contrasts and ANOVA-style joint tests of parameters
<code>estat ic</code>	Akaike's, consistent Akaike's, corrected Akaike's, and Schwarz's Bayesian information criteria (AIC, CAIC, AICc, and BIC, respectively)
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estat (svy)</code>	postestimation statistics for survey data
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
* <code>forecast</code>	dynamic forecasts and simulations
* <code>hausman</code>	Hausman's specification test
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of parameters
* <code>lrtest</code>	likelihood-ratio test
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of parameters
<code>predict</code>	number of events, incidence rates, probabilities, etc.
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
<code>pwcompare</code>	pairwise comparisons of parameters
<code>suest</code>	seemingly unrelated estimation
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

*`forecast`, `hausman`, and `lrtest` are not appropriate with `svy` estimation results.

predict

Description for predict

predict creates a new variable containing predictions such as numbers of events, incidence rates, probabilities, linear predictions, and standard errors.

Menu for predict

Statistics > Postestimation

Syntax for predict

```
predict [type] newvar [if] [in] [ , statistic nooffset ]
```

```
predict [type] stub* [if] [in] , scores
```

statistic	Description
Main	
n	number of events; the default
ir	incidence rate
pr	probability of a degenerate zero
pr(<i>n</i>)	probability $\Pr(y_j = n)$
pr(<i>a</i> , <i>b</i>)	probability $\Pr(a \leq y_j \leq b)$
xb	linear prediction
stdp	standard error of the linear prediction

These statistics are available both in and out of sample; type predict ... if e(sample) ... if wanted only for the estimation sample.

Options for predict

Main

n, the default, calculates the predicted number of events, which is $(1 - F_j) \exp(\mathbf{x}_j\beta)$ if neither `offset()` nor `exposure()` was specified when the model was fit, where F_j is the predicted probability of a zero outcome; $(1 - F_j) \exp(\mathbf{x}_j\beta + \text{offset}_j^\beta)$ if `offset()` was specified; or $(1 - F_j) \{ \exp(\mathbf{x}_j\beta) \times \text{exposure}_j \}$ if `exposure()` was specified.

ir calculates the incidence rate, which is the predicted number of events when exposure is 1. This is equivalent to specifying both the **n** and the **nooffset** options.

pr calculates the probability of a degenerate zero, predicted from the fitted degenerate distribution $F_j = F(\mathbf{z}_j\gamma)$. If `offset()` was specified within the `inflate()` option, then $F_j = F(\mathbf{z}_j\gamma + \text{offset}_j^\gamma)$ is calculated.

pr(*n*) calculates the probability $\Pr(y_j = n)$, where *n* is a nonnegative integer that may be specified as a number or a variable. Note that **pr** is not equivalent to **pr(0)**.

pr(*a*, *b*) calculates the probability $\Pr(a \leq y_j \leq b)$, where *a* and *b* are nonnegative integers that may be specified as numbers or variables;

b missing (*b* ≥ .) means $+\infty$;

pr(20, .) calculates $\Pr(y_j \geq 20)$;

pr(20, *b*) calculates $\Pr(y_j \geq 20)$ in observations for which *b* ≥ . and calculates

$\Pr(20 \leq y_j \leq b)$ elsewhere.

pr(., *b*) produces a syntax error. A missing value in an observation of the variable *a* causes a missing value in that observation for **pr(*a*, *b*)**.

xb calculates the linear prediction, which is $\mathbf{x}_j\beta$ if neither `offset()` nor `exposure()` was specified; $\mathbf{x}_j\beta + \text{offset}_j^\beta$ if `offset()` was specified; or $\mathbf{x}_j\beta + \ln(\text{exposure}_j)$ if `exposure()` was specified; see **nooffset** below.

stdp calculates the standard error of the linear prediction.

nooffset is relevant only if you specified `offset()` or `exposure()` when you fit the model. It modifies the calculations made by **predict** so that they ignore the offset or exposure variable; the linear prediction is treated as $\mathbf{x}_j\beta$ rather than as $\mathbf{x}_j\beta + \text{offset}_j^\beta$ or $\mathbf{x}_j\beta + \ln(\text{exposure}_j)$. Specifying **predict** ..., **nooffset** is equivalent to specifying **predict** ..., **ir**.

scores calculates equation-level score variables.

The first new variable will contain $\partial \ln L / \partial (\mathbf{x}_j\beta)$.

The second new variable will contain $\partial \ln L / \partial (\mathbf{z}_j\gamma)$.

margins

Description for margins

margins estimates margins of response for the numbers of events, incidence rates, probabilities, and linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [ , options ]
margins [marginlist] , predict (statistic ...) [predict (statistic ...) ...] [options]
```

statistic	Description
n	number of events; the default
ir	incidence rate
pr	probability of a degenerate zero
pr(n)	probability $\Pr(y_j = n)$
pr(a,b)	probability $\Pr(a \leq y_j \leq b)$
xb	linear prediction
stdp	not allowed with margins

Statistics not allowed with margins are functions of stochastic quantities other than e(b).

For the full syntax, see [R] margins.

Remarks and examples

► Example 1: Obtaining predicted counts

Continuing with [example 1](#) from [\[R\] zip](#), we will use `predict` to compute the predicted number of fish captured by each individual.

```
. use https://www.stata-press.com/data/r19/fish
(Fictional fishing data)
. zip count persons livebait, inflate(child camper)
(output omitted)
. predict numfish
(option n assumed; predicted number of events)
. summarize numfish
```

Variable	Obs	Mean	Std. dev.	Min	Max
numfish	250	2.770999	3.269588	.079269	13.55015

The average predicted number of fish caught by all visitors, regardless of whether or not they fished, is 2.77 fish.



► Example 2: Obtaining predicted probabilities

`predict` with the `pr` option computes the probability that an individual does not fish.

```
. predict pr, pr
```

On the other hand, `predict` with the `pr(n)` option computes the probability of catching *n* fish; particularly, the probability of catching zero fish will be

```
. predict pr0, pr(0)
. list pr pr0 in 1
```

	pr	pr0
1.	.3793549	.8609267

Notice that `pr0` is always equal to or greater than `pr`. For example, for the first individual, the probability of not fishing is 0.38; on the other hand, the probability of catching zero fish (0.86) is equal to the sum of the probability of not fishing and the probability of fishing but not catching any fish. `pr0` can be also computed as one minus the probability of catching at least one fish, that is:

```
. predict pr_catch, pr(1,.)
. gen pr0b = 1-pr_catch
```



Methods and formulas

See [Methods and formulas](#) in [\[R\] zip](#) for the model definition and notation.

The probabilities calculated using the `pr(n)` option are the probability $\Pr(y_j = n)$. These are calculated using

$$\begin{aligned}\Pr(y_j = 0 | \mathbf{x}_j, \mathbf{z}_j) &= F_j + (1 - F_j) \exp(-\lambda_j) \\ \Pr(y_j = n | \mathbf{x}_j, \mathbf{z}_j) &= (1 - F_j) \frac{\lambda_j^n \exp(-\lambda_j)}{n!} \quad \text{for } n = 1, 2, \dots\end{aligned}$$

where F_j is the probability of obtaining an observation from the degenerate distribution whose mass is concentrated at zero. F_j can be obtained by using the `pr` option.

See [Cameron and Trivedi \(2013, sec. 4.6\)](#) for further details.

References

- Cameron, A. C., and P. K. Trivedi. 2013. *Regression Analysis of Count Data*. 2nd ed. New York: Cambridge University Press.
- Manjón, M., and O. Martínez. 2014. The chi-squared goodness-of-fit test for count-data models. *Stata Journal* 14: 798–816.

Also see

[\[R\] zip](#) — Zero-inflated Poisson regression

[\[U\] 20 Estimation and postestimation commands](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

