

## Description

To demonstrate linear mediation models, we use the following data:

```
. use https://www.stata-press.com/data/r19/gsem_multimed
(Fictional job-performance data)
. summarize
```

Variable	Obs	Mean	Std. dev.	Min	Max
branch	1,500	38	21.65593	1	75
support	1,500	.0084667	.5058316	-1.6	1.8
satis	1,500	.0212	.6087235	-1.6	2
perform	1,500	5.005317	.8949845	2.35022	8.084294

```
. notes
_dta:
1. Fictional data on job performance, job satisfaction, and perceived
   support from managers for 1,500 sales employees of a large department
   store in 75 locations.
2. Variable support is average of Likert-scale questions, each question
   scored from -2 to 2.
3. Variable satis is average of Likert-scale questions, each question scored
   from -2 to 2.
4. Variable perform is job performance measured on continuous scale.
```

See [Structural models 1: Linear regression](#) and [Multilevel mixed-effects models](#) in [SEM] [Intro 5](#) for background.

## Remarks and examples


Remarks are presented under the following headings:

- [One-level model with sem](#)
- [One-level model with gsem](#)
- [Two-level model with gsem](#)
- [Fitting the models with the Builder](#)

### One-level model with sem

You can fit single-level mediation models with `sem` or `gsem`. You will be better off using `sem` because then you can use `estat teffects` afterward to compute indirect and total effects.

The model we wish to fit is the simplest form of a mediation model, namely,



We are interested in the effect of managerial support on job performance, but we suspect a portion of the effect might be mediated through job satisfaction. In traditional mediation analysis, the model would be fit by a series of linear regression models as described in [Baron and Kenny \(1986\)](#). That approach is sufficient because the errors are not correlated. The advantage of using structural equation modeling is that you can fit a single model and estimate the indirect and total effects, and you can embed the simple mediation model in a larger model and even use latent variables to measure any piece of the mediation model.

To fit this model with the command syntax, we type

```

. sem (perform <- satis support) (satis <- support)
Endogenous variables
  Observed: perform satis
Exogenous variables
  Observed: support
Fitting target model:
Iteration 0:  Log likelihood = -3779.9224
Iteration 1:  Log likelihood = -3779.9224
Structural equation model
Estimation method: ml
Log likelihood = -3779.9224
Number of obs = 1,500
  
```

	OIM					
	Coefficient	std. err.	z	P> z	[95% conf. interval]	
Structural						
perform						
satis	.8984401	.0251903	35.67	0.000	.849068	.9478123
support	.6161077	.0303143	20.32	0.000	.5566927	.6755227
_cons	4.981054	.0150589	330.77	0.000	4.951539	5.010569
satis						
support	.2288945	.0305047	7.50	0.000	.1691064	.2886826
_cons	.019262	.0154273	1.25	0.212	-.0109749	.0494989
var(e.perf~m)	.3397087	.0124044			.3162461	.364912
var(e.satis)	.3569007	.0130322			.3322507	.3833795

LR test of model vs. saturated: chi2(0) = 0.00

Prob > chi2 = .

Notes:

1. The direct effect of managerial support on job performance is measured by `perform <- support` and is estimated to be 0.6161. The effect is small albeit highly statistically significant. The standard deviations of performance and support are 0.89 and 0.51. A one standard deviation increase in support improves performance by a third of a standard deviation.
2. The direct effect of job satisfaction on job performance is measured by `perform <- satis` and is estimated to be 0.8984. That is a moderate effect, practically speaking, and is highly statistically significant.
3. The effect of managerial support on job satisfaction is measured by `satis <- support` and is practically small but statistically significant.
4. What is the total effect of managerial support on performance? It is the direct effect (0.6161) plus the indirect effect of support on satisfaction on performance ( $0.2289 \times 0.8984 = 0.2056$ ), meaning the total effect is 0.8217. It would be desirable to put a standard error on that, but that's more work.

We can use `estat teffects` after estimation to obtain the total effect and its standard error:

```
. estat teffects
```

Direct effects

	OIM				[95% conf. interval]	
	Coefficient	std. err.	z	P> z		
Structural						
perform						
satis	.8984401	.0251903	35.67	0.000	.849068	.9478123
support	.6161077	.0303143	20.32	0.000	.5566927	.6755227
satis						
support	.2288945	.0305047	7.50	0.000	.1691064	.2886826

Indirect effects

	OIM				[95% conf. interval]	
	Coefficient	std. err.	z	P> z		
Structural						
perform						
satis	0 (no path)					
support	.205648	.0280066	7.34	0.000	.150756	.26054
satis						
support	0 (no path)					

Total effects

	OIM				[95% conf. interval]	
	Coefficient	std. err.	z	P> z		
Structural						
perform						
satis	.8984401	.0251903	35.67	0.000	.849068	.9478123
support	.8217557	.0404579	20.31	0.000	.7424597	.9010516
satis						
support	.2288945	.0305047	7.50	0.000	.1691064	.2886826

## One-level model with gsem

We can fit the same model with `gsem`. The command is the same except that we substitute `gsem` for `sem`, and results are identical:

```
. gsem (perform <- satis support) (satis <- support)
Iteration 0:  Log likelihood = -2674.3421
Iteration 1:  Log likelihood = -2674.3421   (backed up)
Generalized structural equation model                      Number of obs = 1,500
Response: perform
Family:   Gaussian
Link:     Identity
Response: satis
Family:   Gaussian
Link:     Identity
Log likelihood = -2674.3421
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
perform						
satis	.8984401	.0251903	35.67	0.000	.849068	.9478123
support	.6161077	.0303143	20.32	0.000	.5566927	.6755227
_cons	4.981054	.0150589	330.77	0.000	4.951539	5.010569
satis						
support	.2288945	.0305047	7.50	0.000	.1691064	.2886826
_cons	.019262	.0154273	1.25	0.212	-.0109749	.0494989
var(e.perf~m)	.3397087	.0124044			.3162461	.364912
var(e.satis)	.3569007	.0130322			.3322507	.3833795

After `gsem`, however, we cannot use `estat teffects`:

```
. estat teffects
      estat teffects not valid
      r(321);
```

We can, however, calculate the indirect and total effects for ourselves and obtain the standard error by using `nlcom`. Referring back to [note 4](#) of the previous section, the formula for the indirect effect and total effects are

$$\text{indirect effect} = \beta_1\beta_4$$

$$\text{total effect} = \beta_2 + \beta_1\beta_4$$

where

$\beta_1$  = path coefficient for `perform <- satis`

$\beta_4$  = path coefficient for `satis <- support`

$\beta_2$  = path coefficient for `perform <- support`

It turns out that we can access the coefficients by typing

$$\beta_1 = \_b[\text{perform:satis}]$$

$$\beta_4 = \_b[\text{satis:support}]$$

$$\beta_2 = \_b[\text{perform:support}]$$

which is most easily revealed by typing

```
. gsem, coeflegend
(output omitted)
```

Thus we can obtain the indirect effect by typing

```
. nlcom _b[perform:satis]*_b[satis:support]
      _nl_1:  _b[perform:satis]*_b[satis:support]
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
_nl_1	.205648	.0280066	7.34	0.000	.150756	.26054


and we can obtain the total effect by typing

```
. nlcom _b[perform:support]+_b[perform:satis]*_b[satis:support]
      _nl_1:  _b[perform:support]+_b[perform:satis]*_b[satis:support]
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
_nl_1	.8217557	.0404579	20.31	0.000	.7424597	.9010516

## Two-level model with gsem

It may be easier to use `sem` rather than `gsem` for fitting single-level models, but if you want to fit multilevel models, you must use `gsem`. A variation on the model we just fit is



In this model, we include a random intercept in each equation at the branch (individual store) level. The model above is one of many variations on two-level mediation models; see [Krull and MacKinnon \(2001\)](#) for an introduction to multilevel mediation models, and see [Preacher, Zyphur, and Zhang \(2010\)](#) for a discussion of fitting these models with structural equation modeling.

To fit this model with the command syntax, we type

```
. gsem (perform <- satis support M1[branch]) (satis <- support M2[branch]),
> cov(M1[branch]*M2[branch]@0)

Fitting fixed-effects model:
Iteration 0: Log likelihood = -2674.3421
Iteration 1: Log likelihood = -2674.3421
Refining starting values:
Grid node 0: Log likelihood = -2132.1613
Fitting full model:
Iteration 0: Log likelihood = -2132.1613 (not concave)
Iteration 1: Log likelihood = -1801.3155
Iteration 2: Log likelihood = -1769.6421
Iteration 3: Log likelihood = -1705.1282
Iteration 4: Log likelihood = -1703.746
Iteration 5: Log likelihood = -1703.7141
Iteration 6: Log likelihood = -1703.714
Generalized structural equation model                                Number of obs = 1,500
Response: perform
Family: Gaussian
Link: Identity
Response: satis
Family: Gaussian
Link: Identity
Log likelihood = -1703.714
( 1) [perform]M1[branch] = 1
( 2) [satis]M2[branch] = 1
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
perform						
satis	.604264	.0336398	17.96	0.000	.5383313	.6701968
support	.6981525	.0250432	27.88	0.000	.6490687	.7472364
M1[branch]	1 (constrained)					
_cons	4.986596	.0489465	101.88	0.000	4.890663	5.082529
satis						
support	.2692633	.0179649	14.99	0.000	.2340528	.3044739
M2[branch]	1 (constrained)					
_cons	.0189202	.0570868	0.33	0.740	-.0929678	.1308083
var(						
M1[branch])	.1695962	.0302866			.119511	.2406713
var(						
M2[branch])	.2384738	.0399154			.1717781	.3310652
var(e.perf~m)	.201053	.0075451			.1867957	.2163985
var(e.satis)	.1188436	.0044523			.1104299	.1278983

Notes:

1. In *One-level model with sem* above, we measured the direct effects on job performance of job satisfaction and managerial support as 0.8984 and 0.6161. Now the direct effects are 0.6043 and 0.6982.
2. We can calculate the indirect and total effects just as we did in the previous section, which we will do below. We mentioned earlier that there are other variations of two-level mediation models, and how you calculate total effects depends on the model chosen.

In this case, the indirect effect is

```
. nlcom _b[perform:satis]*_b[satis:support]
      _nl_1: _b[perform:satis]*_b[satis:support]
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
_nl_1	.1627062	.0141382	11.51	0.000	.1349958	.1904165

and the total effect is

```
. nlcom _b[perform:support]+_b[perform:satis]*_b[satis:support]
      _nl_1: _b[perform:support]+_b[perform:satis]*_b[satis:support]
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
_nl_1	.8608587	.0257501	33.43	0.000	.8103894	.911328

## Fitting the models with the Builder

Use the diagram in *One-level model with sem* above for reference.

1. Open the dataset.

In the Command window, type

```
. use https://www.stata-press.com/data/r19/gsem_multmed
```


2. Open a new Builder diagram.

Select menu item **Statistics > SEM (structural equation modeling) > Model building and estimation**.


3. Create a regression component for the perform outcome.

Select the Add regression component tool, , and then click in the center of the diagram.



In the resulting dialog box,

- a. select perform in the *Dependent variable* control;
- b. select support with the *Independent variables* control;
- c. select Left in the *Independent variables' direction* control;
- d. click on **OK**.
- e. Use the Select tool, , to select only the perform rectangle, and drag it to the right to increase the distance between the rectangles. (You can hold the *Shift* key while dragging to ensure that the movement is directly to the right.)

4. Create the mediating variable.



- Select the Add observed variable tool, , and then click in the diagram above the path from support to perform.
- In the Contextual Toolbar, select `satis` with the *Variable* control.

5. Create the paths to and from the mediating variable.


- Select the Add path tool, .
- Click in the upper right of the support rectangle (it will highlight when you hover over it), and drag a path to the lower left of the `satis` rectangle (it will highlight when you can release to connect the path).
- Continuing with the  tool, draw a path from the lower right of the `satis` rectangle to the upper left of the perform rectangle.

6. Clean up the direction of the error term.


We want the error for each of the endogenous variables to be to the right of the rectangle. The error for `satis` may have been created in another direction. If so,

- choose the Select tool, ;
- click in the `satis` rectangle;
- click on one of the **Error rotation** buttons, , in the Contextual Toolbar until the error is to the right of the rectangle.

7. Clean up the location of the paths.



If you do not like where the paths have been connected to the rectangles, use the Select tool, , to click on the path, and then simply click on where it connects to a rectangle and drag the endpoint.

8. Estimate.



Click on the **Estimate** button, , in the Standard Toolbar, and then click on **OK** in the resulting *SEM estimation options* dialog box.



9. To fit the model in *Two-level model with gsem*, continue with the previous diagram, and put the builder in *gsem* mode by clicking on the  button.


10. Create the multilevel latent variable corresponding to the random intercept for `satis`.

- Select the Add multilevel latent variable tool, , and click above the rectangle for `satis`.
- In the Contextual Toolbar, click on the  button.
- Select the nesting level and nesting variable by selecting 2 from the *Nesting depth* control and selecting branch `> Observations` in the next control.
- Specify M1 as the *Base name*.
- Click on **OK**.

11. Create the multilevel latent variable corresponding to the random intercept for `perform`.

- Select the Add multilevel latent variable tool, , and click above the rectangle for `satis` and to the right of the `branch1` double oval.
- In the Contextual Toolbar, click on the  button.

- c. Select the nesting level and nesting variable by selecting 2 from the *Nesting depth* control and selecting branch > *Observations* in the next control.
  - d. Specify M2 as the *Base name*.
  - e. Click on **OK**.
12. Draw paths from the multilevel latent variables to their corresponding endogenous variables.
    - a. Select the Add path tool, .
    - b. Click in the bottom of the branch<sub>1</sub> double oval, and drag a path to the top of the *satis* rectangle.
    - c. Continuing with the  tool, click in the bottom of the branch<sub>2</sub> double oval, and drag a path to the top of the *perform* rectangle.
  13. Estimate again.

Click on the **Estimate** button, , in the Standard Toolbar, and then click on **OK** in the resulting *GSEM estimation options* dialog box.

You can open a completed diagram for the first model in the Builder by typing

```
. webgetsem sem_med
```

You can open a completed diagram for the second model in the Builder by typing

```
. webgetsem gsem_mlmed
```

## References

- Baron, R. M., and D. A. Kenny. 1986. The moderator–mediator variable distinction in social psychological research: Conceptual, strategic, and statistical considerations. *Journal of Personality and Social Psychology* 51: 1173–1182. <https://doi.org/10.1037//0022-3514.51.6.1173>.
- Krull, J. L., and D. P. MacKinnon. 2001. Multilevel modeling of individual and group level mediated effects. *Multivariate Behavioral Research* 36: 249–277. [https://doi.org/10.1207/S15327906MBR3602\\_06](https://doi.org/10.1207/S15327906MBR3602_06).
- Preacher, K. J., M. J. Zyphur, and Z. Zhang. 2010. A general multilevel SEM framework for assessing multilevel mediation. *Psychological Methods* 15: 209–233. <https://doi.org/10.1037/a0020141>.

## Also see

- [SEM] **Example 38g** — Random-intercept and random-slope models (multilevel)
- [SEM] **Intro 5** — Tour of models
- [SEM] **gsem** — Generalized structural equation model estimation command
- [CAUSAL] **mediate** — Causal mediation analysis

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

