

Description

Tobit regression is demonstrated using `auto.dta`:

```
. use https://www.stata-press.com/data/r19/auto  
(1978 automobile data)  
. generate wgt = weight/1000
```

See *Structural models 1: Linear regression* in [SEM] **Intro 5** for background.

Remarks and examples

Remarks are presented under the following headings:

Fitting tobit regression models


Fitting the model with the Builder

Fitting tobit regression models

The first example in [R] **tobit** is

```
. tobit mpg wgt, ll(17)
```

This model corresponds to



Censoring information does not appear in the path diagram by default. It can be added to the path diagram by customizing the appearance of `mpg` in the Builder. The Builder reports the censoring information for `mpg` in the Details pane.

To fit this model with `gsem`, we type

```
. gsem mpg <- wgt, family(gaussian, lcensored(17))
Refining starting values:
Grid node 0:  Log likelihood = -170.32555
Fitting full model:
Iteration 0:  Log likelihood = -170.32555
Iteration 1:  Log likelihood = -164.66209
Iteration 2:  Log likelihood = -164.25471
Iteration 3:  Log likelihood = -164.25438
Iteration 4:  Log likelihood = -164.25438

Generalized structural equation model
Response:      mpg                               Number of obs      = 74
Lower limit: 17                               Uncensored      = 56
Family:       Gaussian                         Left-censored   = 18
Link:         Identity                        Right-censored  = 0
Log likelihood = -164.25438
```

	Coefficient	Std. err.	z	P> z	[95% conf. interval]	
mpg						
wgt	-6.87305	.700257	-9.82	0.000	-8.245529	-5.500572
_cons	41.49856	2.058384	20.16	0.000	37.4642	45.53291
var(e.mpg)	14.78942	2.817609			10.18085	21.48414

Notes:

1. The reported coefficients and standard errors (SEs) match those reported by `tobit`.
2. `gsem` reports the point estimate of `e.mpg` as 14.78942. This is an estimate of σ^2 , the error variance. `tobit` reports an estimated σ as 3.845701. And $\sqrt{14.78942} = 3.8457$.

Fitting the model with the Builder

Use the diagram in *Fitting tobit regression models* above for reference.



1. Open the dataset and create the rescaled weight variable.

In the Command window, type


```
. use https://www.stata-press.com/data/r19/auto
. generate wgt = weight/1000
```

2. Open a new Builder diagram.


Select menu item **Statistics > SEM (structural equation modeling) > Model building and estimation**.

3. Put the Builder in `gsem` mode by clicking on the  button.
4. Create the independent variable.
 - a. Select the Add observed variable tool, .
 - b. Click in the diagram about one-fourth of the way in from the left and half of the way up from the bottom.
 - c. In the Contextual Toolbar, use the *Variable* control to select the variable `wgt`.


5. Create the tobit response.

- a. Select the Add generalized response variable tool, .
- b. Click about one-third of the way in from the right side of the diagram, to the right of the `wgt` rectangle.
- c. In the Contextual Toolbar, select Gaussian, Identity in the *Family/Link* control (it may already be selected).
- d. In the Contextual Toolbar, use the *Variable* control to select the variable `mpg`.
- e. In the Contextual Toolbar, click on the **Properties...** button.
- f. In the resulting *Variable properties* dialog box, click on the **Censoring...** button in the **Variable** tab.
- g. In the resulting *Censoring* dialog box, select the *Left-censored* radio button. In the resulting *Left censoring* box below, select the *Constant* radio button (it may already be selected), and type 17 in the *Constant* control.
- h. Click on **OK** in the *Censoring* dialog box, and then click on **OK** in the *Variable properties* dialog box. The Details pane will now show the censoring information for `mpg`.

6. Create a path from the independent variable to the dependent variable.

- a. Select the Add path tool, .
- b. Click in the right side of the `wgt` rectangle (it will highlight when you hover over it), and drag a path to the left side of the `mpg` rectangle (it will highlight when you can release to connect the path).

7. Estimate.

Click on the **Estimate** button, , in the Standard Toolbar, and then click on **OK** in the resulting *GSEM estimation options* dialog box.

You can open a completed diagram in the Builder by typing

```
. webgetsem gsem_tobit
```

Also see

[SEM] **Example 38g** — Random-intercept and random-slope models (multilevel)

[SEM] **Example 44g** — Interval regression

[SEM] **Example 45g** — Heckman selection model

[SEM] **Example 46g** — Endogenous treatment-effects model

[SEM] **Intro 5** — Tour of models

[SEM] **gsem** — Generalized structural equation model estimation command

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).