

Description

`spmatrix fromdata` creates custom spatial weighting matrices from Sp data.

There are two other ways to create custom weighting matrices: `spmatrix userdefined` and `spmatrix spfrommata`. Those ways may require less work, but they require knowledge of Mata.

Quick start

Create spectral-normalized spatial weighting matrix W_{new} from the $N \times N$ “matrix” stored in variables x_1, x_2, \dots, x_n

```
spmatrix fromdata Wnew = x1 - xn
```

Menu

Statistics > Spatial autoregressive models

Syntax

```
spmatrix fromdata spmatname = varlist [ , options ]
```

spmatname is the name of the spatial weighting matrix to be created.

<i>options</i>	Description
<code>idistance</code>	store reciprocal of elements
<code>normalize(<i>normalize</i>)</code>	type of normalization; default is <code>normalized(spectral)</code>
<code>replace</code>	replace existing weighting matrix

Options

`idistance` converts distance to inverse distance by storing the reciprocal of the elements.

`normalize(normalize)` specifies how the resulting matrix is to be scaled. `normalize(spectral)` is the default. `normalize(minmax)`, `normalize(row)`, and `normalize(none)` are also allowed. See [SP] [spmatrix create](#) for full details of the option and [Choosing weighting matrices and their normalization](#) in [SP] [spregress](#) for details about normalization.

`replace` specifies that matrix *spmatname* be overwritten if it already exists.

Remarks and examples

The `fromdata` in `spmatrix fromdata` means that the matrix itself is stored as variables in the data. Some researchers are used to working this way, and if you are among them, `spmatrix fromdata` is for you.

If the matrix is stored with the variables because you created it using the data, you may want to consider using `spmatrix userdefined` and `spmatrix spfrommata` instead. Both require knowledge of Mata, so that is a disadvantage if you do not already know Mata. On the other hand, `spmatrix userdefined` does not require much knowledge and handles the creation of most custom weighting matrices simply and elegantly. `spmatrix spfrommata` requires more extensive knowledge of Mata, but it will handle problems that no other method can.

The problem with `spmatrix fromdata` is not that the matrix is stored in the data but that filling in the matrix is more work than it needs to be. Stata draws a distinction between rows and columns. Rows are observations and columns are variables. Stata is perfectly willing to sweep down observations, but few Stata commands will sweep across variables. Mata, being a matrix language, draws no such distinction.

Also see

[SP] [spmatrix](#) — Categorical guide to the `spmatrix` command

[SP] [spmatrix spfrommata](#) — Copy Mata matrix to Sp

[SP] [spmatrix userdefined](#) — Create custom weighting matrix

[SP] [Intro](#) — Introduction to spatial data and SAR models

Mata Reference Manual

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

