

spshape2dta — Translate shapefile to Stata format

[Description](#)
[Options](#)

[Quick start](#)
[Remarks and examples](#)

[Menu](#)
[Also see](#)

[Syntax](#)

Description

`spshape2dta` *name* reads files *name.shp* and *name.dbf* and creates Sp dataset *name.dta* and translated shapefile *name_shp.dta*. The translated shapefile will be linked to the Sp dataset *name.dta*.

Quick start

Create *myfile.dta* and *myfile_shp.dta* from *myfile.shp* and *myfile.dbf*

```
spshape2dta myfile
```

Create *newfile.dta* and *newfile_shp.dta* from *oldfile.shp* and *oldfile.dbf*

```
spshape2dta oldfile, saving(newfile)
```

Menu

Statistics > Spatial autoregressive models

Syntax

```
spshape2dta name [ , options ]
```

<i>options</i>	Description
<code>clear</code>	clear existing data from memory
<code>replace</code>	if <i>name.dta</i> or <i>name_shp.dta</i> exists, replace them
<code>saving(<i>name2</i>)</code>	create new files named <i>name2.dta</i> and <i>name2_shp.dta</i> instead of <i>name.dta</i> and <i>name_shp.dta</i>

`spshape2dta` translates files *name.shp* and *name.dbf*. They must be in the current directory.

`spshape2dta` creates files *name.dta* and *name_shp.dta*. They will be created in the current directory. The data in memory, if any, remain unchanged.

Options

`clear` specifies to clear any data in memory.

`replace` specifies that if the new files being created already exist on disk, they can be replaced.

`saving(name2)` specifies that rather than the new files being named `name.dta` and `name_shp.dta`, they be named `name2.dta` and `name2_shp.dta`.

Remarks and examples

[stata.com](https://www.stata.com)

`spshape2dta` is the first step in preparing data to be used with shapefiles. See [\[SP\] Intro 4](#) for step-by-step instructions.

`spshape2dta` creates two files:

```
name.dta
name_shp.dta
```

`name.dta` is an ordinary Stata dataset. The dataset will have N observations, one for each spatial unit. The dataset will be `spset`.

```
. use name
. spset
   Sp dataset: name.dta
Linked shapefile: name_shp.dta
   Data: Cross sectional
Spatial-unit ID: _ID
Coordinates: _CY, _CX (latitude-and-longitude, miles)
```

`name.dta` will contain the variables

`_ID` values 1, 2, ..., N . This variable links observations in the data to observations in the Stata-format shapefile, `name_shp.dta`.
`_CX`, `_CY` contain the centroids for the places (spatial units)

`name.dta` will include the other variables defined in `name.dbf`. Usually, there will be five or ten. What they contain varies but can usually be determined from their names and by looking at their values.

`name.dta` will be linked to `name_shp.dta`, which is called the Stata-format shapefile. It contains the map. It too is an ordinary Stata dataset, but you ignore it. `Sp` will use `name_shp.dta` behind the scenes when you construct contiguity spatial weighting matrices using `spmatrix create contiguity` or when you graph choropleth maps using `grmap`.

Also see

[\[SP\] Intro 3](#) — Preparing data for analysis

[\[SP\] Intro 4](#) — Preparing data: Data with shapefiles

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).