

cttost — Convert count-time data to survival-time data

[Description](#)
[Options](#)[Quick start](#)
[Remarks and examples](#)[Menu](#)
[Also see](#)[Syntax](#)

Description

`cttost` converts count-time data to their survival-time format so that they can be analyzed with Stata. Do not confuse count-time data with counting-process data, which can also be analyzed with the `st` commands; see [\[ST\] ctset](#) for a definition and examples of count data.

Quick start

Convert count-time data to survival-time data using `ctset` data

```
cttost
```

As above, but name the new weight variable `mywvar` instead of using the default name

```
cttost, wvar(mywvar)
```

Menu

Statistics > Survival analysis > Setup and utilities > Convert count-time data to survival-time data

Syntax

```
cttost [ , options ]
```

<i>options</i>	Description
<code>t0(<i>t0var</i>)</code>	name of entry-time variable
<code>wvar(<i>wvar</i>)</code>	name of frequency-weighted variable
<code>clear</code>	overwrite current data in memory
<code><u>n</u>opreserve</code>	do not save the original data; programmer's command

You must `ctset` your data before using `cttost`; see [ST] [ctset](#).

`nopreserve` does not appear in the dialog box.

Options

`t0(t0var)` specifies the name of the new variable to create that records entry time. (For most ct data, no entry-time variable is necessary because everyone enters at time 0.)

Even if an entry-time variable is necessary, you need not specify this option. `cttost` will, by default, choose `t0`, `time0`, or `etime` according to which name does not already exist in the data.

`wvar(wvar)` specifies the name of the new variable to be created that records the frequency weights for the new pseudo-observations. Count-time data are actually converted to frequency-weighted st data, and a variable is needed to record the weights. This sounds more complicated than it is. Understand that `cttost` needs a new variable name, which will become a permanent part of the st data.

If you do not specify `wvar()`, `cttost` will, by default, choose `w`, `pop`, `weight`, or `wgt` according to which name does not already exist in the data.

`clear` specifies that it is okay to proceed with the conversion, even though the current dataset has not been saved on disk.

The following option is available with `cttost` but is not shown in the dialog box:

`nopreserve` speeds the conversion by not saving the original data that can be restored should things go wrong or should you press *Break*. `nopreserve` is intended for use by programmers who use `cttost` as a subroutine. Programmers can specify this option if they have already preserved the original data. `nopreserve` does not affect the conversion.

Remarks and examples

[stata.com](http://www.stata.com)

Converting ct to st data is easy. We have some count-time data,

```
. use http://www.stata-press.com/data/r15/cttost
. ct
   dataset name:  http://www.stata-press.com/data/r15/cttost.dta
             time:  time
             no. fail:  ndead
             no. lost:  ncens
             no. enter:  --                (meaning all enter at time 0)
             by:  agecat treat
```

```
. list in 1/5
```

	agecat	treat	time	ndead	ncens
1.	2	1	464	4	0
2.	3	0	268	3	1
3.	2	0	638	2	0
4.	1	0	803	1	4
5.	1	0	431	2	0

and to convert it, we type cttost:

```
. cttost
      failure event:  ndead != 0 & ndead < .
obs. time interval:  (0, time]
exit on or before:  failure
                    weight:  [fweight=w]
```

```
      33 total observations
       0 exclusions
```

```
      33 physical observations remaining, equal to
      82 weighted observations, representing
      39 failures in single-record/single-failure data
48,726 total analysis time at risk and under observation
                                     at risk from t =          0
                                     earliest observed entry t =      0
                                     last observed exit t =      1,227
```

Now that it is converted, we can use any of the st commands:

```
. sts test treat, logrank
      failure _d:  ndead
analysis time _t:  time
      weight:  [fweight=w]
```

Log-rank test for equality of survivor functions

treat	Events observed	Events expected
0	22	17.05
1	17	21.95
Total	39	39.00
	chi2(1) =	2.73
	Pr>chi2 =	0.0986

Also see

[ST] [ct](#) — Count-time data

[ST] [ctset](#) — Declare data to be count-time data