snapspan — Convert snapshot data to time-span data

DescriptionQuick startMenuSyntaxOptionsRemarks and examplesAlso see

Description

snapspan converts snapshot data for a given subject to time-span data required for use with survival analysis commands, such as stcox, streg, and stset. snapspan replaces the data in the specified variables. Transformed variables may be "events" that occur at the instant of the snapshot or retrospective variables that are to apply to the time span ending at the time of the current snapshot.

Quick start

Create a time-span dataset from data containing subject identifier id, event variable evar occurring at the time in tvar, and other variables measured at that time

snapspan id tvar evar

Same as above, and create new variable time0 containing the entry time for each record snapspan id tvar evar, generate(time0)

Menu

Statistics > Survival analysis > Setup and utilities > Convert snapshot data to time-span data

Syntax

snapspan idvar timevar varlist [, generate(newt0var) replace]

idvar records the subject ID and may be string or numeric.

- timevar records the time of the snapshot; it must be numeric and may be recorded on any scale: date, hour, minute, second, etc.
- *varlist* are the "event" variables, meaning that they occur at the instant of *timevar*. *varlist* can also include retrospective variables that are to apply to the time span ending at the time of the current snapshot. The other variables are assumed to be measured at the time of the snapshot and thus apply from the time of the snapshot forward. See *Specifying varlist* below.

snapspan does not allow alias variables; see [D] frunalias for advice on how to get around this restriction.

Options

- generate(*newt0var*) adds *newt0var* to the dataset containing the entry time for each converted timespan record.
- replace specifies that it is okay to change the data in memory, even though the dataset has not been saved on disk in its current form.

Remarks and examples

Remarks are presented under the following headings:

Snapshot and time-span datasets Specifying varlist

Snapshot and time-span datasets

snapspan converts a snapshot dataset to a time-span dataset. A snapshot dataset records a subject *id*, a *time*, and then other variables measured at the *time*:

Snapshot datasets:

idvar	timevar	x1	x2			
47	12	5	27			
47	42	5	18			
47	55	5	19			
idvar	datevar	x1	x2			
122	14jul1998	5	27			
122	12aug1998	5	18			
122	08sep1998	5	19			
idvar	year	x1	x2			
122	1994	5	27			
122	1995	5	5 18			
122	1997	5	19			

A time-span dataset records a span of time (*time0*, *time1*]:

Time-span data are required, for instance, by stset and the st system. The variables assumed to occur at time1 are the failure or event variables. All the other variables are assumed to be constant over the span.

idvar	time0	time1	x1	x2	 event
47	0	12	5	13	 0
47	12	42	5	27	 0
47	42	55	5	18	 1
idvar	time0	time1	x1	x2	 event
122	01jan1998	14jul1998	5	13	 0
122	14jul1998	12aug1998	5	27	 0
122	12aug1998	08sep1998	5	18	 1
idvar	time0	time1	x1	x2	 event
122	1993	1994	5	13	 0
122	1994	1995	5	27	 0
122	1995	1997	5	18	 1

Time-span datasets:

To convert snapshot data to time-span data, you need to distinguish between event and nonevent variables. Event variables happen at an instant.

Say that you have a snapshot dataset containing variable e recording an event (e = 1 might record surgery, death, becoming unemployed, etc.) and the rest of the variables—call them x1, x2, etc.—recording characteristics (such as sex, birth date, blood pressure, or weekly wage). The same data, in snapshot and time-span form, would be

In	n snapshot form:			In time-span form:						
id	time	x1	x2	е	id	time0	time	x1	x2	e
1	5	a1	b1	e1	1	-	5			e1
1	7	a2	b2	e2	1	5	7	a1	b1	e2
1	9	a3	b3	e3	1	7	9	a2	b2	e3
1	11	a4	b4	e4	1	9	11	a3	b3	e4

snapspan converts data from the form on the left to the form on the right:

. snapspan id time e, generate(time0) replace

The form on the right is suitable for use by stcox and stset and the other survival analysis commands.

Specifying varlist

The varlist-the third variable on-specifies the "event" variables.

In fact, the *varlist* specifies the variables that apply to the time span ending at the time of the current snapshot. The other variables are assumed to be measured at the time of the snapshot and thus apply from the time of the snapshot forward.

Thus varlist should include retrospective variables.

For instance, say that the snapshot recorded bp, blood pressure; smokes, whether the patient smoked in the last 2 weeks; and event, a variable recording examination, surgery, etc. Then *varlist* should include smokes and event. The remaining variables, bp and the rest, would be assumed to apply from the time of the snapshot forward.

Suppose that the snapshot recorded ecs, employment change status (hired, fired, promoted, etc.); wage, the current hourly wage; and ms, current marital status. Then *varlist* should include esc and ms (assuming snapshot records are not generated for reason of ms change). The remaining variables, wage and the rest, would be assumed to apply from the time of the snapshot forward.

Also see

- [ST] stset Declare data to be survival-time data
- [D] frunalias Change storage type of alias variables

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on citing Stata documentation.