estat - Postestimation statistics for survey data

Description Options References

Quick start Remarks and examples Also see Menu Stored results Syntax Methods and formulas

Description

estat svyset reports the survey design characteristics associated with the current estimation results.

estat effects displays a table of design and misspecification effects for each estimated parameter.

estat lceffects displays a table of design and misspecification effects for a user-specified linear combination of the parameter estimates.

estat size displays a table of sample and subpopulation sizes for each estimated subpopulation mean, proportion, ratio, or total. This command is available only after svy: mean, svy: proportion, svy: ratio, and svy: total; see [R] mean, [R] proportion, [R] ratio, and [R] total.

estat sd reports subpopulation standard deviations based on the estimation results from mean and svy: mean; see [R] mean. estat sd is not appropriate with estimation results that used direct standard-ization or poststratification.

estat strata displays a table of the number of singleton and certainty strata within each sampling stage. The variance scaling factors are also displayed for estimation results where singleunit(scaled) was svyset.

estat cv reports the coefficient of variation (CV) for each coefficient in the current estimation results. The CV for coefficient b is

$$CV(b) = \frac{SE(b)}{|b|} \times 100\%$$

estat gof reports a goodness-of-fit test for binary response models using survey data. This command is available only after svy: logistic, svy: logit, and svy: probit; see [R] logistic, [R] logit, and [R] probit.

estat vce displays the covariance or correlation matrix of the parameter estimates of the previous model. See [R] estat vce for examples.

Quick start

Design effects for each parameter in current estimation results after a command using the svy: prefix estat effects

Design effects for the sum of parameter estimates for variables v1 and v2

estat lceffects v1 + v2

Same as above, but add misspecification effects

estat lceffects v1 + v2, deff deft meff meft

Number of observations used and subpopulation size for each parameter

estat size

Estimate of subpopulation standard deviation based on estimation results from svy: mean estat sd

- Compute standard deviation using an estimate of SRS variance for sampling within a subpopulation estat sd, srssubpop
- Display the number of singleton and certainty strata within each sampling stage estat strata
- Coefficient of variation for each parameter in current estimation results estat cv
- Goodness-of-fit test for binary response models using survey data and grouping data into quintiles estat gof, group(5)
- Variance-covariance matrix of parameter estimates from the most recent model estat vce
- Same as above, but display a correlation matrix estat vce, correlation

Menu

Statistics > Survey data analysis > DEFF, MEFF, and other statistics

Syntax

Survey design characteristics

estat svyset

```
Design and misspecification effects for point estimates
```

estat effects [, estat_effects_options]

Design and misspecification effects for linear combinations of point estimates

estat lceffects exp [, estat_lceffects_options]

Subpopulation sizes

estat size [, estat_size_options]

Subpopulation standard-deviation estimates

```
estat sd [, estat_sd_options]
```

Singleton and certainty strata

estat strata

Coefficient of variation for survey data

```
estat cv [, estat_cv_options]
```

Goodness-of-fit test for binary response models using survey data

estat gof [if] [in] [, estat_gof_options]

Display covariance matrix estimates

```
estat vce [, estat_vce_options]
```

estat_effects_options	Description			
deff	report DEFF design effects			
deft	report DEFT design effects			
srssubpop report design effects, assuming SRS within subpopulation				
meff	report MEFF design effects			
meft	report MEFT design effects			
display_options	control spacing and display of omitted variables and base and empty cells			

stat_lceffects_options Description				
deff	report DEFF design effects			
deft	report DEFT design effects			
<u>srs</u> subpop	report design effects, assuming SRS within subpopulation			
meff	report MEFF design effects			
meft	report MEFT design effects			
estat_size_options	Description			
obs	report number of observations (within subpopulation)			
size	report subpopulation sizes			
estat_sd_options	Description			
variance	report subpopulation variances instead of standard deviations			
<u>srs</u> subpop	report standard deviation, assuming SRS within subpopulation			
estat_cv_options	Description			
nolegend	suppress the table legend			
display_options	control spacing and display of omitted variables and base and empty cells			
estat_gof_options	Description			
group(#)	compute test statistic using # quantiles			
total	compute test statistic using the total estimator instead of the mean estimator			
all	execute test for all observations in the data			
estat_vce_options	Description			
<u>cov</u> ariance	display as covariance matrix; the default			
<u>c</u> orrelation	display as correlation matrix			
$\underline{eq}uation(spec)$	display only specified equations			
<u>b</u> lock	display submatrices by equation			
diag	display submatrices by equation; diagonal blocks only			
<pre>format(%fmt)</pre>	display format for covariances and correlations			
<u>nolin</u> es	suppress lines between equations			
display_options	control display of omitted variables and base and empty cells			

collect is allowed with all estat commands; see [U] 11.1.10 Prefix commands.

Options

Options are presented under the following headings:

Options for estat effects Options for estat lceffects Options for estat size Options for estat sd Options for estat cv Options for estat gof Options for estat vce

Options for estat effects

deff and deft request that the design-effect measures DEFF and DEFT be displayed. This is the default, unless direct standardization or poststratification was used.

The deff and deft options are not allowed with estimation results that used direct standardization or poststratification. These methods obscure the measure of design effect because they adjust the frequency distribution of the target population.

srssubpop requests that DEFF and DEFT be computed using an estimate of simple random sampling (SRS) variance for sampling within a subpopulation. By default, DEFF and DEFT are computed using an estimate of the SRS variance for sampling from the entire population. Typically, srssubpop is used when computing subpopulation estimates by strata or by groups of strata.

meff and meft request that the misspecification-effect measures MEFF and MEFT be displayed.

display_options: noomitted, vsquish, noemptycells, baselevels, allbaselevels; see [R] Estimation options.

Options for estat Iceffects

deff and deft request that the design-effect measures DEFF and DEFT be displayed. This is the default, unless direct standardization or poststratification was used.

The deff and deft options are not allowed with estimation results that used direct standardization or poststratification. These methods obscure the measure of design effect because they adjust the frequency distribution of the target population.

srssubpop requests that DEFF and DEFT be computed using an estimate of simple random sampling (SRS) variance for sampling within a subpopulation. By default, DEFF and DEFT are computed using an estimate of the SRS variance for sampling from the entire population. Typically, srssubpop is used when computing subpopulation estimates by strata or by groups of strata.

meff and meft request that the misspecification-effect measures MEFF and MEFT be displayed.

Options for estat size

- obs requests that the number of observations used to compute the estimate be displayed for each row of estimates.
- size requests that the estimate of the subpopulation size be displayed for each row of estimates. The subpopulation size estimate equals the sum of the weights for those observations in the estimation sample that are also in the specified subpopulation. The estimated population size is reported when a subpopulation is not specified.

Options for estat sd

variance requests that the subpopulation variance be displayed instead of the standard deviation.

srssubpop requests that the standard deviation be computed using an estimate of SRS variance for sampling within a subpopulation. By default, the standard deviation is computed using an estimate of the SRS variance for sampling from the entire population. Typically, srssubpop is given when computing subpopulation estimates by strata or by groups of strata.

Options for estat cv

nolegend prevents the table legend identifying the subpopulations from being displayed.

display_options: noomitted, vsquish, noemptycells, baselevels, allbaselevels; see [R] Estimation options.

Options for estat gof

- group(#) specifies the number of quantiles to be used to group the data for the goodness-of-fit test. The minimum allowed value is group(2). The maximum allowed value is group(df), where df is the design degrees of freedom (e(df_r)). The default is group(10).
- total requests that the goodness-of-fit test statistic be computed using the total estimator instead of the mean estimator.
- all requests that the goodness-of-fit test statistic be computed for all observations in the data, ignoring any if or in restrictions specified with the model fit.

Options for estat vce

covariance displays the matrix as a variance-covariance matrix; this is the default.

- correlation displays the matrix as a correlation matrix rather than a variance-covariance matrix. rho is a synonym.
- equation(*spec*) selects the part of the VCE to be displayed. If *spec* is *eqlist*, the VCE for the listed equations is displayed. If *spec* is *eqlist1* \ *eqlist2*, the part of the VCE associated with the equations in *eqlist1* (rowwise) and *eqlist2* (columnwise) is displayed. If *spec* is *, all equations are displayed. equation() implies block if diag is not specified.

block displays the submatrices pertaining to distinct equations separately.

diag displays the diagonal submatrices pertaining to distinct equations separately.

- format(% fmt) specifies the number format for displaying the elements of the matrix. The default is
 format(%10.0g) for covariances and format(%8.4f) for correlations. See [U] 12.5 Formats: Controlling how data are displayed for more information.
- nolines suppresses lines between equations.
- display_options: noomitted, noemptycells, baselevels, allbaselevels; see [R] Estimation options.

Remarks and examples

Example 1

Using data from the Second National Health and Nutrition Examination Survey (NHANES II) (Mc-Dowell et al. 1981), let's estimate the population means for total serum cholesterol (tcresult) and for serum triglycerides (tgresult).

```
. use https://www.stata-press.com/data/r19/nhanes2
. svy: mean tcresult tgresult
(running mean on estimation sample)
Survey: Mean estimation
Number of strata = 31
                                  Number of obs =
                                                          5,050
Number of PSUs
               = 62
                                  Population size = 56,820,832
                                  Design df
                                                  =
                                                             31
                           Linearized
                            std. err.
                                           [95% conf. interval]
                     Mean
   tcresult
                 211.3975
                            1.252274
                                           208.8435
                                                       213.9515
    tgresult
                  138.576
                            2.071934
                                           134.3503
                                                       142.8018
```

We can use estat svyset to remind us of the survey design characteristics that were used to produce these results.

```
. estat svyset
Sampling weights: finalwgt
VCE: linearized
Single unit: missing
Strata 1: strata
Sampling unit 1: psu
FPC 1: <zero>
```

estat effects reports a table of design and misspecification effects for each mean we estimated.

```
. estat effects, deff deft meff meft
```

	Mean	Linearized std. err.	DEFF	DEFT	MEFF	MEFT
tcresult	211.3975	1.252274	3.57141	1.88982	3.46105	1.86039
tgresult	138.576	2.071934	2.35697	1.53524	2.32821	1.52585

estat size reports a table that contains sample and population sizes.

. estat size

	Mean	Linearized std. err.	Obs	Size
tcresult	211.3975	1.252274	5,050	56,820,832
tgresult	138.576	2.071934	5,050	56,820,832

estat size can also report a table of subpopulation sizes.

- . svy: mean tcresult, over(sex)
 (output omitted)
- . estat size

Over	Mean	Linearized std. err.	Obs	Size
c.tcresult@				
sex Male	210.7937	1.312967	4,915	56.159.480
Female	215.2188	1.193853	5,436	60,998,033

estat sd reports a table of subpopulation standard deviations.

. estat sd

Over	Mean	Std. dev.
c.tcresult@ sex Male	210.7937	45.79065
Female	215.2188	50.72563

estat cv reports a table of coefficients of variations for the estimates.

. estat cv

Over	Mean	Linearized std. err.	CV (%)
c.tcresult@ sex			
Male Female	210.7937 215.2188	1.312967 1.193853	.622868 .554716

Example 2: Design effects with subpopulations

When there are subpopulations, estat effects can compute design effects with respect to one of two different hypothetical SRS designs. The default design is one in which SRS is conducted across the full population. The alternate design is one in which SRS is conducted entirely within the subpopulation of interest. This alternate design is used when the srssubpop option is specified.

Deciding which design is preferable depends on the nature of the subpopulations. If we can imagine identifying members of the subpopulations before sampling them, the alternate design is preferable. This case arises primarily when the subpopulations are strata or groups of strata. Otherwise, we may prefer to use the default.

4

Here is an example using the default with the NHANES II data.

- . use https://www.stata-press.com/data/r19/nhanes2b
- . svy: mean iron, over(sex) (output omitted)
- . estat effects

Over	Mean	Linearized std. err.	DEFF	DEFT
c.iron@sex Male Female	104.7969 97.16247	.557267 .6743344	1.36097 2.01403	1.16661 1.41916

Thus the design-based variance estimate is about 36% larger than the estimate from the hypothetical SRS design including the full population. We can get DEFF and DEFT for the alternate SRS design by using the srssubpop option.

. estat effects, srssubpop

Over	Mean	Linearized std. err.	DEFF	DEFT
c.iron@sex Male Female	104.7969 97.16247	.557267 .6743344	1.348 2.03132	1.16104 1.42524

Because the NHANES II did not stratify on sex, we think it problematic to consider design effects with respect to SRS of the female (or male) subpopulation. Consequently, we would prefer to use the default here, although the values of DEFF differ little between the two in this case.

For other examples (generally involving heavy oversampling or undersampling of specified subpopulations), the differences in DEFF for the two schemes can be much more dramatic. Consider the NMIHS data (Gonzalez, Krauss, and Scott 1992), and compute the mean of birthwgt over race:

- . use https://www.stata-press.com/data/r19/nmihs
- . svy: mean birthwgt, over(race)
 (output omitted)
- . estat effects

Over	Mean	Linearized std. err.	DEFF	DEFT
c.birthwgt@				
nonblack black	3402.32 3127.834	7.609532 6.529814	1.44376 .172041	1.20157 .414778
. estat effect	ts, srssubpop			
Over	Mean	Linearized std. err.	DEFF	DEFT
c.birthwgt@				
nonblack black	3402.32 3127.834	7.609532 6.529814	.826842 .528963	.909308 .727298

Because the NMIHS survey was stratified on race, marital status, age, and birthweight, we believe it reasonable to consider design effects computed with respect to SRS within an individual race group. Consequently, we would recommend here the alternative hypothetical design for computing design effects; that is, we would use the srssubpop option.

Example 3: Misspecification effects

Misspecification effects assess biases in variance estimators that are computed under the wrong assumptions. The survey literature (for example, Scott and Holt 1982, 850; Skinner 1989) defines misspecification effects with respect to a general set of "wrong" variance estimators. estat effects considers only one specific form: variance estimators computed under the incorrect assumption that our observed sample was selected through SRS.

The resulting "misspecification effect" measure is informative primarily when an unweighted point estimator is approximately unbiased for the parameter of interest. See Eltinge and Sribney (1996a) for a detailed discussion of extensions of misspecification effects that are appropriate for *biased* point estimators.

Note the difference between a misspecification effect and a design effect. For a design effect, we compare our complex-design-based variance estimate with an estimate of the true variance that we would have obtained under a hypothetical true simple random sample. For a misspecification effect, we compare our complex-design-based variance estimate with an estimate of the variance from fitting the same model without weighting, clustering, or stratification.

4

estat effects defines MEFF and MEFT as

$$\begin{split} \text{MEFF} &= \hat{V}/\hat{V}_{\text{msp}} \\ \text{MEFT} &= \sqrt{\text{MEFF}} \end{split}$$

where \hat{V} is the appropriate design-based estimate of variance and \hat{V}_{msp} is the variance estimate computed with a misspecified design—ignoring the sampling weights, stratification, and clustering.

Here we request that the misspecification effects be displayed for the estimation of mean zinc levels from our NHANES II data.

```
. use https://www.stata-press.com/data/r19/nhanes2b
```

- . svy: mean zinc, over(sex)
- (output omitted)
- . estat effects, meff meft

Over	Mean	Linearized std. err.	MEFF	MEFT
c.zinc@sex Male Female	90.74543 83.8635	.5850741 .4689532	6.28254 6.32648	2.5065 2.51525

If we run ci means without weights, we get the standard errors that are $(\hat{V}_{msp})^{1/2}$.

```
. sort sex
```

```
. ci means zinc if sex == "Male":sex
    Variable
                      Obs
                                  Mean
                                          Std. err.
                                                            [95% conf. interval]
                    4.375
                              89.53143
                                           .2334228
                                                            89.0738
                                                                        89.98906
        zinc
. display _se[zinc#1.sex]/r(se)
2.5064994
. display ( se[zinc#1.sex]/r(se))^2
6.2825393
. ci means zinc if sex == "Female":sex
   Variable
                      Obs
                                                            [95% conf. interval]
                                  Mean
                                          Std. err.
                    4,827
                              83.76652
                                            .186444
                                                           83.40101
        zinc
                                                                        84.13204
. display _se[zinc#2.sex]/r(se)
2.515249
. display (_se[zinc#2.sex]/r(se))^2
6.3264774
```

Example 4: Design and misspecification effects for linear combinations

Let's compare the mean of total serum cholesterol (tcresult) between men and women in the NHANES II dataset.

```
. use https://www.stata-press.com/data/r19/nhanes2
. svy: mean tcresult, over(sex)
(running mean on estimation sample)
Survey: Mean estimation
Number of strata = 31
                                   Number of obs =
                                                         10,351
Number of PSUs
               = 62
                                   Population size = 117, 157, 513
                                   Design df
                                                  =
                                                              31
                             Linearized
                                            [95% conf. interval]
                       Mean
                            std. err.
c.tcresult@sex
                   210.7937
                             1.312967
                                            208.1159
                                                        213.4715
        Male
      Female
                   215.2188
                              1.193853
                                             212.784
                                                        217.6537
```

We can use estat lceffects to report the standard error, design effects, and misspecification effects of the difference between the above means.

. estat lceffects tcresult#1.sex - tcresult#2.sex, deff deft meff meft

```
( 1) c.tcresult@1bn.sex - c.tcresult@2.sex = 0
```

Mean	Coefficient	Std. err.	DEFF	DEFT	MEFF	MEFT
(1)	-4.425109	1.086786	1.31241	1.1456	1.27473	1.12904

4

Example 5: Using survey data to determine Neyman allocation

Suppose that we have partitioned our population into L strata and stratum h contains N_h individuals. Also let σ_h represent the standard deviation of a quantity we wish to sample from the population. According to Cochran (1977, sec. 5.5), we can minimize the variance of the stratified mean estimator, for a fixed sample size n, if we choose the stratum sample sizes according to Neyman allocation:

$$n_h = n \frac{N_h \sigma_h}{\sum_{i=1}^L N_i \sigma_i} \tag{1}$$

We can use estat sd with our current survey data to produce a table of subpopulation standard-deviation estimates. Then we could plug these estimates into (1) to improve our survey design for the next time we sample from our population.

Here is an example using birthweight from the NMIHS data. First, we need estimation results from svy: mean over the strata.

```
. use https://www.stata-press.com/data/r19/nmihs
. svyset [pw=finwgt], strata(stratan)
Sampling weights: finwgt
            VCE: linearized
      Single unit: missing
            Strata 1: stratan
Sampling unit 1: <observations>
            FPC 1: <zero>
. svy: mean birthwgt, over(stratan)
      (output omitted)
```

Next we will use estat size to report the table of stratum sizes. We will also generate matrix p_{obs} to contain the observed percent allocations for each stratum. In the matrix expression, $r(_N)$ is a row vector of stratum sample sizes and e(N) contains the total sample size. $r(_N_subp)$ is a row vector of the estimated population stratum sizes.

. estat size

Over	Mean	Linearized std. err.	Obs	Size
c.birthwgt@ stratan				
1	1049.434	19.00149	841	18,402.98161
2	2189.561	9.162736	803	67,650.95932
3	3303.492	7.38429	3,578	579,104.6188
4	1036.626	12.32294	710	29,814.93215
5	2211.217	9.864682	714	153,379.07445
6	3485.42	8.057648	3,300	3,047,209.105

```
. matrix p_{obs} = 100 * r(N)/e(N)
```

. matrix nsubp = r(_N_subp)

Now we call estat sd to report the stratum standard-deviation estimates and generate matrix p_neyman to contain the percent allocations according to (1). In the matrix expression, r(sd) is a vector of the stratum standard deviations.

```
. estat sd
```

Over	Me	an Sto	l. dev.			
c.birthwgt(stratan	<u>ð</u>					
1	1049.4	34 23	305.931			
2	2189.5	61 55	55.7971			
3	3303.4	92 68	37.3575			
4	1036.6	26 99	99.0867			
5	2211.2	17 34	19.8068			
6	3485.	42 30	0.6945			
matrix n n	yman = 100	* hadar	ard(ns	ubn r(sd))/el(nsubn*	r(sd), 1, 1
. matrix p_n	cyman 100			uop,1 (5u))/ci(iisubp)	1(50),1,1)
. matrix list	c p_obs, io	rmat(%4	.1±)			
p_obs[1,6]						
c.birth	vgt@ c.bir	thwgt@	c.birt	hwgt@ c.	birthwgt@	c.birthwgt@
1.stra	an 2.st	ratan	3.str	atan 4	.stratan	5.stratan
r1 8	3.5	8.1		36.0	7.1	7.2
c.birth	vot.0					
6 strat	an					
r1 3:	3.2					
. matrix list	p_neyman,	format	(%4.1İ)			
p_neyman[1,6]						
c.birth	vgt@ c.bir	thwgt@	c.birt	hwgt@ c.	birthwgt@	c.birthwgt@
1.stra	an 2.st	ratan	3.str	atan 4	.stratan	5.stratan
r1 2	2.9	2.5		26.9	2.0	3.6
c.birth	vot.0					
6.strat	an					
r1 6'	2 0					
0.						

We can see that strata 3 and 6 each contain about one-third of the observed data, with the rest of the observations spread out roughly equally to the remaining strata. However, plugging our sample estimates into (1) indicates that stratum 6 should get 62% of the sampling units, stratum 3 should get about 27%, and the remaining strata should get a roughly equal distribution of sampling units.

Example 6: Summarizing singleton and certainty strata

Use estat strata with svy estimation results to produce a table that reports the number of singleton and certainty strata in each sampling stage. Here is an example using (fictional) data from a complex survey with five sampling stages (the dataset is already svyset). If singleton strata are present, estat strata will report their effect on the standard errors.

```
. use https://www.stata-press.com/data/r19/strata5
```

```
. svy: total y
 (output omitted)
```

```
(output onnited
```

```
. estat strata
```

Stage	Singleton strata	Certainty strata	Total strata
1	0	1	4
2	1	0	10
3	0	3	29
4	2	0	110
5	204	311	865

Note: Missing standard error because of stratum with single sampling unit.

estat strata also reports the scale factor used when the singleunit(scaled) option is svyset. Of the 865 strata in the last stage, 204 are singleton strata and 311 are certainty strata. Thus the scaling factor for the last stage is

865 - 311	\sim	1 58
$\overline{865 - 311 - 204}$	\sim	1.00

```
. svyset, singleunit(scaled) noclear
  (output omitted)
```

```
. svy: total y (output omitted)
```

. estat strata

Stage	Singleton strata	Certainty strata	Total strata	Scale factor
1	0	1	4	1
2	1	0	10	1.11
3	0	3	29	1
4	2	0	110	1.02
5	204	311	865	1.58

Note: Variances scaled within each stage to handle strata with a single sampling unit.

The singleunit(scaled) option of svyset is one of three methods in which Stata's svy commands can automatically handle singleton strata when performing variance estimation; see [SVY] Variance estimation for a brief discussion of these methods.

Example 7: Goodness-of-fit test for svy: logistic

From example 2 in [SVY] **svy estimation**, we modeled the incidence of high blood pressure as a function of height, weight, age, and sex (using the female indicator variable).

```
. use https://www.stata-press.com/data/r19/nhanes2d
. svyset
Sampling weights: finalwgt
            VCE: linearized
    Single unit: missing
       Strata 1: strata
Sampling unit 1: psu
          FPC 1: <zero>
. svy: logistic highbp height weight age female
(running logistic on estimation sample)
Survey: Logistic regression
Number of strata = 31
                                                 Number of obs =
                                                                        10,351
Number of PSUs = 62
                                                 Population size = 117, 157, 513
                                                 Design df
                                                                =
                                                                            31
                                                 F(4, 28)
                                                                 =
                                                                        368.33
                                                 Prob > F
                                                                 =
                                                                        0.0000
                           Linearized
              Odds ratio
      highbp
                            std. err.
                                           t
                                                P>|t|
                                                          [95% conf. interval]
      height
                 .9657022
                            .0051511
                                       -6.54
                                                0.000
                                                          .9552534
                                                                      .9762654
                                        20.22
                                                0.000
                                                          1.047551
                                                                      1.058524
      weight
                1.053023
                            .0026902
                1.050059
                            .0019761
                                        25.96
                                                0.000
                                                          1.046037
                                                                     1.054097
        age
                                                          .5564402
      female
                 .6272129
                            .0368195
                                        -7.95
                                                0.000
                                                                      .706987
       cons
                  .716868
                          .6106878
                                       -0.39
                                                0.699
                                                          .1261491
                                                                      4.073749
```

Note: _cons estimates baseline odds.

We can use estat gof to perform a goodness-of-fit test for this model.

```
. estat gof Logistic model for highbp, goodness-of-fit test F(9,23)\ =\ 5.32 \label{eq:F} Prob > F = 0.0006
```

The F statistic is significant at the 5% level, indicating that the model is not a good fit for these data.

4

Stored results

estat svyset stores the following in r():

```
Scalars
    r(stages)
                                 number of sampling stages
    r(stages_wt)
                                 last stage containing stage-level weights
                                 bootstrap mean-weight adjustment
    r(bsn)
    r(fay)
                                 Fay's adjustment
    r(dof)
                                 dof() value
Macros
    r(wtype)
                                 weight type
    r(wexp)
                                 weight expression
    r(wvar)
                                 weight variable name
```

r(weight#)	variable identifying weight for stage #
r(su#)	variable identifying sampling units for stage #
r(strata#)	variable identifying strata for stage #
r(fpc#)	FPC for stage #
r(bsrweight)	bsrweight() variable list
r(brrweight)	brrweight() variable list
r(jkrweight)	jkrweight() variable list
r(sdrweight)	sdrweight() variable list
r(sdrfpc)	<pre>fpc() value from within sdrweight()</pre>
r(vce)	vcetype specified in vce()
r(mse)	mse, if specified
r(poststrata)	poststrata() variable
r(postweight)	postweight() variable
r(rake)	rake() specification
r(regress)	regress() specification
r(settings)	svyset arguments to reproduce the current settings
r(singleunit)	singleunit() setting
-	

estat strata stores the following in r():

Matrices

r(_N_strata_single)	number of strata with one sampling unit
r(_N_strata_certain)	number of certainty strata
r(_N_strata)	number of strata
r(scale)	variance scale factors used when singleunit(scaled) is svyset

estat effects stores the following in r():

Matrices

r(deff)	vector of DEFF estimates
r(deft)	vector of DEFT estimates
r(deffsub)	vector of DEFF estimates for srssubpop
r(deftsub)	vector of DEFT estimates for srssubpop
r(meff)	vector of MEFF estimates
r(meft)	vector of MEFT estimates

estat lceffects stores the following in r():

Scalars

r(estimate)	point estimate
r(se)	estimate of standard error
r(df)	degrees of freedom
r(deff)	DEFF estimate
r(deft)	DEFT estimate
r(deffsub)	DEFF estimate for srssubpop
r(deftsub)	DEFT estimate for srssubpop
r(meff)	MEFF estimate
r(meft)	MEFT estimate

estat size stores the following in r():

Matrices

r(_N)	vector of numbers of nonmissing observations
r(_N_subp)	vector of subpopulation size estimates

estat sd stores the following in r():

Macros	
r(srssubpop)	srssubpop, if specified
Matrices	
r(mean)	vector of subpopulation mean estimates
r(sd)	vector of subpopulation standard-deviation estimates
r(variance)	vector of subpopulation variance estimates

estat cv stores the following in r():

Matrices	
r(b)	estimates
r(se)	standard errors of the estimates
r(cv)	coefficients of variation of the estimates

estat gof stores the following in r():

Scalars	
r(p)	<i>p</i> -value associated with the test statistic
r(F)	F statistic, if e(df_r) was stored by estimation command
r(df1)	numerator degrees of freedom for F statistic
r(df2)	denominator degrees of freedom for F statistic
r(chi2)	χ^2 statistic, if e(df_r) was not stored by estimation command
r(df)	degrees of freedom for χ^2 statistic

estat vce stores the following in r():

Matrices	
r(V)	VCE or correlation matrix

Methods and formulas

Methods and formulas are presented under the following headings:

Design effects Linear combinations Misspecification effects Population and subpopulation standard deviations Coefficient of variation Goodness of fit for binary response models

Design effects

estat effects produces two estimators of design effect, DEFF and DEFT.

DEFF is estimated as described in Kish (1965) as

$$\text{DEFF} = \frac{\hat{V}(\hat{\theta})}{\hat{V}_{\text{srswor}}(\tilde{\theta}_{\text{srs}})}$$

where $\hat{V}(\hat{\theta})$ is the design-based estimate of variance for a parameter, θ , and $\hat{V}_{srswor}(\tilde{\theta}_{srs})$ is an estimate of the variance for an estimator, $\tilde{\theta}_{srs}$, that would be obtained from a similar hypothetical survey conducted using SRS without replacement (wor) and with the same number of sample elements, m, as in the actual survey. For example, if θ is a total Y, then

$$\hat{V}_{\text{srswor}}(\tilde{\theta}_{\text{srs}}) = (1-f)\frac{\widehat{M}}{m-1}\sum_{j=1}^{m} w_j (y_j - \hat{\overline{Y}})^2 \tag{1}$$

where $\hat{\overline{Y}} = \hat{Y}/\widehat{M}$. The factor (1 - f) is a finite population correction. If the user sets an FPC for the first stage, $f = m/\widehat{M}$ is used; otherwise, f = 0.

DEFT is estimated as described in Kish (1987, 41) as

$$\text{DEFT} = \sqrt{\frac{\hat{V}(\hat{\theta})}{\hat{V}_{\text{srswr}}(\tilde{\theta}_{\text{srs}})}}$$

where $\hat{V}_{\text{srswr}}(\tilde{\theta}_{\text{srs}})$ is an estimate of the variance for an estimator, $\tilde{\theta}_{\text{srs}}$, obtained from a similar survey conducted using SRS with replacement (wr). $\hat{V}_{\text{srswr}}(\tilde{\theta}_{\text{srs}})$ is computed using (1) with f = 0.

When computing estimates for a subpopulation, S, and the srssubpop option is not specified (that is, the default), (1) is used with $w_{Sj} = I_S(j) w_j$ in place of w_j , where

$$I_{\mathcal{S}}(j) = egin{cases} 1, ext{if } j \in \mathcal{S} \ 0, ext{otherwise} \end{cases}$$

The sums in (1) are still calculated over all elements in the sample, regardless of whether they belong to the subpopulation: by default, the SRS is assumed to be done across the full population.

When the subsolution option is specified, the SRS is carried out within subpopulation S. Here (1) is used with the sums restricted to those elements belonging to the subpopulation; m is replaced with m_S , the number of sample elements from the subpopulation; \widehat{M} is replaced with \widehat{M}_S , the sum of the weights from the subpopulation; and \widehat{Y} is replaced with $\widehat{Y}_S = \widehat{Y}_S / \widehat{M}_S$, the weighted mean across the subpopulation.

Linear combinations

estat lceffects estimates $\eta = C\theta$, where θ is a $q \times 1$ vector of parameters (for example, population means or population regression coefficients) and C is any $1 \times q$ vector of constants. The estimate of η is $\hat{\eta} = C\hat{\theta}$, and its variance estimate is

$$\hat{V}(\hat{\eta}) = C\hat{V}(\hat{\theta})C'$$

Similarly, the SRS without replacement (srswor) variance estimator used in the computation of DEFF is

$$\hat{V}_{\rm srswor}(\tilde{\eta}_{\rm srs}) = C\hat{V}_{\rm srswor}(\hat{\theta}_{\rm srs})C'$$

and the SRS with replacement (srswr) variance estimator used in the computation of DEFT is

$$\hat{V}_{\rm srswr}(\tilde{\eta}_{\rm srs}) = C\hat{V}_{\rm srswr}(\hat{\theta}_{\rm srs})C'$$

The variance estimator used in computing MEFF and MEFT is

$$\hat{V}_{\rm msp}(\tilde{\eta}_{\rm msp}) = C \hat{V}_{\rm msp}(\hat{\theta}_{\rm msp}) C'$$

estat lceffects was originally developed under a different command name; see Eltinge and Sribney (1996b).

Misspecification effects

estat effects produces two estimators of misspecification effect, MEFF and MEFT.

$$\begin{split} \text{MEFF} &= \frac{\hat{V}(\hat{\theta})}{\hat{V}_{\text{msp}}(\hat{\theta}_{\text{msp}})} \\ \text{MEFT} &= \sqrt{\text{MEFF}} \end{split}$$

where $\hat{V}(\hat{\theta})$ is the design-based estimate of variance for a parameter, θ , and $\hat{V}_{msp}(\hat{\theta}_{msp})$ is the variance estimate for $\hat{\theta}_{msp}$. These estimators, $\hat{\theta}_{msp}$ and $\hat{V}_{msp}(\hat{\theta}_{msp})$, are based on the incorrect assumption that the observations were obtained through SRS with replacement: they are the estimators obtained by simply ignoring weights, stratification, and clustering. When θ is a total Y, the estimator and its variance estimate are computed using the standard formulas for an unweighted total:

$$\widehat{Y}_{\mathrm{msp}} = \widehat{M} \, \overline{y} = \frac{\widehat{M}}{m} \sum_{j=1}^{m} y_j$$

$$\hat{V}_{\mathrm{msp}}(\hat{Y}_{\mathrm{msp}}) = \frac{\widehat{M}^2}{m(m-1)} \sum_{j=1}^m \bigl(y_j - \overline{y}\bigr)^2$$

When computing MEFF and MEFT for a subpopulation, sums are restricted to those elements belonging to the subpopulation, and \widehat{M}_S and \widehat{M}_S are used in place of m and \widehat{M} .

Population and subpopulation standard deviations

For srswr designs, the variance of the mean estimator is

$$V_{\rm srswr}(\overline{y}) = \sigma^2/n$$

where n is the sample size and σ is the population standard deviation. estat sd uses this formula and the results from mean and svy: mean to estimate the population standard deviation via

$$\hat{\sigma} = \sqrt{n \; \hat{V}_{\rm srswr}(\overline{y})}$$

Subpopulation standard deviations are computed similarly, using the corresponding variance estimate and sample size.

Coefficient of variation

The coefficient of variation (CV) for estimate $\hat{\theta}$ is

$$\operatorname{cv}(\hat{\theta}) = rac{\sqrt{\hat{V}(\hat{\theta})}}{|\hat{\theta}|} \times 100\%$$

A missing value is reported when $\hat{\theta}$ is zero.

Goodness of fit for binary response models

Let y_j be the *j*th observed value of the dependent variable, \hat{p}_j be the predicted probability of a positive outcome, and $\hat{r}_j = y_j - \hat{p}_j$. Let *g* be the requested number of groups from the group() option; then the \hat{r}_j are placed in *g* quantile groups as described in *Methods and formulas* for the xtile command in [D] **pctile**. Let $\bar{r} = (\bar{r}_1, \ldots, \bar{r}_g)$, where \bar{r}_i is the subpopulation mean of the \hat{r}_j for the *i*th quantile group. The standard Wald statistic for testing $H_0: \bar{r} = \mathbf{0}$ is

$$\widehat{X}^2 = \overline{r} \{ \widehat{V}(\overline{r}) \}^{-1} \overline{r}'$$

where $\hat{V}(\bar{r})$ is the design-based variance estimate for \bar{r} . Here \hat{X}^2 is approximately distributed as a χ^2 with g-1 degrees of freedom. This Wald statistic is one of the three goodness-of-fit statistics discussed in Graubard, Korn, and Midthune (1997). estat gof reports this statistic when the design degrees of freedom is missing, such as with svy bootstrap results.

According to Archer and Lemeshow (2006), the F-adjusted mean residual test is given by

$$\hat{F} = \hat{X}^2(d-g+2)/(dg)$$

where d is the design degrees of freedom. Here \hat{F} is approximately distributed as an F with g-1 numerator and d-g+2 denominator degrees of freedom.

With the total option, estat gof uses the subpopulation total estimator instead of the subpopulation mean estimator.

References

Archer, K. J., and S. A. Lemeshow. 2006. Goodness-of-fit test for a logistic regression model fitted using survey sample data. Stata Journal 6: 97–105.

Cochran, W. G. 1977. Sampling Techniques. 3rd ed. New York: Wiley.

Eltinge, J. L., and W. M. Sribney. 1996a. Accounting for point-estimation bias in assessment of misspecification effects, confidence-set coverage rates and test sizes. Unpublished manuscript, Department of Statistics, Texas A&M University.

. 1996b. svy5: Estimates of linear combinations and hypothesis tests for survey data. *Stata Technical Bulletin* 31: 31–42. Reprinted in *Stata Technical Bulletin Reprints*, vol. 6, pp. 246–259. College Station, TX: Stata Press.

- Gonzalez, J. F., Jr., N. Krauss, and C. Scott. 1992. Estimation in the 1988 National Maternal and Infant Health Survey. Proceedings of the Section on Statistics Education, American Statistical Association 343–348.
- Graubard, B. I., E. L. Korn, and D. Midthune. 1997. "Testing goodness-of-fit for logistic regression with survey data". In Proceedings of the Section on Survey Research Methods, Joint Statistical Meetings, 170–174. Alexandria, VA: American Statistical Association.
- Kish, L. 1965. Survey Sampling. New York: Wiley.

——. 1987. Statistical Design for Research. New York: Wiley.

- McDowell, A., A. Engel, J. T. Massey, and K. Maurer. 1981. "Plan and operation of the Second National Health and Nutrition Examination Survey, 1976–1980". In Vital and Health Statistics, ser. 1, no. 15. Hyattsville, MD: National Center for Health Statistics.
- Scott, A. J., and D. Holt. 1982. The effect of two-stage sampling on ordinary least squares methods. Journal of the American Statistical Association 77: 848–854. https://doi.org/10.2307/2287317.
- Skinner, C. J. 1989. "Introduction to part A". In Analysis of Complex Surveys, edited by C. J. Skinner, D. Holt, and T. M. F. Smith, 23–58. New York: Wiley.
- West, B. T., and S. E. McCabe. 2012. Incorporating complex sample design effects when only final survey weights are available. Stata Journal 12: 718–725.

Also see

[SVY] svy postestimation — Postestimation tools for svy

[SVY] svy estimation — Estimation commands for survey data

[SVY] Subpopulation estimation — Subpopulation estimation for survey data

[SVY] Variance estimation — Variance estimation for survey data

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on citing Stata documentation.