

Description

`svyemarkout` is a programmer's command that resets the values of *markvar* to contain 0 wherever any of the survey-characteristic variables (previously set by `svyset`) contain missing values.

Syntax

```
svyemarkout [ markvar ]
```

Remarks and examples

`svyemarkout` assumes that *markvar* was created by `marksample` or `mark`; see [\[P\] mark](#). This command is most helpful for developing estimation commands that use `ml` to fit models using maximum pseudolikelihood directly, instead of relying on the `svy` prefix; see [\[P\] program properties](#) for a discussion of how to write programs to be used with the `svy` prefix.

► Example 1

```
program mysvyprogram, ...
    ...
    syntax ...
    marksample touse
    svyemarkout 'touse'
    ...
end
```



Stored results

`svyemarkout` stores the following in `s()`:

```
Macros
    s(weight)      weight variable set by svyset
```

Also see

[\[P\] mark](#) — Mark observations for inclusion

[\[P\] program properties](#) — Properties of user-defined programs

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

