

## collect style html — Collection styles for HTML files

[Description](#)  
[Options](#)

[Quick start](#)  
[Remarks and examples](#)

[Menu](#)  
[Stored results](#)

[Syntax](#)  
[Also see](#)

## Description

`collect style html` specifies styles to be used when exporting a table from a collection to an HTML file.

`collect style html`, typed without any options, will clear the existing HTML appearance styles for the current collection.

## Quick start

Specify that tables exported from the current collection to a HyperText Markup Language (HTML) file use tag `<th>` for header cells.

```
collect style html, usesth
```

Clear the current HTML appearance styles

```
collect style html
```

## Menu

Statistics > Summaries, tables, and tests > Tables and collections > Collect styles > Styles for HTML

## Syntax

*Specify styles to be used when exporting a collection to an HTML file*

```
collect style html [ , options ]
```

*Clear existing HTML appearance styles*

```
collect style html [ , name(cname) ]
```

*options*

Description

---

<code>name(cname)</code>	apply HTML styles to collection <i>cname</i>
<code>[no]bcollapse</code>	collapse adjacent cell borders
<code>[no]usesth</code>	use HTML tag <code>&lt;th&gt;</code> for header cells

---

## Options

`name(cname)` specifies that the HTML styles be applied to collection *cname*.

When `name(cname)` is specified without any other options, HTML styles are cleared from collection *cname*.

The default in both cases is to apply the style changes to the current collection.

`bcollapse` and `nobcollapse` control whether adjacent cell borders are collapsed into a single border.

`bcollapse`, the default, specifies that `collect export` collapse adjacent cell borders into a single border.

`nobcollapse` specifies that `collect export` not collapse adjacent cell borders into a single border.

`useth` and `nouseth` control which HTML tag to use for header cells.

`useth` specifies that `collect export` use the HTML tag `<th>` for header cells.

`nouseth`, the default, specifies that `collect export` use the HTML tag `<td>` rather than `<th>` for header cells.

## Remarks and examples

[stata.com](http://www.stata.com)

`collect style html` allows you to specify styles for the table that you will export to an HTML file with `collect export`. If you do not like the change you have made, you can clear the HTML appearance styles by typing the following:

```
. collect style html
```

This change will be applied to the current collection. To make this change for another collection, specify the collection name with the `name()` option.

## Stored results

`collect style html` stores the following in `s()`:

```
Macros
      s(collection) name of collection
```

## Also see

[TABLES] [collect export](#) — Export table from a collection