

Description

`collect style smcl` specifies styles to be used when exporting a table from a collection to a SMCL file.

`collect style smcl`, typed without any options, will clear the existing SMCL appearance styles for the current collection.

Quick start

Specify that long table notes wrap with the width of the table

```
collect style smcl, wrapnotes
```

Clear the current SMCL appearance styles

```
collect style smcl
```

Menu

Statistics > Summaries, tables, and tests > Tables and collections > Collect styles > Styles for SMCL

Syntax

Specify styles to be used when exporting a collection to a SMCL file

```
collect style smcl [ , options ]
```

Clear existing SMCL appearance styles

```
collect style smcl [ , name(cname) ]
```

cname is the name of an existing collection.

<i>options</i>	Description
<code>name(cname)</code>	apply SMCL styles to collection <i>cname</i>
<code>[no]wrapnotes</code>	specify whether to wrap long notes at table’s width

Options

`name(cname)` specifies that the SMCL styles be applied to collection *cname*.

When `name(cname)` is specified without any other options, SMCL styles are cleared from collection *cname*.

The default in both cases is to apply the style changes to the current collection.

`wrapnotes` and `nowrapnotes` specify whether to break long table notes.

`wrapnotes`, the default, specifies that long notes break at the table's width.

`nowrapnotes` specifies that long notes are allowed to extend beyond the table width.

SMCL line sizes can range from 40 to 255, so tables with fewer than 40 display columns will have notes that wrap at 40 display columns.

Remarks and examples

`collect style smcl` allows you to specify styles for the table that you will export to a SMCL file with `collect export`. If you do not like the change you have made, you can clear the SMCL appearance styles by typing the following:

```
. collect style smcl
```

This change will be applied to the current collection. To make this change for another collection, specify the collection name with the `name()` option.

Stored results

`collect style smcl` stores the following in `s()`:

Macros

```
s(collection)  name of collection
```

Also see

[TABLES] [collect export](#) — Export table from a collection

[TABLES] [collect query](#) — Query collection style properties

