

## Description

This is the [TABLES] manual. What is surprising is that, used alone, the commands in this manual cannot create a table. The tables created here are all based on results collected from other commands, commands not documented in this manual, commands like `regress`, `margins`, `bayes`, `ttest`, `mi`, `mean`, `table`, and so on.

This manual documents the commands that collect results from other commands; lay out those results into one-way, two-way, or multiway tables; customize the headers of those tables; change the appearance of the results; and export the tables to Microsoft Word, Microsoft Excel, PDF, HTML,  $\text{\LaTeX}$ , [SMCL](#), or Markdown.

We call the collected results from one or more commands collections. The purpose of this manual is to explain how to create collections, manage collections, create tables from collections, and export those tables.

For more details about how to create tables step by step, see [Mitchell \(2025\)](#).

## Remarks and examples

Remarks are presented under the following headings:

*What is in this manual?*  
*What are collections?*  
*Do you need collections?*  
*The dtable and etable commands*  
*The table command*

## What is in this manual?

Presenting results is the final step for most research, and a major part of presenting results is creating effective tables.

Here are some tables created with the collection system:

```
. use https://www.stata-press.com/data/r19/nhanes21
. table ...
...
...
. collect layout ...
. collect preview
```

	Male		Female	
Diabetes status				
Not diabetic	4698.0	(95.6)	5152.0	(94.8)
Diabetic	217.0	(4.4)	282.0	(5.2)
Age, mean (sd)	47.4	(17.2)	47.7	(17.3)
BMI, mean (sd)	25.5	(4.0)	25.6	(5.6)
Health status				
Excellent	1252.0	(25.5)	1155.0	(21.3)
Very good	1213.0	(24.7)	1378.0	(25.4)
Good	1340.0	(27.3)	1598.0	(29.5)
Fair	722.0	(14.7)	948.0	(17.5)
Poor	382.0	(7.8)	347.0	(6.4)
Systolic BP, mean (sd)	132.9	(21.0)	129.1	(25.1)

```
. use https://www.stata-press.com/data/r19/nhanes21
. collect: ...
...
...
. collect layout ...
. collect preview
```

	NE	MW	Region S	W	All
Age (years)					
Odds ratio	1.07	1.06	1.06	1.06	1.06
SE	(0.01)	(0.01)	(0.01)	(0.01)	(0.00)
Weight (kg)					
Odds ratio	1.03	1.03	1.02	1.02	1.03
SE	(0.01)	(0.01)	(0.01)	(0.01)	(0.00)
Female					
Odds ratio	1.93	1.41	1.48	1.25	1.48
SE	(0.44)	(0.27)	(0.26)	(0.25)	(0.15)
Intercept					
Odds ratio	0.00	0.00	0.00	0.00	0.00
SE	(0.00)	(0.00)	(0.00)	(0.00)	(0.00)

This manual is a little bit about the collect: prefix. It is a lot about the

...  
...  
...

you saw above in the command listings.

## What are collections?

Collections are the collected results from one or more commands. They contain every result stored by the commands. They also contain labels for everything in the collection. Some labels are system default labels such as “Coefficient” for regression coefficients or  $\chi^2$  for chi-squared statistics. Some labels come from you and your dataset. If the collected commands reference variables, such as regression coefficients, the variables will be labeled with the [variable labels](#) from the dataset. If the collected commands use categorical variables that are [value labeled](#), those labels become part of the collection.

Collections also contain [styles](#). Styles determine how everything looks on the tables you create. Styles determine how row and column headers are composed. Styles determine what numeric format is used. Styles determine whether text is bolded, italicized, colored, etc. When you create a collection, it will have the default system styles unless you specified that it start from a set of styles you previously saved.

You have great control over which values or labels are affected by styles. You can choose an overall numeric format for all values or a custom numeric format for coefficients, their standard errors, and their confidence intervals. All of this while using a different format for their  $z$  statistics and a yet different format for their  $p$ -values. And the control can be even finer still. You can choose to have all coefficient statistics for the variable `weight` highlighted by giving their cells a light-blue background.

You can modify anything in a collection. You can modify any label. You can modify any style.

You cannot modify values. Those were produced by your commands, and they are sacrosanct. You can modify anything that identifies, labels, formats, or presents those values.

You reference everything stored in a collection using [tags](#). Those tags are created automatically for you when you collect results. You can also specify additional tags while collecting, and you can even remap tags in a collection. Tags are organized into groupings called dimensions; this organization makes it easier to specify what you want on the rows and columns of your tables.

For an illustrative look “under the hood” of the collection system, see [Mitchell \(2025, chap. 5\)](#).

## Do you need collections?

There are three primary reasons you may need collections.

1. You want to create a table showing the results from more than one command.
2. You want to customize how a table looks—layout, headers, numeric formats, bolding, italics, colors, etc.
3. You want to present your results in Microsoft Word, Microsoft Excel, PDF, HTML,  $\text{\LaTeX}$ , [SMCL](#), or Markdown.

Other commands in Stata are built for creating specific kinds of tables from data. Conversely, collections do not create results from data. They give you a framework to format the results you have collected from other commands.

Collecting results is easy; simply prefix almost any command with `collect:`, or type `collect get` after the command has run. You have created a collection. Every time you type `collect:` or `collect get` again, you are adding to a collection.

## The dtable and etable commands

The collection system was designed to give you the flexibility to create a table specific to your style and needs. However, there are certain tables that are used so commonly that they necessitated their own special commands. These commands are `dtable` and `etable`, and they are designed for creating and exporting tables all in a single step, without any knowledge of the commands in this manual.

`dtable` is designed to create a table of descriptive statistics, such as summary statistics for continuous and categorical variables, summary statistics for groups of your data, and tests of equality. `etable` is designed to create a table of estimation results, from one or more models. You can use it to create a table with the active estimation results, results from a preceding `margins` command, or results you stored with `estimates store`.

Both `dtable` and `etable` allow you to create a table complete with a title and notes, and export it to Microsoft Word, Microsoft Excel, PDF, HTML,  $\LaTeX$ , `SMCL`, or Markdown. Additionally, they automatically store the results in a collection, allowing you to customize the table further with the `collect` suite of commands. To learn more, see [\[R\] dtable](#) and [\[R\] etable](#).

If your goal is to create a table with a combination of estimation results, summary statistics, and other results, you will benefit from learning about the `table` command below.

## The table command

Stata has a couple of different commands that produce tabular results. If your intent is to summarize data to understand them, you may need only these commands and not need collections. However, if you want to customize the layout and appearance of the results from these commands, you will need to collect their results.

The `table` command is unique in that it creates a stunningly large range of tables and stores the results in a collection. If you came here to do any of the following things, you should begin with the `table` command:

- [One-way tabulations of frequencies, percentages, and proportions](#)
- [Two-way tabulations of frequencies, percentages, and proportions](#)
- [Multiway tabulations of frequencies, percentages, and proportions](#)
- [One-way, two-way, and multiway tables of summary statistics](#)
- [Tables of hypothesis tests](#)
- [Tables of regression results](#) (this includes the possibility of multiple regression commands)
- [Combinations of the above](#)

If you want to customize the results of `table` or export them, simply start with a `table` command, and then use any of the collection commands in this manual to customize and export the results. You may find that you need to combine the results of several `table` commands to create a collection with all the results you need on a table. You can do that by using `collect combine` or the `append` option of `table`. You can even combine the results from the `table` command with other commands such as [regression commands](#), `lincom`, `nlcom`, `ttest`, `margins`, and more.

## Acknowledgments

We are grateful to the authors of community-contributed commands for creating and exporting tables. We thank John Luke Gallup of Portland State University for `outreg`; Ian Watson, freelance researcher and of the University of New South Wales, for `tabout`; Ben Jann of the University of Bern for `estout`; Roy Wada of the Boston Public Health Commission for `outreg2`; Attaullah Shah of the Institute of Management Sciences for `asdoc`; and many more for their previous and ongoing contributions to Stata's reporting capabilities.

## Reference

Mitchell, M. N. 2025. *Create and Export Tables Using Stata*. College Station, TX: Stata Press.

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

