

set etable_style — Default style settings for etable

[Description](#)[Syntax](#)[Option](#)[Remarks and examples](#)[Also see](#)

Description

`set etable_style` controls the default styles used in tables created by `etable`. The default setting is `etable`, which means that `etable` uses the styles defined in the file `style-etable.stjson`. This file can be found in the ado-path.

Syntax

Use the system default styles in tables

```
set etable_style etable [ , permanently ]
```

Specify a style set to be used as the default in tables

```
set etable_style style [ , permanently ]
```

Option

`permanently` specifies that, in addition to making the change right now, the setting be remembered and become the default setting when you invoke Stata.

Remarks and examples

stata.com

`set etable_style` controls the default style used in tables created by `etable`. The default setting is `etable`, which means `etable` uses the styles defined in the file `style-etable.stjson`. This file can be found in the ado-path.

However, if you have a style that you plan to use with many of the tables that you will be creating, you can save that style to a file with `collect style save`. For example, you can save your style as `tabstyle.stjson` by typing the following:

```
. collect style save tabstyle.stjson
```

Then, to use that style by default with tables created by `etable`, you would type

```
. set etable_style tabstyle
```

`set etable_style` will then search for `style-tabstyle.stjson` in the ado-path. If `style-tabstyle.stjson` is not found, it will search the ado-path for `tabstyle.stjson`.

To see the current setting, type

```
. display c(etable_style)
```

Also see

[R] [etable](#) — Create a table of estimation results

[TABLES] [collect style save](#) — Save collection styles to disk