

<a href="#">Description</a>	<a href="#">Quick start</a>	<a href="#">Menu for estat</a>	<a href="#">Syntax</a>	<a href="#">Options</a>
<a href="#">Remarks and examples</a>	<a href="#">Methods and formulas</a>	<a href="#">References</a>	<a href="#">Also see</a>	

## Description

estat acplot plots the estimated autocorrelation and autocovariance functions of a stationary process using the parameters of a previously fit parametric model.

estat acplot is available after arima and arfima; see [\[TS\] arima](#) and [\[TS\] arfima](#).

## Quick start

Autocorrelation function using estimates from arima or arfima

```
estat acplot
```

Autocovariance function using estimates from arima or arfima

```
estat acplot, covariance
```

Same as above, and save results in mydata.dta

```
estat acplot, covariance saving(mydata)
```

## Menu for estat

Statistics > Postestimation

## Syntax

```
estat acplot [ , options ]
```

<i>options</i>	Description
<a href="#"><code>saving(filename[ , ...])</code></a>	save results to <i>filename</i> ; save variables in double precision; save variables with prefix <i>stubname</i>
<a href="#"><code>level(#)</code></a>	set confidence level; default is <code>level(95)</code>
<a href="#"><code>lags(#)</code></a>	use # autocorrelations
<a href="#"><code>covariance</code></a>	calculate autocovariances; the default is to calculate autocorrelations
<a href="#"><code>smemory</code></a>	report short-memory ACF; only allowed after <code>arfima</code>
CI plot	
<a href="#"><code>ciopts(rcap_options)</code></a>	affect rendition of the confidence bands
Plot	
<a href="#"><code>marker_options</code></a>	change look of markers (color, size, etc.)
<a href="#"><code>marker_label_options</code></a>	add marker labels; change look or position
<a href="#"><code>cline_options</code></a>	affect rendition of the plotted points
Y axis, X axis, Titles, Legend, Overall	
<a href="#"><code>twoway_options</code></a>	any options other than <code>by()</code> documented in <a href="#">[G-3]</a> <a href="#"><i>twoway_options</i></a>

## Options

`saving(filename[ , suboptions ])` creates a Stata data file (.dta file) consisting of the autocorrelation estimates, standard errors, and confidence bounds.

Five variables are saved: `lag` (lag number), `ac` (autocorrelation estimate), `se` (standard error), `ci_l` (lower confidence bound), and `ci_u` (upper confidence bound).

`double` specifies that the variables be saved as doubles, meaning 8-byte reals. By default, they are saved as floats, meaning 4-byte reals.

`name(stubname)` specifies that variables be saved with prefix *stubname*.

`replace` indicates that *filename* be overwritten if it exists.

`level(#)` specifies the confidence level, as a percentage, for confidence intervals. The default is `level(95)` or as set by `set level`; see [\[R\]](#) [level](#).

`lags(#)` specifies the number of autocorrelations to calculate. The default is to use  $\min\{\text{floor}(n/2) - 2, 40\}$ , where  $\text{floor}(n/2)$  is the greatest integer less than or equal to  $n/2$  and  $n$  is the number of observations.

`covariance` specifies the calculation of autocovariances instead of the default autocorrelations.

`smemory` specifies that the ARFIMA fractional integration parameter be ignored. The computed autocorrelations are for the short-memory ARMA component of the model. This option is allowed only after `arfima`.

CI plot

`ciopts(rcap_options)` affects the rendition of the confidence bands; see [\[G-3\]](#) [rcap\\_options](#).

## Plot

*marker\_options* affect the rendition of markers drawn at the plotted points, including their shape, size, color, and outline; see [G-3] *marker\_options*.

*marker\_label\_options* specify if and how the markers are to be labeled; see [G-3] *marker\_label\_options*.

*cline\_options* affect whether lines connect the plotted points and the rendition of those lines; see [G-3] *cline\_options*.

## Y axis, X axis, Titles, Legend, Overall

*twoway\_options* are any of the options documented in [G-3] *twoway\_options*, except by (). These include options for titling the graph (see [G-3] *title\_options*) and for saving the graph to disk (see [G-3] *saving\_option*).

## Remarks and examples

The dependent variable evolves over time because of random shocks in the time domain representation. The autocovariances  $\gamma_j$ ,  $j \in \{0, 1, \dots, \infty\}$ , of a covariance-stationary process  $y_t$  specify its variance and dependence structure, and the autocorrelations  $\rho_j$ ,  $j \in \{1, 2, \dots, \infty\}$ , provide a scale-free measure of  $y_t$ 's dependence structure. The autocorrelation at lag  $j$  specifies whether realizations at time  $t$  and realizations at time  $t - j$  are positively related, unrelated, or negatively related. `estat acplot` uses the estimated parameters of a parametric model to estimate and plot the autocorrelations and autocovariances of a stationary process.

## ► Example 1

In [example 1](#) of [\[TS\] arima](#), we fit an ARIMA(1,1,1) model of the US Wholesale Price Index (WPI) using quarterly data over the period 1960q1 through 1990q4.


```
. use https://www.stata-press.com/data/r19/wpi1
. arima wpi, arima(1,1,1)
(setting optimization to BHHH)
Iteration 0:  Log likelihood = -139.80133
Iteration 1:  Log likelihood = -135.6278
Iteration 2:  Log likelihood = -135.41838
Iteration 3:  Log likelihood = -135.36691
Iteration 4:  Log likelihood = -135.35892
(switching optimization to BFGS)
Iteration 5:  Log likelihood = -135.35471
Iteration 6:  Log likelihood = -135.35135
Iteration 7:  Log likelihood = -135.35132
Iteration 8:  Log likelihood = -135.35131
ARIMA regression
Sample: 1960q2 thru 1990q4                Number of obs      =          123
                                           Wald chi2(2)       =          310.64
Log likelihood = -135.3513                 Prob > chi2        =           0.0000
```

D.wpi	OPG					
	Coefficient	std. err.	z	P> z	[95% conf. interval]	
wpi						
_cons	.7498197	.3340968	2.24	0.025	.0950019	1.404637
ARMA						
ar						
L1.	.8742288	.0545435	16.03	0.000	.7673256	.981132
ma						
L1.	-.4120458	.1000284	-4.12	0.000	-.6080979	-.2159938
/sigma	.7250436	.0368065	19.70	0.000	.6529042	.7971829

Note: The test of the variance against zero is one sided, and the two-sided confidence interval is truncated at zero.

Now we use `estat acplot` to estimate the autocorrelations implied by the estimated ARMA parameters. We include `lags(50)` to indicate that autocorrelations be computed for 50 lags. By default, a 95% confidence interval is provided for each autocorrelation.

```
. estat acplot, lags(50)
```



The graph is similar to a typical autocorrelation function of an AR(1) process with a positive coefficient. The autocorrelations of a stationary AR(1) process decay exponentially toward zero.

◀

## Methods and formulas

The autocovariance function for ARFIMA models is described in [Methods and formulas](#) of [\[TS\] arfima](#). The autocovariance function for ARIMA models is obtained by setting the fractional difference parameter to zero.

[Box et al. \(2016\)](#) provide excellent descriptions of the autocovariance function for ARIMA and seasonal ARIMA models. [Palma \(2007\)](#) provides an excellent summary of the autocovariance function for ARFIMA models.

## References

- Box, G. E. P., G. M. Jenkins, G. C. Reinsel, and G. M. Ljung. 2016. *Time Series Analysis: Forecasting and Control*. 5th ed. Hoboken, NJ: Wiley.
- Palma, W. 2007. *Long-Memory Time Series: Theory and Methods*. Hoboken, NJ: Wiley.

## Also see

[\[TS\] arfima](#) — Autoregressive fractionally integrated moving-average models

[\[TS\] arima](#) — ARIMA, ARMAX, and other dynamic regression models

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.



For suggested citations, see the FAQ on [citing Stata documentation](#).