xtfrontier postestimation — Postestimation tools for xtfrontier

Postestimation commands predict margins Remarks and examples
Methods and formulas Also see

Postestimation commands

The following postestimation commands are available after `xtfrontier`:

Command	Description
`contrast`	contrasts and ANOVA-style joint tests of parameters
`estat ic`	Akaike's, consistent Akaike's, corrected Akaike's, and Schwarz's Bayesian information criteria (AIC, CAIC, AICc, and BIC, respectively)
`estat summarize`	summary statistics for the estimation sample
`estat vce`	variance–covariance matrix of the estimators (VCE)
`estimates`	cataloging estimation results
`etable`	table of estimation results
`forecast`	dynamic forecasts and simulations
`hausman`	Hausman's specification test
`lincom`	point estimates, standard errors, testing, and inference for linear combinations of parameters
`lrtest`	likelihood-ratio test
`margins`	marginal means, predictive margins, marginal effects, and average marginal effects
`marginsplot`	graph the results from margins (profile plots, interaction plots, etc.)
`nlcom`	point estimates, standard errors, testing, and inference for nonlinear combinations of parameters
`predict`	linear predictions and their SEs, technical efficiency
`predictnl`	point estimates, standard errors, testing, and inference for generalized predictions
`pwcompare`	pairwise comparisons of parameters
`test`	Wald tests of simple and composite linear hypotheses
`testnl`	Wald tests of nonlinear hypotheses

predict

Description for predict

`predict` creates a new variable containing predictions such as linear predictions, standard errors, and technical efficiencies.

Menu for predict

Statistics > Postestimation

Syntax for predict

`predict` [*type*] *newvar* [*if*] [*in*] [, *statistic*]

statistic	Description
Main	
`xb`	linear prediction; the default
`stdp`	standard error of the linear prediction
`u`	minus the natural log of the technical efficiency via $E(u_{it} \mid \epsilon_{it})$
`m`	minus the natural log of the technical efficiency via $M(u_{it} \mid \epsilon_{it})$
`te`	the technical efficiency via $E\{\exp(-su_{it}) \mid \epsilon_{it}\}$

where

$$s = \begin{cases} 1, & \text{for production functions} \\ -1, & \text{for cost functions} \end{cases}$$

Options for predict

Main

`xb`, the default, calculates the linear prediction.

`stdp` calculates the standard error of the linear prediction.

`u` produces estimates of minus the natural log of the technical efficiency via $E(u_{it} \mid \epsilon_{it})$.

`m` produces estimates of minus the natural log of the technical efficiency via the mode, $M(u_{it} \mid \epsilon_{it})$.

`te` produces estimates of the technical efficiency via $E\{\exp(-su_{it}) \mid \epsilon_{it}\}$.

margins

Description for margins

`margins` estimates margins of response for linear predictions.

Menu for margins

Statistics > Postestimation

Syntax for margins

`margins` [*marginlist*] [, *options*]

`margins` [*marginlist*] , `predict(`*statistic* ...`)` [*options*]

statistic	Description
`xb`	linear prediction; the default
`stdp`	not allowed with `margins`
`u`	not allowed with `margins`
`m`	not allowed with `margins`
`te`	not allowed with `margins`

Statistics not allowed with `margins` are functions of stochastic quantities other than `e(b)`.

For the full syntax, see [R] **margins**.

Remarks and examples

▷ Example 1

A production function exhibits *constant returns to scale* if doubling the amount of each input results in a doubling in the quantity produced. When the production function is linear in logs, constant returns to scale implies that the sum of the coefficients on the inputs is one. In example 2 of [XT] **xtfrontier**, we fit a time-varying decay model. Here we test whether the estimated production function exhibits constant returns:

```
. use https://www.stata-press.com/data/r19/xtfrontier1
. xtfrontier lnwidgets lnmachines lnworkers, tvd
  (output omitted)
. test lnmachines + lnworkers = 1
 ( 1)  [lnwidgets]lnmachines + [lnwidgets]lnworkers = 1
           chi2(  1) =  331.55
         Prob > chi2 =    0.0000
```

The test statistic is highly significant, so we reject the null hypothesis and conclude that this production function does not exhibit constant returns to scale.

The previous Wald χ^2 test indicated that the sum of the coefficients does not equal one. An alternative is to use `lincom` to compute the sum explicitly:

```
. lincom lnmachines + lnworkers
 ( 1)  [lnwidgets]lnmachines + [lnwidgets]lnworkers = 0
```

lnwidgets	Coefficient	Std. err.	z	P>|z|	[95% conf.	interval]
(1)	.5849967	.0227918	25.67	0.000	.5403256	.6296677

The sum of the coefficients is significantly less than one, so this production function exhibits *decreasing returns to scale*. If we doubled the number of machines and workers, we would obtain less than twice as much output.

◁

Methods and formulas

Continuing from the *Methods and formulas* section of [XT] **xtfrontier**, estimates for u_{it} can be obtained from the mean or the mode of the conditional distribution $f(u|\epsilon)$.

$$E\left(u_{it} \mid \epsilon_{it}\right) = \tilde{\mu}_i + \tilde{\sigma}_i \left\{ \frac{\phi\left(-\tilde{\mu}_i/\tilde{\sigma}_i\right)}{1-\Phi\left(-\tilde{\mu}_i/\tilde{\sigma}_i\right)} \right\}$$

$$M\left(u_{it} \mid \epsilon_{it}\right) = \begin{cases} -\tilde{\mu}_i, & \text{if } \tilde{\mu}_i >= 0 \\ 0, & \text{otherwise} \end{cases}$$

where

$$\tilde{\mu}_i = \frac{\mu\sigma_v^2 - s\sum_{t=1}^{T_i} \eta_{it}\epsilon_{it}\sigma_u^2}{\sigma_v^2 + \sum_{t=1}^{T_i} \eta_{it}^2\sigma_u^2}$$

$$\tilde{\sigma}_i^2 = \frac{\sigma_v^2\sigma_u^2}{\sigma_v^2 + \sum_{t=1}^{T_i} \eta_{it}^2\sigma_u^2}$$

These estimates can be obtained from `predict` *newvar*`, u` and `predict` *newvar*`, m`, respectively, and are calculated by plugging in the estimated parameters.

`predict` *newvar*`, te` produces estimates of the technical-efficiency term. These estimates are obtained from

$$E\left\{\exp(-su_{it}) \mid \epsilon_{it}\right\} = \left[\frac{1-\Phi\left\{s\eta_{it}\tilde{\sigma}_i - (\tilde{\mu}_i/\,\tilde{\sigma}_i)\right\}}{1-\Phi\left(-\tilde{\mu}_i/\,\tilde{\sigma}_i\right)}\right] \exp\left(-s\eta_{it}\tilde{\mu}_i + \frac{1}{2}\eta_{it}^2\tilde{\sigma}_i^2\right)$$

Replacing $\eta_{it} = 1$ and $\eta = 0$ in these formulas produces the formulas for the time-invariant models.

Also see

[XT] **xtfrontier** — Stochastic frontier models for panel data

[U] 20 Estimation and postestimation commands

Stata, Stata Press, Mata, NetCourse, and NetCourseNow are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow is a trademark of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on citing Stata documentation.