

Postestimation commands

predict

margins

Also see

Postestimation commands

The following postestimation commands are available after `xtivreg`:

Command	Description
* <code>contrast</code>	contrasts and ANOVA-style joint tests of estimates
<code>estat summarize</code>	summary statistics for the estimation sample
<code>estat vce</code>	variance–covariance matrix of the estimators (VCE)
<code>estimates</code>	cataloging estimation results
<code>etable</code>	table of estimation results
<code>forecast</code>	dynamic forecasts and simulations
<code>hausman</code>	Hausman’s specification test
<code>lincom</code>	point estimates, standard errors, testing, and inference for linear combinations of coefficients
<code>margins</code>	marginal means, predictive margins, marginal effects, and average marginal effects
<code>marginsplot</code>	graph the results from margins (profile plots, interaction plots, etc.)
<code>nlcom</code>	point estimates, standard errors, testing, and inference for nonlinear combinations of coefficients
<code>predict</code>	linear predictions, first-differenced error components
<code>predictnl</code>	point estimates, standard errors, testing, and inference for generalized predictions
* <code>pwcompare</code>	pairwise comparisons of estimates
<code>test</code>	Wald tests of simple and composite linear hypotheses
<code>testnl</code>	Wald tests of nonlinear hypotheses

* `contrast` and `pwcompare` are not appropriate after `xtivreg, fd`.

predict

Description for predict

`predict` creates a new variable containing predictions such as fitted values and predictions.

Menu for predict

Statistics > Postestimation

Syntax for predict

For all but the first-differenced estimator

```
predict [type] newvar [if] [in] [ , statistic ]
```

First-differenced estimator

```
predict [type] newvar [if] [in] [ , FD_statistic ]
```

statistic	Description
Main	
xb	$\mathbf{Z}_{it}\hat{\boldsymbol{\delta}}$, fitted values; the default
ue	$\hat{\mu}_i + \hat{\nu}_{it}$, the combined residual
*xbu	$\mathbf{Z}_{it}\hat{\boldsymbol{\delta}} + \hat{\mu}_i$, prediction including effect
*u	$\hat{\mu}_i$, the fixed- or random-error component
*e	$\hat{\nu}_{it}$, the overall error component

Unstarred statistics are available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample. Starred statistics are calculated only for the estimation sample, even when `if e(sample)` is not specified.

FD_statistic	Description
Main	
xb	$\mathbf{x}_j\mathbf{b}$, fitted values for the first-differenced model; the default
e	$e_{it} - e_{it-1}$, the first-differenced overall error component

These statistics are available both in and out of sample; type `predict ... if e(sample) ...` if wanted only for the estimation sample.

Options for predict

Main

`xb`, the default, calculates the linear prediction, that is, $\mathbf{Z}_{it}\hat{\boldsymbol{\delta}}$.
`ue` calculates the prediction of $\hat{\mu}_i + \hat{\nu}_{it}$. This is not available after the first-differenced model.

- xbu calculates the prediction of $\mathbf{Z}_{it}\hat{\boldsymbol{\delta}} + \hat{\mu}_i$, the prediction including the fixed or random component. This is not available after the first-differenced model.
- u calculates the prediction of $\hat{\mu}_i$, the estimated fixed or random effect. This is not available after the first-differenced model.
- e calculates the prediction of \hat{v}_{it} .

margins

Description for margins

`margins` estimates margins of response for fitted values.

Menu for margins

Statistics > Postestimation

Syntax for margins

```
margins [marginlist] [ , options ]
margins [marginlist] , predict(statistic ...) [options]
```

For all but the first-differenced estimator

<i>statistic</i>	Description
xb	$\mathbf{Z}_{it}\hat{\boldsymbol{\delta}}$, fitted values; the default
ue	not allowed with <code>margins</code>
xbu	not allowed with <code>margins</code>
u	not allowed with <code>margins</code>
e	not allowed with <code>margins</code>

First-differenced estimator

<i>statistic</i>	Description
xb	$\mathbf{x}_j\mathbf{b}$, fitted values for the first-differenced model; the default
e	not allowed with <code>margins</code>

Statistics not allowed with `margins` are functions of stochastic quantities other than `e(b)`.

For the full syntax, see [R] [margins](#).

Also see

[XT] [xtivreg](#) — Instrumental variables and two-stage least squares for panel-data models

[U] [20 Estimation and postestimation commands](#)

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2023 StataCorp LLC, College Station, TX, USA. All rights reserved.

