

[Description](#)

[Syntax](#)

[Remarks and examples](#)

[Quick start](#)

[Options for graph by panel](#)

[References](#)

[Menu](#)

[Options for overlaid panels](#)

[Also see](#)

## Description

`xtline` draws line plots for panel data.

## Quick start

Matrix of line plots of `y` against time variable `tvar` with panel identifier `pvar`

```
xtline y, i(pvar) t(tvar)
```

Same as above, but using `xtset` data

```
xtline y
```

Same as above, but overlay line plots for each panel identifier `pvar`

```
xtline y, overlay
```

Add “My Title” to graph showing a matrix of line plots

```
xtline y, byopts(title(My Title))
```

Add “My Title” to graph of overlaid line plots

```
xtline y, overlay title(My Title)
```

## Menu

Statistics > Longitudinal/panel data > Line plots

## Syntax

Graph by panel

```
xtline varlist [if] [in] [, panel_options]
```

Overlaid panels

```
xtline varname [if] [in], overlay [overlaid_options]
```

<i>panel_options</i>	Description
Main	
<i>i</i> ( <i>varname</i> <sub><i>i</i></sub> )	use <i>varname</i> <sub><i>i</i></sub> as the panel ID variable
<i>t</i> ( <i>varname</i> <sub><i>t</i></sub> )	use <i>varname</i> <sub><i>t</i></sub> as the time variable
Plot	
<i>cline_options</i>	affect rendition of the plotted points connected by lines
Add plots	
addplot( <i>plot</i> )	add other plots to the generated graph
Y axis, Time axis, Titles, Legend, Overall	
<i>twoway_options</i>	any options other than by() documented in [G-3] <i>twoway_options</i>
<i>byopts</i> ( <i>byopts</i> )	affect appearance of the combined graph

<i>overlaid_options</i>	Description
Main	
<u>o</u> verlay	overlay each panel on the same graph
<i>i</i> ( <i>varname</i> <sub><i>i</i></sub> )	use <i>varname</i> <sub><i>i</i></sub> as the panel ID variable
<i>t</i> ( <i>varname</i> <sub><i>t</i></sub> )	use <i>varname</i> <sub><i>t</i></sub> as the time variable
Plots	
<u>plot</u> #opts( <i>cline_options</i> )	affect rendition of the # panel line
Add plots	
addplot( <i>plot</i> )	add other plots to the generated graph
Y axis, Time axis, Titles, Legend, Overall	
<i>twoway_options</i>	any options other than by() documented in [G-3] <i>twoway_options</i>

A panel variable and a time variable must be specified. Use xtset (see [XT] [xtset](#)) or specify the *i*() and *t*() options. The *t*() option allows noninteger values for the time variable, whereas xtset does not.

## Options for graph by panel

### Main

$i(\text{varname}_i)$  and  $t(\text{varname}_t)$  override the panel settings from `xtset`; see [XT] `xtset`.  $\text{varname}_i$  is allowed to be a string variable.  $\text{varname}_t$  can take on noninteger values and have repeated values within panel. That is to say, it can be any numeric variable that you would like to specify for the  $x$ -dimension of the graph. It is an error to specify `i()` without `t()` and vice versa.

### Plot

`cline_options` affect the rendition of the plotted points connected by lines; see [G-3] `cline_options`.

### Add plots

`addplot(plot)` provides a way to add other plots to the generated graph; see [G-3] `addplot_option`.

### Y axis, Time axis, Titles, Legend, Overall

`twoway_options` are any of the options documented in [G-3] `twoway_options`, excluding `by()`. These include options for titling the graph (see [G-3] `title_options`) and for saving the graph to disk (see [G-3] `saving_option`).

`byopts(byopts)` allows all the options documented in [G-3] `by_option`. These options affect the appearance of the `by`-graph. `byopts()` may not be combined with `overlay`.

## Options for overlaid panels

### Main

`overlay` causes the plot from each panel to be overlaid on the same graph. The default is to generate plots by panel. This option may not be combined with `byopts()` or be specified when there are multiple variables in `varlist`.

$i(\text{varname}_i)$  and  $t(\text{varname}_t)$  override the panel settings from `xtset`; see [XT] `xtset`.  $\text{varname}_i$  is allowed to be a string variable.  $\text{varname}_t$  can take on noninteger values and have repeated values within panel. That is to say, it can be any numeric variable that you would like to specify for the  $x$ -dimension of the graph. It is an error to specify `i()` without `t()` and vice versa.

### Plots

`plot#opts(cline_options)` affect the rendition of the  $\#$ th panel (in sorted order). The `cline_options` can affect whether and how the points are connected; see [G-3] `cline_options`.

### Add plots

`addplot(plot)` provides a way to add other plots to the generated graph; see [G-3] `addplot_option`.

### Y axis, Time axis, Titles, Legend, Overall


`twoway_options` are any of the options documented in [G-3] `twoway_options`, excluding `by()`. These include options for titling the graph (see [G-3] `title_options`) and for saving the graph to disk (see [G-3] `saving_option`).

## Remarks and examples

### ► Example 1


Suppose that Tess, Sam, and Arnold kept a calorie log for an entire calendar year. At the end of the year, if they pooled their data together, they would have a dataset (for example, `xtline1.dta`) that contains the number of calories each of them consumed for 365 days. They could then use `xtset` to identify the date variable and treat each person as a panel and use `xtline` to plot the calories versus time for each person separately.

```
. use https://www.stata-press.com/data/r19/xtline1
(Simulated data of calories consumed for 365 days)
. xtset person day
Panel variable: person (strongly balanced)
Time variable: day, 01jan2002 to 31dec2002
Delta: 1 day
. xtline calories, tlabel(#3)
```



Specify the `overlay` option so that the values are plotted on the same graph to provide a better comparison among Tess, Sam, and Arnold.

```
. xtline calories, overlay
```



◀

## References

- Chatfield, M. D. 2018. [Graphing each individual's data over time](#). *Stata Journal* 18: 503–516.
- Gallup, J. L. 2020. [Added-variable plots for panel-data estimation](#). *Stata Journal* 20: 30–50.

## Also see

- [XT] [xtset](#) — Declare data to be panel data
- [G-2] [graph twoway](#) — Two-way graphs
- [TS] [tsline](#) — Time-series line plots

Stata, Stata Press, and Mata are registered trademarks of StataCorp LLC. Stata and Stata Press are registered trademarks with the World Intellectual Property Organization of the United Nations. StataNow and NetCourseNow are trademarks of StataCorp LLC. Other brand and product names are registered trademarks or trademarks of their respective companies. Copyright © 1985–2025 StataCorp LLC, College Station, TX, USA. All rights reserved.

For suggested citations, see the FAQ on [citing Stata documentation](#).

