

biprobit — Bivariate probit regression[Syntax](#)[Remarks and examples](#)[Also see](#)[Menu](#)[Stored results](#)[Description](#)[Methods and formulas](#)[Options](#)[References](#)

Syntax

*Bivariate probit regression***biprobit** *depvar₁* *depvar₂* [*indepvars*] [*if*] [*in*] [*weight*] [, *options*]*Seemingly unrelated bivariate probit regression***biprobit** *equation₁* *equation₂* [*if*] [*in*] [*weight*] [, *su_options*]where *equation₁* and *equation₂* are specified as([*eqname*:] *depvar* [=] [*indepvars*] [, noconstant offset(*varname*)])

<i>options</i>	Description
Model	
<u>noconstant</u>	suppress constant term
<u>partial</u>	fit partial observability model
<u>offset1</u> (<i>varname</i>)	offset variable for first equation
<u>offset2</u> (<i>varname</i>)	offset variable for second equation
<u>constraints</u> (<i>constraints</i>)	apply specified linear constraints
<u>collinear</u>	keep collinear variables
SE/Robust	
<u>vce</u> (<i>vcetype</i>)	<i>vcetype</i> may be <u>oim</u> , <u>robust</u> , <u>cluster</u> <i>clustvar</i> , <u>opg</u> , <u>bootstrap</u> , or <u>jackknife</u>
Reporting	
<u>level</u> (#)	set confidence level; default is <u>level</u> (95)
<u>noskip</u>	perform likelihood-ratio test
<u>nocnsreport</u>	do not display constraints
<u>display_options</u>	control column formats, row spacing, line width, display of omitted variables and base and empty cells, and factor-variable labeling
Maximization	
<u>maximize_options</u>	control the maximization process; seldom used
<u>coeflegend</u>	display legend instead of statistics

<i>su_options</i>	Description
<hr/>	
Model	
<u>partial</u>	fit partial observability model
<u>constraints</u> (<i>constraints</i>)	apply specified linear constraints
<u>collinear</u>	keep collinear variables
SE/Robust	
<u>vce</u> (<i>vcetype</i>)	<i>vcetype</i> may be <u>oim</u> , <u>robust</u> , <u>cluster</u> <i>clustvar</i> , <u>opg</u> , <u>bootstrap</u> , or <u>jackknife</u>
Reporting	
<u>level</u> (#)	set confidence level; default is <u>level</u> (95)
<u>noskip</u>	perform likelihood-ratio test
<u>nocnsreport</u>	do not display constraints
<u>display_options</u>	control column formats, row spacing, line width, display of omitted variables and base and empty cells, and factor-variable labeling
Maximization	
<u>maximize_options</u>	control the maximization process; seldom used
<u>coeflegend</u>	display legend instead of statistics

indepvars may contain factor variables; see [U] 11.4.3 Factor variables.

depvar1, *depvar2*, *indepvars*, and *depvar* may contain time-series operators; see [U] 11.4.4 Time-series varlists.

bootstrap, by, fp, jackknife, rolling, statsby, and svy are allowed; see [U] 11.1.10 Prefix commands.

Weights are not allowed with the bootstrap prefix; see [R] bootstrap.

vce(), noskip, and weights are not allowed with the svy prefix; see [SVY] svy.

pweights, fweights, and iweights are allowed; see [U] 11.1.6 weight.

coeflegend does not appear in the dialog box.

See [U] 20 Estimation and postestimation commands for more capabilities of estimation commands.

Menu

biprobit

Statistics > Binary outcomes > Bivariate probit regression

seemingly unrelated biprobit

Statistics > Binary outcomes > Seemingly unrelated bivariate probit regression

Description

biprobit fits maximum-likelihood two-equation probit models—either a bivariate probit or a seemingly unrelated probit (limited to two equations).

Options

Model

`noconstant`; see [R] estimation options.

`partial` specifies that the partial observability model be fit. This particular model commonly has poor convergence properties, so we recommend that you use the `difficult` option if you want to fit the Poirier partial observability model; see [R] maximize.

This model computes the product of the two dependent variables so that you do not have to replace each with the product.

`offset1(varname)`, `offset2(varname)`, `constraints(constraints)`, `collinear`; see [R] estimation options.

SE/Robust

`vce(vcetype)` specifies the type of standard error reported, which includes types that are derived from asymptotic theory (`oim`, `opg`), that are robust to some kinds of misspecification (`robust`), that allow for intragroup correlation (`cluster clustvar`), and that use bootstrap or jackknife methods (`bootstrap`, `jackknife`); see [R] vce_option.

Reporting

`level(#)`; see [R] estimation options.

`noskip` specifies that a full maximum-likelihood model with only a constant for the regression equation be fit. This model is not displayed but is used as the base model to compute a likelihood-ratio test for the model test statistic displayed in the estimation header. By default, the overall model test statistic is an asymptotically equivalent Wald test of all the parameters in the regression equation being zero (except the constant). For many models, this option can substantially increase estimation time.

`nocnsreport`; see [R] estimation options.

`display_options`: `noomitted`, `vsquish`, `noemptycells`, `baselevels`, `allbaselevels`, `nofvlabel`, `fvwrap(#)`, `fvwrapon(style)`, `cformat(%fmt)`, `pformat(%fmt)`, `sformat(%fmt)`, and `nolstretch`; see [R] estimation options.

Maximization

`maximize_options`: `difficult`, `technique(algorithm_spec)`, `iterate(#)`, `[no]log`, `trace`, `gradient`, `showstep`, `hessian`, `showtolerance`, `tolerance(#)`, `ltolerance(#)`, `rtolerance(#)`, `nonrtolerance`, and `from(init_specs)`; see [R] maximize. These options are seldom used.

Setting the optimization type to `technique(bhhh)` resets the default `vcetype` to `vce(opg)`.

The following option is available with `biprobit` but is not shown in the dialog box:

`coeflegend`; see [R] estimation options.

[stata.com](#)

Remarks and examples

For a good introduction to the bivariate probit models, see Greene (2012, 738–752) and Pindyck and Rubinfeld (1998). Poirier (1980) explains the partial observability model. Van de Ven and Van Pragg (1981) explain the probit model with sample selection; see [R] heckprobit for details.

▷ Example 1

We use the data from Pindyck and Rubinfeld (1998, 332). In this dataset, the variables are whether children attend private school (`private`), number of years the family has been at the present residence (`years`), log of property tax (`logptax`), log of income (`loginc`), and whether the head of the household voted for an increase in property taxes (`vote`).

We wish to model the bivariate outcomes of whether children attend private school and whether the head of the household voted for an increase in property tax based on the other covariates.

```
. use http://www.stata-press.com/data/r13/school
. biprobit private vote years logptax loginc
```

Fitting comparison equation 1:

```
Iteration 0:  log likelihood = -31.967097
Iteration 1:  log likelihood = -31.452424
Iteration 2:  log likelihood = -31.448958
Iteration 3:  log likelihood = -31.448958
```

Fitting comparison equation 2:

```
Iteration 0:  log likelihood = -63.036914
Iteration 1:  log likelihood = -58.534843
Iteration 2:  log likelihood = -58.497292
Iteration 3:  log likelihood = -58.497288
Comparison:  log likelihood = -89.946246
```

Fitting full model:

```
Iteration 0:  log likelihood = -89.946246
Iteration 1:  log likelihood = -89.258897
Iteration 2:  log likelihood = -89.254028
Iteration 3:  log likelihood = -89.254028
```

Bivariate probit regression	Number of obs	=	95
	Wald chi2(6)	=	9.59
Log likelihood = -89.254028	Prob > chi2	=	0.1431

	Coef.	Std. Err.	z	P> z	[95% Conf. Interval]
private					
years	-.0118884	.0256778	-0.46	0.643	-.0622159 .0384391
logptax	-.1066962	.6669782	-0.16	0.873	-1.413949 1.200557
loginc	.3762037	.5306484	0.71	0.478	-.663848 1.416255
_cons	-4.184694	4.837817	-0.86	0.387	-13.66664 5.297253
vote					
years	-.0168561	.0147834	-1.14	0.254	-.0458309 .0121188
logptax	-1.288707	.5752266	-2.24	0.025	-2.416131 -.1612839
loginc	.998286	.4403565	2.27	0.023	.1352031 1.861369
_cons	-.5360573	4.068509	-0.13	0.895	-8.510188 7.438073
/athrho	-.2764525	.2412099	-1.15	0.252	-.7492153 .1963102
rho	-.2696186	.2236753			-.6346806 .1938267

Likelihood-ratio test of rho=0: chi2(1) = 1.38444 Prob > chi2 = 0.2393

The output shows several iteration logs. The first iteration log corresponds to running the univariate probit model for the first equation, and the second log corresponds to running the univariate probit for the second model. If $\rho = 0$, the sum of the log likelihoods from these two models will equal the log likelihood of the bivariate probit model; this sum is printed in the iteration log as the comparison log likelihood.

The final iteration log is for fitting the full bivariate probit model. A likelihood-ratio test of the log likelihood for this model and the comparison log likelihood is presented at the end of the output. If we had specified the `vce(robust)` option, this test would be presented as a Wald test instead of as a likelihood-ratio test.

We could have fit the same model by using the seemingly unrelated syntax as

```
. biprobit (private=years logptax loginc) (vote=years logptax loginc)
```



Stored results

`biprobit` stores the following in `e()`:

Scalars

<code>e(N)</code>	number of observations
<code>e(k)</code>	number of parameters
<code>e(k_eq)</code>	number of equations in <code>e(b)</code>
<code>e(k_aux)</code>	number of auxiliary parameters
<code>e(k_eq_model)</code>	number of equations in overall model test
<code>e(k_dv)</code>	number of dependent variables
<code>e(df_m)</code>	model degrees of freedom
<code>e(l1)</code>	log likelihood
<code>e(l1_0)</code>	log likelihood, constant-only model (<code>noskip</code> only)
<code>e(l1_c)</code>	log likelihood, comparison model
<code>e(N_clust)</code>	number of clusters
<code>e(chi2)</code>	χ^2
<code>e(chi2_c)</code>	χ^2 for comparison test
<code>e(p)</code>	significance
<code>e(rho)</code>	ρ
<code>e(rank)</code>	rank of <code>e(V)</code>
<code>e(rank0)</code>	rank of <code>e(V)</code> for constant-only model
<code>e(ic)</code>	number of iterations
<code>e(rc)</code>	return code
<code>e(converged)</code>	1 if converged, 0 otherwise

Macros

<code>e(cmd)</code>	<code>biprobit</code>
<code>e(cmdline)</code>	command as typed
<code>e(depvar)</code>	names of dependent variables
<code>e(wtype)</code>	weight type
<code>e(wexp)</code>	weight expression
<code>e(title)</code>	title in estimation output
<code>e(clustvar)</code>	name of cluster variable
<code>e(offset1)</code>	offset for first equation
<code>e(offset2)</code>	offset for second equation
<code>e(chi2type)</code>	Wald or LR; type of model χ^2 test
<code>e(chi2_ct)</code>	Wald or LR; type of model χ^2 test corresponding to <code>e(chi2_c)</code>
<code>e(vce)</code>	<code>vcetype</code> specified in <code>vce()</code>
<code>e(vcetype)</code>	title used to label Std. Err.
<code>e(opt)</code>	type of optimization
<code>e(which)</code>	<code>max</code> or <code>min</code> ; whether optimizer is to perform maximization or minimization
<code>e(ml_method)</code>	type of <code>ml</code> method
<code>e(user)</code>	name of likelihood-evaluator program
<code>e(technique)</code>	maximization technique
<code>e(properties)</code>	<code>b V</code>
<code>d(predict)</code>	program used to implement <code>predict</code>
<code>e(asbalanced)</code>	factor variables <code>fvset</code> as <code>asbalanced</code>
<code>e(asobserved)</code>	factor variables <code>fvset</code> as <code>asobserved</code>

Matrices

<code>e(b)</code>	coefficient vector
<code>e(Cns)</code>	constraints matrix
<code>e(ilog)</code>	iteration log (up to 20 iterations)
<code>e(gradient)</code>	gradient vector
<code>e(V)</code>	variance-covariance matrix of the estimators
<code>e(V_modelbased)</code>	model-based variance

Functions

<code>e(sample)</code>	marks estimation sample
------------------------	-------------------------

Methods and formulas

The log likelihood, $\ln L$, is given by

$$\begin{aligned}\xi_j^\beta &= x_j \beta + \text{offset}_j^\beta \\ \xi_j^\gamma &= z_j \gamma + \text{offset}_j^\gamma \\ q_{1j} &= \begin{cases} 1 & \text{if } y_{1j} \neq 0 \\ -1 & \text{otherwise} \end{cases} \\ q_{2j} &= \begin{cases} 1 & \text{if } y_{2j} \neq 0 \\ -1 & \text{otherwise} \end{cases} \\ \rho_j^* &= q_{1j} q_{2j} \rho \\ \ln L &= \sum_{j=1}^n w_j \ln \Phi_2(q_{1j} \xi_j^\beta, q_{2j} \xi_j^\gamma, \rho_j^*)\end{aligned}$$

where $\Phi_2()$ is the cumulative bivariate normal distribution function (with mean $[0 \ 0]'$) and w_j is an optional weight for observation j . This derivation assumes that

$$\begin{aligned}y_{1j}^* &= x_j \beta + \epsilon_{1j} + \text{offset}_j^\beta \\ y_{2j}^* &= z_j \gamma + \epsilon_{2j} + \text{offset}_j^\gamma \\ E(\epsilon_1) &= E(\epsilon_2) = 0 \\ \text{Var}(\epsilon_1) &= \text{Var}(\epsilon_2) = 1 \\ \text{Cov}(\epsilon_1, \epsilon_2) &= \rho\end{aligned}$$

where y_{1j}^* and y_{2j}^* are the unobserved latent variables; instead, we observe only $y_{ij} = 1$ if $y_{ij}^* > 0$ and $y_{ij} = 0$ otherwise (for $i = 1, 2$).

In the maximum likelihood estimation, ρ is not directly estimated, but $\text{atanh } \rho$ is

$$\text{atanh } \rho = \frac{1}{2} \ln \left(\frac{1+\rho}{1-\rho} \right)$$

From the form of the likelihood, if $\rho = 0$, then the log likelihood for the bivariate probit models is equal to the sum of the log likelihoods of the two univariate probit models. A likelihood-ratio test may therefore be performed by comparing the likelihood of the full bivariate model with the sum of the log likelihoods for the univariate probit models.

This command supports the Huber/White/sandwich estimator of the variance and its clustered version using `vce(robust)` and `vce(cluster clustvar)`, respectively. See [P] `_robust`, particularly *Maximum likelihood estimators* and *Methods and formulas*.

`biprobit` also supports estimation with survey data. For details on VCEs with survey data, see [SVY] `variance estimation`.

References

- De Luca, G. 2008. SNP and SML estimation of univariate and bivariate binary-choice models. *Stata Journal* 8: 190–220.
- Greene, W. H. 2012. *Econometric Analysis*. 7th ed. Upper Saddle River, NJ: Prentice Hall.
- Hardin, J. W. 1996. sg61: Bivariate probit models. *Stata Technical Bulletin* 33: 15–20. Reprinted in *Stata Technical Bulletin Reprints*, vol. 6, pp. 152–158. College Station, TX: Stata Press.
- Heckman, J. 1979. Sample selection bias as a specification error. *Econometrica* 47: 153–161.
- Lokshin, M., and Z. Sajaia. 2011. Impact of interventions on discrete outcomes: Maximum likelihood estimation of the binary choice models with binary endogenous regressors. *Stata Journal* 11: 368–385.
- Pindyck, R. S., and D. L. Rubinfeld. 1998. *Econometric Models and Economic Forecasts*. 4th ed. New York: McGraw–Hill.
- Poirier, D. J. 1980. Partial observability in bivariate probit models. *Journal of Econometrics* 12: 209–217.
- Van de Ven, W. P. M. M., and B. M. S. Van Pragg. 1981. The demand for deductibles in private health insurance: A probit model with sample selection. *Journal of Econometrics* 17: 229–252.

Also see

- [R] **biprobit postestimation** — Postestimation tools for biprobit
- [R] **mprobit** — Multinomial probit regression
- [R] **probit** — Probit regression
- [SVY] **svy estimation** — Estimation commands for survey data
- [U] **20 Estimation and postestimation commands**